

# Package: biomod2 (via r-universe)

October 9, 2026

**Type** Package

**Title** Ensemble Platform for Species Distribution Modeling

**Version** 4.3-4-8

**Date** 2026-10-09

**BugReports** <https://github.com/biomodhub/biomod2/issues>

**URL** <https://biomodhub.github.io/biomod2/>

**Description** Functions for species distribution modelling, to calibrate, evaluate, and project species-environment relationships across space and time using multiple modelling algorithms and ensemble forecasting. It accommodates diverse ecological data types (presence-only, presence-absence, counts, multi-class abundance, or relative/absolute abundance) within a unified modelling workflow which includes cross-validation schemes, pseudo-absence selection strategies, expanded model parametrization options, a dozen of algorithms, and tools for exploring and visualizing outputs.

**Depends** R (>= 4.1)

**Imports** stats, utils, methods, terra (>= 1.6-33), sp, reshape, reshape2, abind, foreach, ggplot2, gbm (>= 2.1.3), rpart, MASS, pROC (>= 1.15.0), PresenceAbsence, dplyr, rlang, scales

**Suggests** Hmisc, gam, mgcv, earth, maxnet, mda, nnet, randomForest, xgboost (>= 3.1.3.1), cito, torch, car, caret, dismo, ENMeval, doParallel, raster, ggpubr, testthat, knitr, markdown, rmarkdown, tidyterra, ggtext, patchwork, kableExtra, DT, R.utils, paletteer, viridis

**License** GPL-3

**Encoding** UTF-8

**VignetteBuilder** knitr

**Collate** 'biomod2-package.R' 'biomod2\_globalVariables.R'  
'biomod2\_classes\_0.R' 'biomod2\_classes\_1.R'  
'biomod2\_classes\_2.R' 'biomod2\_classes\_3.R'

```
'biomod2_classes_4.R' 'biomod2_classes_5.R'
'biomod2_internal.R' 'biomod2_data.R'
'BIOMOD_EnsembleForecasting.R' 'BIOMOD_EnsembleModeling.R'
'BIOMOD_FormatingData.R' 'BIOMOD_LoadModels.R'
'BIOMOD_Modeling.R' 'BIOMOD_Projection.R' 'BIOMOD_RangeSize.R'
'BIOMOD_Report.R' 'DEPRECATED.R' 'bm_BinaryTransformation.R'
'bm_CrossValidation.R' 'bm_FindOptimStat.R' 'bm_MakeFormula.R'
'bm_ModelingOptions.R' 'bm_ModelAnalysis.R'
'bm_PlotEvalBoxplot.R' 'bm_PlotEvalMean.R' 'bm_PlotRangeSize.R'
'bm_PlotResponseCurves.R' 'bm_PlotVarImpBoxplot.R'
'bm_PseudoAbsences.R' 'bm_RunModelsLoop.R' 'bm_RangeSize.R'
'bm_SRE.R' 'bm_SampleBinaryVector.R' 'bm_SampleFactorLevels.R'
'bm_Tuning.R' 'bm_VariablesImportance.R' 'zzz.R'
```

**LazyData** true

**Config/roxygen2/version** 8.0.0

**Config/pak/sysreqs** libgdal-dev gdal-bin libgeos-dev libicu-dev libproj-dev libsqlite3-dev

**Repository** <https://biomodhub.r-universe.dev>

**Date/Publication** 2026-10-09 09:40:21 UTC

**RemoteUrl** <https://github.com/biomodhub/biomod2>

**RemoteRef** HEAD

**RemoteSha** 11a4c0fe417dc9716f8f96d0575fe41d38308ea8

## Contents

|                                      |    |
|--------------------------------------|----|
| bioclim_current . . . . .            | 3  |
| bioclim_future . . . . .             | 4  |
| BIOMOD.ensemble.models.out . . . . . | 4  |
| BIOMOD.formated.data . . . . .       | 7  |
| BIOMOD.formated.data.PA . . . . .    | 11 |
| BIOMOD.models.options . . . . .      | 16 |
| BIOMOD.models.out . . . . .          | 17 |
| BIOMOD.options.dataset . . . . .     | 19 |
| BIOMOD.options.default . . . . .     | 21 |
| BIOMOD.projection.out . . . . .      | 22 |
| BIOMOD.rangesize.out . . . . .       | 25 |
| BIOMOD.stored.data . . . . .         | 26 |
| BIOMOD_EnsembleForecasting . . . . . | 27 |
| BIOMOD_EnsembleModeling . . . . .    | 31 |
| BIOMOD_FormatingData . . . . .       | 38 |
| BIOMOD_LoadModels . . . . .          | 45 |
| BIOMOD_Modeling . . . . .            | 48 |
| BIOMOD_Projection . . . . .          | 54 |
| BIOMOD_RangeSize . . . . .           | 58 |
| BIOMOD_Report . . . . .              | 61 |
| biomod2_ensemble_model . . . . .     | 65 |

|                                                    |            |
|----------------------------------------------------|------------|
| biomod2_model . . . . .                            | 67         |
| bm_BinaryTransformation . . . . .                  | 68         |
| bm_CrossValidation . . . . .                       | 70         |
| bm_FindOptimStat . . . . .                         | 76         |
| bm_MakeFormula . . . . .                           | 79         |
| bm_ModelAnalysis . . . . .                         | 80         |
| bm_ModelingOptions . . . . .                       | 83         |
| bm_PlotEvalBoxplot . . . . .                       | 87         |
| bm_PlotEvalMean . . . . .                          | 89         |
| bm_PlotRangeSize . . . . .                         | 92         |
| bm_PlotResponseCurves . . . . .                    | 95         |
| bm_PlotVarImpBoxplot . . . . .                     | 99         |
| bm_PseudoAbsences . . . . .                        | 101        |
| bm_RangeSize . . . . .                             | 106        |
| bm_RunModelsLoop . . . . .                         | 110        |
| bm_SampleBinaryVector . . . . .                    | 113        |
| bm_SampleFactorLevels . . . . .                    | 114        |
| bm_SRE . . . . .                                   | 116        |
| bm_Tuning . . . . .                                | 118        |
| bm_VariablesImportance . . . . .                   | 123        |
| DataSpecies . . . . .                              | 125        |
| DataSTOC . . . . .                                 | 126        |
| getters.bm . . . . .                               | 127        |
| getters.out . . . . .                              | 128        |
| load_stored_object . . . . .                       | 134        |
| ModelsTable . . . . .                              | 135        |
| ODMAP . . . . .                                    | 136        |
| OptionsBigboss . . . . .                           | 136        |
| plot,BIOMOD.formated.data,missing-method . . . . . | 138        |
| setters . . . . .                                  | 140        |
| summary,BIOMOD.formated.data-method . . . . .      | 141        |
| <b>Index</b>                                       | <b>143</b> |

---

|                 |                                                                 |
|-----------------|-----------------------------------------------------------------|
| bioclim_current | <i>Bioclimatic variables for SDM based on current condition</i> |
|-----------------|-----------------------------------------------------------------|

---

## Description

A [SpatRaster](#) with 5 bioclimatic variables commonly used for SDM and describing current climate. Additional information available at [worldclim](#).

## Usage

```
bioclim_current
```

**Format**

A [SpatRaster](#) with 5 layers:

**bio3** Isothermality

**bio4** Temperature Seasonality

**bio7** Temperature Annual Range

**bio11** Mean Temperature of Coldest Quarter

**bio12** Annual Precipitation

---

|                |                                                                |
|----------------|----------------------------------------------------------------|
| bioclim_future | <i>Bioclimatic variables for SDM based on future condition</i> |
|----------------|----------------------------------------------------------------|

---

**Description**

A [SpatRaster](#) with 5 bioclimatic variables commonly used for SDM and describing future climate based on old RCP scenarios at the horizon 2080.

**Usage**

```
bioclim_future
```

**Format**

A [SpatRaster](#) with 5 layers:

**bio3** Isothermality

**bio4** Temperature Seasonality

**bio7** Temperature Annual Range

**bio11** Mean Temperature of Coldest Quarter

**bio12** Annual Precipitation

---

|                            |                                                      |
|----------------------------|------------------------------------------------------|
| BIOMOD.ensemble.models.out | BIOMOD_EnsembleModeling() <i>output object class</i> |
|----------------------------|------------------------------------------------------|

---

**Description**

Class returned by [BIOMOD\\_EnsembleModeling](#), and used by [BIOMOD\\_LoadModels](#), [BIOMOD\\_PresenceOnly](#) and [BIOMOD\\_EnsembleForecasting](#)

**Usage**

```
## S4 method for signature 'BIOMOD.ensemble.models.out'
show(object)
```

**Arguments**

object a `BIOMOD.ensemble.models.out` object

**Slots**

modeling.id a character corresponding to the name (ID) of the simulation set

dir.name a character corresponding to the modeling folder

sp.name a character corresponding to the species name

expl.var.names a vector containing names of explanatory variables

data.type a character corresponding to the data type

models.out a `BIOMOD.stored.models.out-class` object containing informations from `BIOMOD_Modeling` object

em.by a character corresponding to the way kept models have been combined to build the ensemble models, must be among PA+run, PA+algo, PA, algo, all

em.computed a vector containing names of ensemble models

em.failed a vector containing names of failed ensemble models

em.models\_kept a list containing single models for each ensemble model

models.evaluation a `BIOMOD.stored.data.frame-class` object containing models evaluation

variables.importance a `BIOMOD.stored.data.frame-class` object containing variables importance

models.prediction a `BIOMOD.stored.data.frame-class` object containing models predictions

models.prediction.eval a `BIOMOD.stored.data.frame-class` object containing models predictions for evaluation data

link a character containing the file name of the saved object

call a language object corresponding to the call used to obtain the object

**Author(s)**

Damien Georges

**See Also**

`BIOMOD_EnsembleModeling`, `BIOMOD_LoadModels`, `BIOMOD_PresenceOnly`, `bm_VariablesImportance`, `bm_PlotEvalMean`, `bm_PlotEvalBoxplot`, `bm_PlotVarImpBoxplot`, `bm_PlotResponseCurves`

Other Toolbox objects: `BIOMOD.formated.data()`, `BIOMOD.formated.data.PA()`, `BIOMOD.models.options`, `BIOMOD.models.out`, `BIOMOD.options.dataset()`, `BIOMOD.options.default()`, `BIOMOD.projection.out`, `BIOMOD.rangesize.out`, `BIOMOD.stored.data`, `biomod2_ensemble_model`, `biomod2_model`

## Examples

[illegible]

```

# Model ensemble models
myBiomodEM <- BIOMOD_EnsembleModeling(bm.mod = myBiomodModelOut,
                                     models.chosen = 'all',
                                     em.by = 'all',
                                     em.algo = c('EMmean', 'EMca'),
                                     metric.select = c('TSS'),
                                     metric.select.thresh = c(0.7),
                                     metric.eval = c('TSS', 'AUCroc'),
                                     var.import = 3,
                                     seed.val = 42)

myBiomodEM

```

---

BIOMOD.formated.data    BIOMOD\_FormatingData() *output object class*

---

## Description

Class returned by [BIOMOD\\_FormatingData](#), and used by [bm\\_Tuning](#), [bm\\_CrossValidation](#) and [BIOMOD\\_Modeling](#)

## Usage

```

## S4 method for signature 'numeric,data.frame'
BIOMOD.formated.data(
  sp,
  env,
  xy = NULL,
  dir.name = ".",
  data.type = NULL,
  sp.name = NULL,
  eval.sp = NULL,
  eval.env = NULL,
  eval.xy = NULL,
  na.rm = TRUE,
  data.mask = NULL,
  shared.eval.env = FALSE,
  filter.raster = FALSE
)

## S4 method for signature 'data.frame,ANY'
BIOMOD.formated.data(
  sp,
  env,
  xy = NULL,
  dir.name = ".",
  data.type = NULL,

```

```

    sp.name = NULL,
    eval.sp = NULL,
    eval.env = NULL,
    eval.xy = NULL,
    na.rm = TRUE,
    filter.raster = FALSE
  )

## S4 method for signature 'numeric,matrix'
BIOMOD.formated.data(
  sp,
  env,
  xy = NULL,
  dir.name = ".",
  data.type = NULL,
  sp.name = NULL,
  eval.sp = NULL,
  eval.env = NULL,
  eval.xy = NULL,
  na.rm = TRUE,
  filter.raster = FALSE
)

## S4 method for signature 'numeric,SpatRaster'
BIOMOD.formated.data(
  sp,
  env,
  xy = NULL,
  dir.name = ".",
  data.type = NULL,
  sp.name = NULL,
  eval.sp = NULL,
  eval.env = NULL,
  eval.xy = NULL,
  na.rm = TRUE,
  shared.eval.env = FALSE,
  filter.raster = FALSE
)

## S4 method for signature 'BIOMOD.formated.data'
show(object)

```

## Arguments

**sp** a vector, a [SpatVector](#) without associated data (*if presence-only*), or a [SpatVector](#) object containing binary data (0 : absence, 1 : presence, NA : indeterminate) for a single species that will be used to build the species distribution model(s)  
*Note that old format from **sp** are still supported such as SpatialPoints (if presence-only) or SpatialPointsDataFrame object containing binary data.*

|                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| env             | <p>a matrix, data.frame, <a href="#">SpatVector</a> or <a href="#">SpatRaster</a> object containing the explanatory variables (in columns or layers) that will be used to build the species distribution model(s).</p> <p><i>Note that old format from <b>raster</b> and <b>sp</b> are still supported such as RasterStack and SpatialPointsDataFrame objects.</i></p>                                                                                                                                                     |
| xy              | <p>(optional, default NULL)</p> <p>If resp.var is a vector, a 2-columns matrix or data.frame containing the corresponding X and Y coordinates that will be used to build the species distribution model(s)</p>                                                                                                                                                                                                                                                                                                             |
| dir.name        | a character corresponding to the modeling folder                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| data.type       | a character corresponding to the data type                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| sp.name         | a character corresponding to the species name                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| eval.sp         | <p>(optional, default NULL)</p> <p>A vector, a <a href="#">SpatVector</a> without associated data (if presence-only), or a <a href="#">SpatVector</a> object containing binary data (0 : absence, 1 : presence, NA : indeterminate) for a single species that will be used to evaluate the species distribution model(s) with independent data</p> <p><i>Note that old format from <b>sp</b> are still supported such as SpatialPoints (if presence-only) or SpatialPointsDataFrame object containing binary data.</i></p> |
| eval.env        | <p>(optional, default NULL)</p> <p>A matrix, data.frame, <a href="#">SpatVector</a> or <a href="#">SpatRaster</a> object containing the explanatory variables (in columns or layers) that will be used to evaluate the species distribution model(s) with independent data</p> <p><i>Note that old format from <b>raster</b> and <b>sp</b> are still supported such as RasterStack and SpatialPointsDataFrame objects.</i></p>                                                                                             |
| eval.xy         | <p>(optional, default NULL)</p> <p>If resp.var is a vector, a 2-columns matrix or data.frame containing the corresponding X and Y coordinates that will be used to evaluate the species distribution model(s) with independent data</p>                                                                                                                                                                                                                                                                                    |
| na.rm           | <p>(optional, default TRUE)</p> <p>A logical value defining whether points having one or several missing values for explanatory variables should be removed from the analysis or not</p>                                                                                                                                                                                                                                                                                                                                   |
| data.mask       | <p>(optional, default NULL)</p> <p>A <a href="#">SpatRaster</a> object containing the mask of the studied area</p>                                                                                                                                                                                                                                                                                                                                                                                                         |
| shared.eval.env | <p>(optional, default FALSE)</p> <p>A logical value defining whether the explanatory variables used for the evaluation dataset are the same than the ones for calibration (if eval.env not provided for example) or not</p>                                                                                                                                                                                                                                                                                                |
| filter.raster   | <p>(optional, default FALSE)</p> <p>If env is of raster type, a logical value defining whether sp is to be filtered when several points occur in the same raster cell</p>                                                                                                                                                                                                                                                                                                                                                  |
| object          | a <a href="#">BIOMOD.formated.data</a> object                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |

**Slots**

data.type a character corresponding to the data type  
 dir.name a character corresponding to the modeling folder  
 sp.name a character corresponding to the species name  
 coord a 2-columns data.frame containing the corresponding X and Y coordinates  
 data.species a vector containing the species observations (0, 1 or NA)  
 data.env.var a data.frame containing explanatory variables  
 data.mask a [SpatRaster](#) object containing the mask of the studied area  
 has.data.eval a logical value defining whether evaluation data is given  
 has.filter.raster a logical value defining whether filtering have been done or not  
 eval.coord (*optional, default NULL*)  
     A 2-columns data.frame containing the corresponding X and Y coordinates for evaluation data  
 eval.data.species (*optional, default NULL*)  
     A vector containing the species observations (0, 1 or NA) for evaluation data  
 eval.data.env.var (*optional, default NULL*)  
     A data.frame containing explanatory variables for evaluation data  
 biomod2.version a character corresponding to the biomod2 version  
 call a language object corresponding to the call used to obtain the object

**Author(s)**

Damien Georges

**See Also**

[BIOMOD\\_FormatingData](#), [bm\\_Tuning](#), [bm\\_CrossValidation](#), [BIOMOD\\_Modeling](#), [bm\\_RunModelsLoop](#)

Other Toolbox objects: [BIOMOD.ensemble.models.out](#), [BIOMOD.formated.data.PA\(\)](#), [BIOMOD.models.options](#), [BIOMOD.models.out](#), [BIOMOD.options.dataset\(\)](#), [BIOMOD.options.default\(\)](#), [BIOMOD.projection.out](#), [BIOMOD.rangesize.out](#), [BIOMOD.stored.data](#), [biomod2\\_ensemble\\_model](#), [biomod2\\_model](#)

**Examples**

```

showClass("BIOMOD.formated.data")

## ----- #
library(terra)

# Load species occurrences (6 species available)
data(DataSpecies)
head(DataSpecies)

# Select the name of the studied species
myRespName <- 'GuloGulo'

```

```

# Get corresponding presence/absence data
myResp <- as.numeric(DataSpecies[, myRespName])

# Get corresponding XY coordinates
myRespXY <- DataSpecies[, c('X_WGS84', 'Y_WGS84')]

# Load environmental variables extracted from BIOCLIM (bio_3, bio_4, bio_7, bio_11 & bio_12)
data(bioclim_current)
myExpl <- terra::rast(bioclim_current)

## ----- #
# Format Data with true absences
myBiomodData <- BIOMOD_FormatingData(resp.name = myRespName,
                                     resp.var = myResp,
                                     resp.xy = myRespXY,
                                     expl.var = myExpl)

myBiomodData
plot(myBiomodData)
summary(myBiomodData)

```

---

BIOMOD.formated.data.PA

*BIOMOD\_FormatingData() output object class (with pseudo-absences)*

---

## Description

Class returned by [BIOMOD\\_FormatingData](#), and used by [bm\\_Tuning](#), [bm\\_CrossValidation](#) and [BIOMOD\\_Modeling](#)

## Usage

```

## S4 method for signature 'numeric,data.frame'
BIOMOD.formated.data.PA(
  sp,
  env,
  xy = NULL,
  dir.name = ".",
  sp.name = NULL,
  eval.sp = NULL,
  eval.env = NULL,
  eval.xy = NULL,
  PA.strategy,
  PA.nb.rep = NULL,
  PA.nb.absences = NULL,

```

```

    PA.dist.min = 0,
    PA.dist.max = NULL,
    PA.sre.quant = NULL,
    PA.fact.aggr = NULL,
    PA.user.table = NULL,
    na.rm = TRUE,
    filter.raster = FALSE,
    seed.val = NULL
  )

## S4 method for signature 'numeric,SpatRaster'
BIOMOD.formated.data.PA(
  sp,
  env,
  xy = NULL,
  dir.name = ".",
  sp.name = NULL,
  eval.sp = NULL,
  eval.env = NULL,
  eval.xy = NULL,
  PA.strategy,
  PA.nb.rep = NULL,
  PA.nb.absences = NULL,
  PA.dist.min = 0,
  PA.dist.max = NULL,
  PA.sre.quant = NULL,
  PA.fact.aggr = NULL,
  PA.user.table = NULL,
  na.rm = TRUE,
  filter.raster = FALSE,
  seed.val = NULL
)

```

## Arguments

- |     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|-----|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| sp  | a vector, a <a href="#">SpatVector</a> without associated data ( <i>if presence-only</i> ), or a <a href="#">SpatVector</a> object containing binary data (0 : absence, 1 : presence, NA : indeterminate) for a single species that will be used to build the species distribution model(s)<br><i>Note that old format from <b>sp</b> are still supported such as SpatialPoints (if presence-only) or SpatialPointsDataFrame object containing binary data.</i> |
| env | a matrix, data.frame, <a href="#">SpatVector</a> or <a href="#">SpatRaster</a> object containing the explanatory variables (in columns or layers) that will be used to build the species distribution model(s).<br><i>Note that old format from <b>raster</b> and <b>sp</b> are still supported such as RasterStack and SpatialPointsDataFrame objects.</i>                                                                                                     |
| xy  | (optional, default NULL)<br>If resp.var is a vector, a 2-columns matrix or data.frame containing the corresponding X and Y coordinates that will be used to build the species distri-                                                                                                                                                                                                                                                                           |

|                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                | but ion model(s)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| dir.name       | a character corresponding to the modeling folder                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| sp.name        | a character corresponding to the species name                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| eval.sp        | <p>(optional, default NULL)</p> <p>A vector, a <a href="#">SpatVector</a> without associated data (if <i>presence-only</i>), or a <a href="#">SpatVector</a> object containing binary data (0 : absence, 1 : presence, NA : indeterminate) for a single species that will be used to evaluate the species distribution model(s) with independent data</p> <p><i>Note that old format from <b>sp</b> are still supported such as SpatialPoints (if presence-only) or SpatialPointsDataFrame object containing binary data.</i></p> |
| eval.env       | <p>(optional, default NULL)</p> <p>A matrix, data.frame, <a href="#">SpatVector</a> or <a href="#">SpatRaster</a> object containing the explanatory variables (in columns or layers) that will be used to evaluate the species distribution model(s) with independent data</p> <p><i>Note that old format from <b>raster</b> and <b>sp</b> are still supported such as RasterStack and SpatialPointsDataFrame objects.</i></p>                                                                                                    |
| eval.xy        | <p>(optional, default NULL)</p> <p>If resp.var is a vector, a 2-columns matrix or data.frame containing the corresponding X and Y coordinates that will be used to evaluate the species distribution model(s) with independent data</p>                                                                                                                                                                                                                                                                                           |
| PA.strategy    | <p>(optional, default NULL)</p> <p>If pseudo-absence selection, a character defining the strategy that will be used to select the pseudo-absence points. Must be random, sre, disk or user.defined (see Details)</p>                                                                                                                                                                                                                                                                                                              |
| PA.nb.rep      | <p>(optional, default NULL)</p> <p>If pseudo-absence selection, an integer corresponding to the number of sets (repetitions) of pseudo-absence points that will be drawn</p>                                                                                                                                                                                                                                                                                                                                                      |
| PA.nb.absences | <p>(optional, default NULL)</p> <p>If pseudo-absence selection, and PA.strategy = 'random' or PA.strategy = 'sre' or PA.strategy = 'disk', an integer (or a vector of integer the same size as PA.nb.rep) corresponding to the number of pseudo-absence points that will be selected for each pseudo-absence repetition (true absences included)</p>                                                                                                                                                                              |
| PA.dist.min    | <p>(optional, default 0)</p> <p>If pseudo-absence selection and PA.strategy = 'disk', a numeric defining the minimal distance to presence points used to make the disk pseudo-absence selection (in the same projection system units as coord, see Details)</p>                                                                                                                                                                                                                                                                   |
| PA.dist.max    | <p>(optional, default NULL)</p> <p>If pseudo-absence selection and PA.strategy = 'disk', a numeric defining the maximal distance to presence points used to make the disk pseudo-absence selection (in the same projection system units as coord, see Details)</p>                                                                                                                                                                                                                                                                |
| PA.sre.quant   | <p>(optional, default NULL)</p> <p>If pseudo-absence selection and PA.strategy = 'sre', a numeric between 0 and 0.5 defining the half-quantile used to make the sre pseudo-absence selection (see Details)</p>                                                                                                                                                                                                                                                                                                                    |

|               |                                                                                                                                                                                                                                                                                                                                          |
|---------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| PA.fact.aggr  | (optional, default NULL)<br>If strategy = 'random' or strategy = 'disk', a integer defining the factor of aggregation to reduce the resolution                                                                                                                                                                                           |
| PA.user.table | (optional, default NULL)<br>If pseudo-absence selection and PA.strategy = 'user.defined', a matrix or data.frame with as many rows as resp.var values, as many columns as PA.nb.rep, and containing TRUE or FALSE values defining which points will be used to build the species distribution model(s) for each repetition (see Details) |
| na.rm         | (optional, default TRUE)<br>A logical value defining whether points having one or several missing values for explanatory variables should be removed from the analysis or not                                                                                                                                                            |
| filter.raster | (optional, default FALSE)<br>If env is of raster type, a logical value defining whether sp is to be filtered when several points occur in the same raster cell                                                                                                                                                                           |
| seed.val      | (optional, default NULL)<br>An integer value corresponding to the new seed value to be set                                                                                                                                                                                                                                               |

## Slots

|                   |                                                                                                                                                                                                  |
|-------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| dir.name          | a character corresponding to the modeling folder                                                                                                                                                 |
| sp.name           | a character corresponding to the species name                                                                                                                                                    |
| coord             | a 2-columns data.frame containing the corresponding X and Y coordinates                                                                                                                          |
| data.species      | a vector containing the species observations (0, 1 or NA)                                                                                                                                        |
| data.env.var      | a data.frame containing explanatory variables                                                                                                                                                    |
| data.mask         | a <a href="#">SpatRaster</a> object containing the mask of the studied area                                                                                                                      |
| has.data.eval     | a logical value defining whether evaluation data is given                                                                                                                                        |
| eval.coord        | (optional, default NULL)<br>A 2-columns data.frame containing the corresponding X and Y coordinates for evaluation data                                                                          |
| eval.data.species | (optional, default NULL)<br>A vector containing the species observations (0, 1 or NA) for evaluation data                                                                                        |
| eval.data.env.var | (optional, default NULL)<br>A data.frame containing explanatory variables for evaluation data                                                                                                    |
| PA.strategy       | a character corresponding to the pseudo-absence selection strategy                                                                                                                               |
| PA.table          | a data.frame containing the corresponding table of selected pseudo-absences (indicated by TRUE or FALSE) from the pa.tab list element returned by the <a href="#">bm_PseudoAbsences</a> function |

## Author(s)

Damien Georges

**See Also**

[BIOMOD\\_FormatingData](#), [bm\\_PseudoAbsences](#), [bm\\_Tuning](#), [bm\\_CrossValidation](#), [BIOMOD\\_Modeling](#), [bm\\_RunModelsLoop](#)

Other Toolbox objects: [BIOMOD.ensemble.models.out](#), [BIOMOD.formated.data\(\)](#), [BIOMOD.models.options](#), [BIOMOD.models.out](#), [BIOMOD.options.dataset\(\)](#), [BIOMOD.options.default\(\)](#), [BIOMOD.projection.out](#), [BIOMOD.rangesize.out](#), [BIOMOD.stored.data](#), [biomod2\\_ensemble\\_model](#), [biomod2\\_model](#)

**Examples**

```
showClass("BIOMOD.formated.data.PA")

## ----- #
library(terra)

# Load species occurrences (6 species available)
data(DataSpecies)
head(DataSpecies)

# Select the name of the studied species
myRespName <- 'GuloGulo'

# Keep only presence informations
DataSpecies <- DataSpecies[which(DataSpecies[, myRespName] == 1), ]

# Get corresponding presence/absence data
myResp <- as.numeric(DataSpecies[, myRespName])

# Get corresponding XY coordinates
myRespXY <- DataSpecies[, c('X_WGS84', 'Y_WGS84')]

# Load environmental variables extracted from BIOCLIM (bio_3, bio_4, bio_7, bio_11 & bio_12)
data(bioclim_current)
myExpl <- terra::rast(bioclim_current)

## ----- #
# Format Data with pseudo-absences : random method
myBiomodData <- BIOMOD_FormatingData(resp.name = myRespName,
                                     resp.var = myResp,
                                     resp.xy = myRespXY,
                                     expl.var = myExpl,
                                     PA.nb.rep = 4,
                                     PA.strategy = 'random',
                                     PA.nb.absences = 1000)

myBiomodData
plot(myBiomodData)
```

---

BIOMOD.models.options [bm\\_ModelingOptions](#) *output object class*

---

## Description

Class returned by [bm\\_ModelingOptions](#) and used by [BIOMOD\\_Modeling](#)

## Usage

```
## S4 method for signature 'BIOMOD.models.options'
show(object)
```

```
## S4 method for signature 'BIOMOD.models.options'
print(x, dataset = "_allData_allRun")
```

## Arguments

|         |                                                                                                                                                                      |
|---------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| object  | a <a href="#">BIOMOD.models.options</a> object                                                                                                                       |
| x       | a <a href="#">BIOMOD.models.options</a> object                                                                                                                       |
| dataset | a character corresponding to the name of a dataset contained in the <code>arg.values</code> slot of the <a href="#">BIOMOD.options.dataset</a> object for each model |

## Slots

`models` a vector containing model names for which options have been retrieved and defined, must be `algo.datatype.package.function`

`options` a list containing [BIOMOD.options.dataset](#) object for each model

## Author(s)

Maya Guéguen

## See Also

[BIOMOD.options.default](#), [BIOMOD.options.dataset](#), [bm\\_ModelingOptions](#), [bm\\_Tuning](#), [BIOMOD\\_Modeling](#)

Other Toolbox objects: [BIOMOD.ensemble.models.out](#), [BIOMOD.formated.data\(\)](#), [BIOMOD.formated.data.PA\(\)](#), [BIOMOD.models.out](#), [BIOMOD.options.dataset\(\)](#), [BIOMOD.options.default\(\)](#), [BIOMOD.projection.out](#), [BIOMOD.rangesize.out](#), [BIOMOD.stored.data](#), [biomod2\\_ensemble\\_model](#), [biomod2\\_model](#)

## Examples

```
showClass("BIOMOD.models.options")
```

---

|                   |                                              |
|-------------------|----------------------------------------------|
| BIOMOD.models.out | BIOMOD_Modeling() <i>output object class</i> |
|-------------------|----------------------------------------------|

---

## Description

Class returned by [BIOMOD\\_Modeling](#), and used by [BIOMOD\\_LoadModels](#), [BIOMOD\\_PresenceOnly](#), [BIOMOD\\_Projection](#) and [BIOMOD\\_EnsembleModeling](#)

## Usage

```
## S4 method for signature 'BIOMOD.models.out'
show(object)
```

## Arguments

object            a [BIOMOD.models.out](#) object

## Slots

modeling.id a character corresponding to the name (ID) of the simulation set

dir.name a character corresponding to the modeling folder

sp.name a character corresponding to the species name

data.type a character corresponding to the data type

expl.var.names a vector containing names of explanatory variables

models.computed a vector containing names of computed models

models.failed a vector containing names of failed models

has.evaluation.data a logical value defining whether evaluation data is given

scale.models a logical value defining whether models have been rescaled or not

formatted.input.data a [BIOMOD.stored.formated.data-class](#) object containing informations from [BIOMOD\\_FormatingData](#) object

calib.lines a [BIOMOD.stored.data.frame-class](#) object containing calibration lines

models.options a [BIOMOD.stored.options-class](#) object containing informations from [bm\\_ModelingOptions](#) object

models.evaluation a [BIOMOD.stored.data.frame-class](#) object containing models evaluation

variables.importance a [BIOMOD.stored.data.frame-class](#) object containing variables importance

models.prediction a [BIOMOD.stored.data.frame-class](#) object containing models predictions

models.prediction.eval a [BIOMOD.stored.data.frame-class](#) object containing models predictions for evaluation data

link a character containing the file name of the saved object

call a language object corresponding to the call used to obtain the object



```

CV.nb.rep = 2,
CV.perc = 0.8,
OPT.strategy = 'bigboss',
metric.eval = c('TSS', 'AUCroc'),
var.import = 3,
seed.val = 42)

myBiomodModelOut

```

---

BIOMOD.options.dataset

*bm\_ModelingOptions output object class*


---

## Description

Class returned by [bm\\_ModelingOptions](#) (a list of BIOMOD.options.dataset more exactly), and used by [BIOMOD\\_Modeling](#)

## Usage

```

## S4 method for signature 'character'
BIOMOD.options.dataset(
  mod,
  typ,
  pkg,
  fun,
  strategy,
  user.val = NULL,
  user.base = NULL,
  tuning.fun = NULL,
  bm.format = NULL,
  calib.lines = NULL
)

## S4 method for signature 'BIOMOD.options.dataset'
show(object)

## S4 method for signature 'BIOMOD.options.dataset'
print(x, dataset = "_allData_allRun")

```

## Arguments

|     |                                                                                                                                                      |
|-----|------------------------------------------------------------------------------------------------------------------------------------------------------|
| mod | a character corresponding to the model name to be computed, must be either ANN, CTA, DNN, FDA, GAM, GBM, GLM, MARS, MAXENT, MAXNET, RF, SRE, XGBOOST |
| typ | a character corresponding to the data type to be used, must be either binary, binary.PA, abundance, compositional                                    |

|             |                                                                                                                                                                                                                 |
|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| pkg         | a character corresponding to the package containing the model function to be called                                                                                                                             |
| fun         | a character corresponding to the model function name to be called                                                                                                                                               |
| strategy    | a character corresponding to the method to select models' parameters values, must be either default, bigboss, user.defined, tuned                                                                               |
| user.val    | (optional, default NULL)<br>A list containing parameters values                                                                                                                                                 |
| user.base   | (optional, default NULL)<br>A character, default or bigboss used when strategy = 'user.defined'. It sets the bases of parameters to be modified by user defined values.                                         |
| tuning.fun  | (optional, default NULL)<br>A character corresponding to the model function name to be called through <a href="#">train</a> function for tuning parameters                                                      |
| bm.format   | (optional, default NULL)<br>A <a href="#">BIOMOD.formated.data</a> or <a href="#">BIOMOD.formated.data.PA</a> object returned by the <a href="#">BIOMOD_FormattingData</a> function                             |
| calib.lines | (optional, default NULL)<br>A data.frame object returned by <a href="#">get_calib_lines</a> or <a href="#">bm_CrossValidation</a> functions, to explore the distribution of calibration and validation datasets |
| object      | a <a href="#">BIOMOD.options.dataset</a> object                                                                                                                                                                 |
| x           | a <a href="#">BIOMOD.options.dataset</a> object                                                                                                                                                                 |
| dataset     | a character corresponding to the name of a dataset contained in the arg.values slot                                                                                                                             |

### Slots

|              |                                                                                                 |
|--------------|-------------------------------------------------------------------------------------------------|
| model        | a character corresponding to the model                                                          |
| type         | a character corresponding to the data type (binary, binary.PA, abundance, compositional)        |
| package      | a character corresponding to the package containing the model function to be called             |
| func         | a character corresponding to the model function name to be called                               |
| args.names   | a vector containing character corresponding to the model function arguments                     |
| args.default | a list containing for each dataset the default values for all arguments listed in args.names    |
| args.values  | a list containing for each dataset the to-be-used values for all arguments listed in args.names |

### Author(s)

Maya Guéguen

### See Also

[BIOMOD.options.default](#), [bm\\_ModelingOptions](#), [bm\\_Tuning](#), [BIOMOD\\_Modeling](#), [bm\\_RunModelsLoop](#)

Other Toolbox objects: [BIOMOD.ensemble.models.out](#), [BIOMOD.formated.data\(\)](#), [BIOMOD.formated.data.PA\(\)](#), [BIOMOD.models.options](#), [BIOMOD.models.out](#), [BIOMOD.options.default\(\)](#), [BIOMOD.projection.out](#), [BIOMOD.rangesize.out](#), [BIOMOD.stored.data](#), [biomod2\\_ensemble\\_model](#), [biomod2\\_model](#)

**Examples**

```
showClass("BIOMOD.options.dataset")
```

---

```
BIOMOD.options.default
```

```
bm_ModelingOptions output object class
```

---

**Description**

Class returned by [bm\\_ModelingOptions](#) (a list of BIOMOD.options.dataset more exactly), and used by [BIOMOD\\_Modeling](#)

**Usage**

```
## S4 method for signature 'character,character'
BIOMOD.options.default(mod, typ, pkg, fun)
```

**Arguments**

|     |                                                                                                                                                      |
|-----|------------------------------------------------------------------------------------------------------------------------------------------------------|
| mod | a character corresponding to the model name to be computed, must be either ANN, CTA, DNN, FDA, GAM, GBM, GLM, MARS, MAXENT, MAXNET, RF, SRE, XGBOOST |
| typ | a character corresponding to the data type to be used, must be either binary, binary.PA, abundance, compositional                                    |
| pkg | a character corresponding to the package containing the model function to be called                                                                  |
| fun | a character corresponding to the model function name to be called                                                                                    |

**Slots**

```
model a character corresponding to the model
type a character corresponding to the data type (binary, binary.PA, abundance, compositional)
package a character corresponding to the package containing the model function to be called
func a character corresponding to the model function name to be called
args.names a vector containing character corresponding to the model function arguments
args.default a list containing for each dataset the default values for all arguments listed in
args.names
```

**Author(s)**

Maya Guéguen

**See Also**

[BIOMOD.options.dataset](#), [bm\\_ModelingOptions](#), [bm\\_Tuning](#), [BIOMOD\\_Modeling](#), [bm\\_RunModelsLoop](#)

Other Toolbox objects: [BIOMOD.ensemble.models.out](#), [BIOMOD.formated.data\(\)](#), [BIOMOD.formated.data.PA\(\)](#), [BIOMOD.models.options](#), [BIOMOD.models.out](#), [BIOMOD.options.dataset\(\)](#), [BIOMOD.projection.out](#), [BIOMOD.rangesize.out](#), [BIOMOD.stored.data](#), [biomod2\\_ensemble\\_model](#), [biomod2\\_model](#)

**Examples**

```
showClass("BIOMOD.options.default")
```

---

BIOMOD.projection.out    [BIOMOD\\_Projection\(\)](#) *output object class*

---

**Description**

Class returned by [BIOMOD\\_Projection](#), and used by [BIOMOD\\_EnsembleForecasting](#)

**Usage**

```
## S4 method for signature 'BIOMOD.projection.out,missing'
plot(
  x,
  coord = NULL,
  plot.output,
  do.plot = TRUE,
  std = TRUE,
  scales,
  size,
  maxcell = 5e+05,
  ...
)

## S4 method for signature 'BIOMOD.projection.out'
show(object)
```

**Arguments**

|             |                                                                                                                                                                                                                                                                                                                                       |
|-------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x           | a <a href="#">BIOMOD.projection.out</a> object                                                                                                                                                                                                                                                                                        |
| coord       | a 2-columns data.frame containing the corresponding X and Y                                                                                                                                                                                                                                                                           |
| plot.output | ( <i>optional, default facet</i> ) a character determining the type of output: with <code>plot.output = 'list'</code> the function will return a list of plots (one plot per model) ; with <code>'facet'</code> ; with <code>plot.output = 'facet'</code> the function will return a single plot with all asked projections as facet. |

|                      |                                                                                                                                                                                                                                                                               |
|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>do.plot</code> | ( <i>optional, default TRUE</i> ) a boolean determining whether the plot should be displayed or just returned.                                                                                                                                                                |
| <code>std</code>     | ( <i>optional, default TRUE</i> ) a boolean controlling the limits of the color scales. With <code>std = TRUE</code> color scales are displayed between 0 and 1 (or 1000). With <code>std = FALSE</code> color scales are displayed between 0 and the maximum value observed. |
| <code>scales</code>  | ( <i>optional, default fixed</i> ) a character determining whether x and y scales are shared among facet. Argument passed to <a href="#">facet_wrap</a> . Possible values: 'fixed', 'free_x', 'free_y', 'free'.                                                               |
| <code>size</code>    | ( <i>optional, default 0.75</i> ) a numeric determining the size of points on the plots and passed to <a href="#">geom_point</a> .                                                                                                                                            |
| <code>maxcell</code> | maximum number of cells to plot. Argument transmitted to <a href="#">plot</a> .                                                                                                                                                                                               |
| <code>...</code>     | additional parameters to be passed to <a href="#">get_predictions</a> to select the models that will be plotted                                                                                                                                                               |
| <code>object</code>  | a <a href="#">BIOMOD.projection.out</a> object                                                                                                                                                                                                                                |

### Slots

|                               |                                                                                                                                     |
|-------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| <code>modeling.id</code>      | a character corresponding to the name (ID) of the simulation set                                                                    |
| <code>proj.name</code>        | a character corresponding to the projection name                                                                                    |
| <code>dir.name</code>         | a character corresponding to the modeling folder                                                                                    |
| <code>sp.name</code>          | a character corresponding to the species name                                                                                       |
| <code>expl.var.names</code>   | a vector containing names of explanatory variables                                                                                  |
| <code>coord</code>            | a 2-columns matrix or data.frame containing the corresponding X and Y coordinates used to project the species distribution model(s) |
| <code>scale.models</code>     | a logical value defining whether models have been rescaled or not                                                                   |
| <code>models.projected</code> | a vector containing names of projected models                                                                                       |
| <code>models.out</code>       | a <a href="#">BIOMOD.stored.data</a> object                                                                                         |
| <code>type</code>             | a character corresponding to the class of the <code>val</code> slot of the <code>proj.out</code> slot                               |
| <code>data.type</code>        | a character corresponding to the data type                                                                                          |
| <code>proj.out</code>         | a <a href="#">BIOMOD.stored.data</a> object                                                                                         |
| <code>call</code>             | a language object corresponding to the call used to obtain the object                                                               |

### Author(s)

Damien Georges

### See Also

[BIOMOD\\_Projection](#), [BIOMOD\\_EnsembleForecasting](#)

Other Toolbox objects: [BIOMOD.ensemble.models.out](#), [BIOMOD.formated.data\(\)](#), [BIOMOD.formated.data.PA\(\)](#), [BIOMOD.models.options](#), [BIOMOD.models.out](#), [BIOMOD.options.dataset\(\)](#), [BIOMOD.options.default\(\)](#), [BIOMOD.rangesize.out](#), [BIOMOD.stored.data](#), [biomod2\\_ensemble\\_model](#), [biomod2\\_model](#)

## Examples

[illegible]

```
# Project single models
myBiomodProj <- BIOMOD_Projection(bm.mod = myBiomodModelOut,
                                proj.name = 'Current',
                                new.env = myExpl,
                                models.chosen = 'all',
                                metric.binary = 'all',
                                metric.filter = 'all',
                                build.clamping.mask = TRUE)

myBiomodProj
plot(myBiomodProj)
```

---

BIOMOD.rangesize.out    BIOMOD\_RangeSize() *output object class*

---

## Description

Class returned by [BIOMOD\\_RangeSize](#), and used by [bm\\_PlotRangeSize](#)

## Slots

`Compt.By.Models` a `data.frame` containing the summary of range change for each comparison

`Diff.By.Pixel` a `SpatRaster` or a `data.frame` containing a value for each point/pixel of each comparison

`loss.gain` a `SpatRaster` or a `data.frame` containg for each point/pixel a value indicating a loss, a gain or a stable sitatution

`data.type` a character corresponding to the data type

`coord` a 2-columns matrix or `data.frame` containing the corresponding X and Y coordinates used to project the species distribution model(s)

`row.names` A vector containing tags matching models names splitted by '\_' character

## Author(s)

Hélène Blancheteau

## See Also

Other Toolbox objects: [BIOMOD.ensemble.models.out](#), [BIOMOD.formated.data\(\)](#), [BIOMOD.formated.data.PA\(\)](#), [BIOMOD.models.options](#), [BIOMOD.models.out](#), [BIOMOD.options.dataset\(\)](#), [BIOMOD.options.default\(\)](#), [BIOMOD.projection.out](#), [BIOMOD.stored.data](#), [biomod2\\_ensemble\\_model](#), [biomod2\\_model](#)

---

|                    |                                                                                                 |
|--------------------|-------------------------------------------------------------------------------------------------|
| BIOMOD.stored.data | <a href="#">BIOMOD_Modeling</a> and <a href="#">BIOMOD_EnsembleModeling</a> output object class |
|--------------------|-------------------------------------------------------------------------------------------------|

---

## Description

Classes used by [BIOMOD\\_Modeling](#) and [BIOMOD\\_EnsembleModeling](#) to build their output object (see [BIOMOD.models.out](#) objects)

## Details

BIOMOD.stored.data is the basic object containing the slots inMemory and link.  
All listed classes below are derived from BIOMOD.stored.data, and contain a val slot of specific type :

- BIOMOD.stored.data.frame : val is a data.frame
- BIOMOD.stored.SpatRaster : val is a [PackedSpatRaster](#)
- BIOMOD.stored.files : val is a character
- BIOMOD.stored.formated.data : val is a [BIOMOD.formated.data](#) object
- BIOMOD.stored.options : val is a [BIOMOD.models.options](#) object
- BIOMOD.stored.models.out : val is a [BIOMOD.models.out](#) object

## Slots

inMemory a logical defining whether the val slot has been loaded in memory or not

link a character containing the file name of the saved val slot

val an object of type depending on the BIOMOD.stored.[...] class (see Details)

## Author(s)

Damien Georges

## See Also

[BIOMOD.formated.data](#), [BIOMOD.models.out](#), [BIOMOD\\_Modeling](#), [BIOMOD\\_EnsembleModeling](#), [BIOMOD\\_Projection](#), [BIOMOD\\_EnsembleForecasting](#)

Other Toolbox objects: [BIOMOD.ensemble.models.out](#), [BIOMOD.formated.data\(\)](#), [BIOMOD.formated.data.PA\(\)](#), [BIOMOD.models.options](#), [BIOMOD.models.out](#), [BIOMOD.options.dataset\(\)](#), [BIOMOD.options.default\(\)](#), [BIOMOD.projection.out](#), [BIOMOD.rangesize.out](#), [biomod2\\_ensemble\\_model](#), [biomod2\\_model](#)

## Examples

```
showClass("BIOMOD.stored.data")
showClass("BIOMOD.stored.data.frame")
showClass("BIOMOD.stored.SpatRaster")
showClass("BIOMOD.stored.files")
showClass("BIOMOD.stored.formated.data")
showClass("BIOMOD.stored.options")
showClass("BIOMOD.stored.models.out")
```

---

BIOMOD\_EnsembleForecasting

*Project ensemble species distribution models onto new environment*

---

## Description

This function allows to project ensemble models built with the [BIOMOD\\_EnsembleModeling](#) function onto new environmental data (*which can represent new areas, resolution or time scales for example*).

## Usage

```
BIOMOD_EnsembleForecasting(
  bm.em,
  bm.proj = NULL,
  proj.name = NULL,
  new.env = NULL,
  new.env.xy = NULL,
  models.chosen = "all",
  metric.binary = NULL,
  metric.filter = NULL,
  na.rm = TRUE,
  nb.cpu = 1,
  ...
)
```

## Arguments

|           |                                                                                                                                                                                                              |
|-----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| bm.em     | a <a href="#">BIOMOD.ensemble.models.out</a> object returned by the <a href="#">BIOMOD_EnsembleModeling</a> function                                                                                         |
| bm.proj   | a <a href="#">BIOMOD.projection.out</a> object returned by the <a href="#">BIOMOD_Projection</a> function                                                                                                    |
| proj.name | ( <i>optional, default NULL</i> )<br>If bm.proj = NULL, a character corresponding to the name (ID) of the projection set ( <i>a new folder will be created within the simulation folder with this name</i> ) |

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>new.env</code>       | <p>(optional, default NULL)</p> <p>If <code>bm.proj = NULL</code>, a <code>matrix</code>, <code>data.frame</code> or <a href="#">SpatRaster</a> object containing the new explanatory variables (in columns or layers, with names matching the variables names given to the <a href="#">BIOMOD_FormatingData</a> function to build <code>bm.mod</code>) that will be used to project the species distribution model(s)</p> <p><i>Note that old format from <b>raster</b> are still supported such as <code>RasterStack</code> objects.</i></p> |
| <code>new.env.xy</code>    | <p>(optional, default NULL)</p> <p>If <code>new.env</code> is a <code>matrix</code> or a <code>data.frame</code>, a 2-columns <code>matrix</code> or <code>data.frame</code> containing the corresponding X and Y coordinates that will be used to project the ensemble species distribution model(s)</p>                                                                                                                                                                                                                                      |
| <code>models.chosen</code> | <p>a vector containing model names to be kept, must be either all or a sub-selection of model names that can be obtained with the <a href="#">get_built_models</a> function applied to <code>bm.mod</code></p>                                                                                                                                                                                                                                                                                                                                 |
| <code>metric.binary</code> | <p>(optional, default NULL)</p> <p>A vector containing evaluation metric names to be used to transform prediction values into binary values based on models evaluation scores obtained with the <a href="#">BIOMOD_EnsembleModeling</a> function. Must be among all (same evaluation metrics than those of <code>bm.mod</code>) or POD, FAR, POFD, SR, ACCURACY, BIAS, AUCroc, AUCprg, TSS, KAPPA, OR, ORSS, CSI, ETS, BOYCE, MPA</p> <p><i>Note that this is for binary data only.</i></p>                                                    |
| <code>metric.filter</code> | <p>(optional, default NULL)</p> <p>A vector containing evaluation metric names to be used to transform prediction values into filtered values based on models evaluation scores obtained with the <a href="#">BIOMOD_EnsembleModeling</a> function. Must be among all (same evaluation metrics than those of <code>bm.mod</code>) or POD, FAR, POFD, SR, ACCURACY, BIAS, AUCroc, AUCprg, TSS, KAPPA, OR, ORSS, CSI, ETS, BOYCE, MPA</p> <p><i>Note that this is for binary data only.</i></p>                                                  |
| <code>na.rm</code>         | <p>(optional, default TRUE)</p> <p>A logical value defining whether ensemble model projection should ignore missing values in single model projections or not (<i>ignored by EMwmean algorithm</i>)</p>                                                                                                                                                                                                                                                                                                                                        |
| <code>nb.cpu</code>        | <p>(optional, default 1)</p> <p>An integer value corresponding to the number of computing resources to be used to parallelize the single models computation</p>                                                                                                                                                                                                                                                                                                                                                                                |
| <code>...</code>           | <p>(optional, see Details)</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |

## Details

... can take the following values :

**digits** (optional, default 0) :

an integer value corresponding to the number of digits of the predictions

**on\_0\_1000** (optional, default TRUE) :

a logical value defining whether 0 - 1 probabilities are to be converted to 0 - 1000 scale to save memory on backup

**keep.in.memory** (optional, default TRUE) :

a logical value defining whether all projections are to be kept loaded at once in memory, or only links pointing to hard drive are to be returned

**do.stack** (optional, default TRUE) :

a logical value defining whether all projections are to be saved as one [SpatRaster](#) object or several [SpatRaster](#) files (the default if projections are too heavy to be all loaded at once in memory)

**output.format** (optional, default .RData or .tif) :

a character value corresponding to the projections saving format on hard drive, must be either .grd, .img, .tif or .RData (the default if new.env is given as matrix or data.frame)

**compress** (optional, default TRUE) :

a logical or a character value defining whether and how objects should be compressed when saved on hard drive. Must be either TRUE, FALSE, gzip (for Windows OS) or xz (for other OS)

## Value

A [BIOMOD.projection.out](#) object containing models projections, or links to saved outputs. Models projections are stored out of R (for memory storage reasons) in proj.name folder created in the current working directory :

1. the output is a data.frame if new.env is a matrix or a data.frame
2. it is a [SpatRaster](#) if new.env is a [SpatRaster](#) (or several [SpatRaster](#) objects, if new.env is too large)
3. raw projections, as well as binary and filtered projections (if asked), are saved in the proj.name folder

## Author(s)

Wilfried Thuiller, Damien Georges, Robin Engler

## See Also

[BIOMOD\\_FormatingData](#), [bm\\_ModelingOptions](#), [BIOMOD\\_Modeling](#), [BIOMOD\\_EnsembleModeling](#), [BIOMOD\\_RangeSize](#)

Other Main functions: [BIOMOD\\_EnsembleModeling\(\)](#), [BIOMOD\\_FormatingData\(\)](#), [BIOMOD\\_LoadModels\(\)](#), [BIOMOD\\_Modeling\(\)](#), [BIOMOD\\_Projection\(\)](#), [BIOMOD\\_RangeSize\(\)](#)

## Examples

```
library(terra)

# Load species occurrences (6 species available)
data(DataSpecies)
head(DataSpecies)

# Select the name of the studied species
myRespName <- 'GuloGulo'
```



```

file.EM <- paste0(myRespName, "/", myRespName, ".AllModels.ensemble.models.out")
if (file.exists(file.EM)) {
  myBiomodEM <- get(load(file.EM))
} else {

  # Model ensemble models
  myBiomodEM <- BIOMOD_EnsembleModeling(bm.mod = myBiomodModelOut,
                                       models.chosen = 'all',
                                       em.by = 'all',
                                       em.algo = c('EMmean', 'EMca'),
                                       metric.select = c('TSS'),
                                       metric.select.thresh = c(0.7),
                                       metric.eval = c('TSS', 'AUCroc'),
                                       var.import = 3,
                                       seed.val = 42)
}

# ----- #
# Project ensemble models (from single projections)
myBiomodEMProj <- BIOMOD_EnsembleForecasting(bm.em = myBiomodEM,
                                             bm.proj = myBiomodProj,
                                             models.chosen = 'all',
                                             metric.binary = 'all',
                                             metric.filter = 'all')

# Project ensemble models (building single projections)
myBiomodEMProj <- BIOMOD_EnsembleForecasting(bm.em = myBiomodEM,
                                             proj.name = 'CurrentEM',
                                             new.env = myExpl,
                                             models.chosen = 'all',
                                             metric.binary = 'all',
                                             metric.filter = 'all')

myBiomodEMProj
plot(myBiomodEMProj)

```

---

BIOMOD\_EnsembleModeling

*Create and evaluate an ensemble set of models and predictions*


---

## Description

This function allows to combine a range of models built with the [BIOMOD\\_Modeling](#) function in one (or several) ensemble model. Modeling uncertainty can be assessed as well as variables importance, ensemble predictions can be evaluated against original data, and created ensemble models can be projected over new conditions (see Details).

**Usage**

```

BIOMOD_EnsembleModeling(
  bm.mod,
  models.chosen = "all",
  em.by = "PA+run",
  em.algo,
  metric.select = "all",
  metric.select.thresh = NULL,
  metric.select.table = NULL,
  metric.select.dataset = NULL,
  metric.eval = c("KAPPA", "TSS", "AUCroc"),
  var.import = 0,
  EMci.alpha = 0.05,
  EMwmean.decay = "proportional",
  nb.cpu = 1,
  seed.val = NULL,
  do.progress = TRUE
)

```

**Arguments**

|                                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>bm.mod</code>               | a <a href="#">BIOMOD.models.out</a> object returned by the <a href="#">BIOMOD_Modeling</a> function                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <code>models.chosen</code>        | a vector containing model names to be kept, must be either <code>all</code> or a sub-selection of model names that can be obtained with the <a href="#">get_built_models</a> function applied to <code>bm.mod</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <code>em.by</code>                | a character corresponding to the way kept models will be combined to build the ensemble models, must be among <code>all</code> , <code>algo</code> , <code>PA</code> , <code>PA+algo</code> , <code>PA+run</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <code>em.algo</code>              | a vector corresponding to the ensemble models that will be computed, must be among <code>EMmean</code> , <code>EMmedian</code> , <code>EMcv</code> , <code>EMci</code> , <code>EMca</code> , <code>EMwmean</code> , <code>EMmode</code> , <code>EMfreq</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <code>metric.select</code>        | a vector containing evaluation metric names to be used to select single models based on their evaluation scores, must be among <code>user.defined</code> or <code>AUCroc</code> , <code>AUCprg</code> , <code>TSS</code> , <code>KAPPA</code> , <code>ACCURACY</code> , <code>BIAS</code> , <code>POD</code> , <code>FAR</code> , <code>POFD</code> , <code>SR</code> , <code>CSI</code> , <code>ETS</code> , <code>OR</code> , <code>ORSS</code> , <code>BOYCE</code> , <code>MPA</code> ( <i>binary data</i> ), <code>RMSE</code> , <code>MAE</code> , <code>MSE</code> , <code>Rsquared</code> , <code>Rsquared_aj</code> , <code>Max_error</code> ( <i>abundance / count / relative data</i> ), <code>Accuracy</code> , <code>Recall</code> , <code>Precision</code> , <code>F1</code> ( <i>ordinal data</i> ) |
| <code>metric.select.thresh</code> | ( <i>optional, default NULL</i> )<br>A vector of numeric values corresponding to the minimum scores (one for each <code>metric.select</code> ) below which single models will be excluded from the ensemble model building                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <code>metric.select.table</code>  | ( <i>optional, default NULL</i> )<br>If <code>metric.select = 'user.defined'</code> , a data.frame containing evaluation scores calculated for each single models and that will be compared to <code>metric.select.thresh</code> values below which single models will be excluded from the ensemble model, with <code>metric.select</code> rownames, and <code>models.chosen</code> colnames                                                                                                                                                                                                                                                                                                                                                                                                                      |

|                                    |                                                                                                                                                                                                                                                                                                                                                                                                           |
|------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>metric.select.dataset</code> | ( <i>optional, default validation if possible</i> )<br>A character defining which dataset should be used to filter and/or weight the ensemble models, must be among calibration, validation, evaluation                                                                                                                                                                                                   |
| <code>metric.eval</code>           | a vector containing evaluation metric names to be used, must be among AUCroc, AUCprg, TSS, KAPPA, ACCURACY, BIAS, POD, FAR, POFD, SR, CSI, ETS, OR, ORSS, BOYCE, MPA ( <i>binary data</i> ), RMSE, MAE, MSE, Rsquared, Rsquared_aj, Max_error ( <i>abundance / count / relative data</i> ), Accuracy, Recall, Precision, F1 ( <i>ordinal data</i> )                                                       |
| <code>var.import</code>            | ( <i>optional, default NULL</i> )<br>An integer corresponding to the number of permutations to be done for each variable to estimate variable importance                                                                                                                                                                                                                                                  |
| <code>EMci.alpha</code>            | ( <i>optional, default 0.05</i> )<br>A numeric value corresponding to the significance level to estimate confidence interval                                                                                                                                                                                                                                                                              |
| <code>EMwmean.decay</code>         | ( <i>optional, default proportional</i> )<br>If <code>em.algo = 'EMwmean'</code> , a numeric value defining the relative importance of weights. A high value will strongly discriminate <i>good</i> models from the bad ones (see Details). It is also possible to set it to <code>proportional</code> and weights will be proportional to the single models evaluation scores, or to provide a function. |
| <code>nb.cpu</code>                | ( <i>optional, default 1</i> )<br>An integer value corresponding to the number of computing resources to be used to parallelize the single models predictions and the ensemble models computation                                                                                                                                                                                                         |
| <code>seed.val</code>              | ( <i>optional, default NULL</i> )<br>An integer value corresponding to the new seed value to be set                                                                                                                                                                                                                                                                                                       |
| <code>do.progress</code>           | ( <i>optional, default TRUE</i> )<br>A logical value defining whether the progress bar is to be rendered or not                                                                                                                                                                                                                                                                                           |

## Details

### Concerning models sub-selection (`models.chosen`) :

Applying `get_built_models` function to the `bm.mod` object gives the names of the single models created with the `BIOMOD_Modeling` function. The `models.chosen` argument can take either a sub-selection of these single model names, or the `all` default value, to decide which single models will be used for the ensemble model building.

### Concerning models assembly rules (`em.by`) :

Single models built with the `BIOMOD_Modeling` function can be combined in 5 different ways to obtain ensemble models :

**PA+run** each combination of pseudo-absence and repetition datasets is done, *merging* algorithms together

**PA+algo** each combination of pseudo-absence and algorithm datasets is done, *merging* repetitions together

**PA** pseudo-absence datasets are considered individually, *merging* algorithms and repetitions together

**algo** algorithm datasets are considered individually, *merging* pseudo-absence and repetitions together

**all** all single models are combined into one

Hence, depending on the chosen method, the number of ensemble models built will vary.

*If no evaluation data was given to the `BIOMOD_FormatingData` function, some ensemble model evaluations may be biased due to difference in data used for single model evaluations.*

**Be aware that all of these combinations are allowed, but some may not make sense depending mainly on how pseudo-absence datasets have been built and whether all of them have been used for all single models or not** (see `PA.nb.absences` and `models.pa` parameters in `BIOMOD_FormatingData` and `BIOMOD_Modeling` functions respectively).

#### Concerning evaluation metrics :

**metric.select** metric(s) must be chosen among the ones used within the `BIOMOD_Modeling` function to build the `bm.mod` object, unless `metric.select = 'user.defined'` and therefore values will be provided through the `metric.select.table` parameter.

Each selected metric will be used at different steps of the ensemble modeling function to :

1. remove *low quality* single models having a score lower than `metric.select.thresh`
2. perform the binary transformation if `em.algo = 'EMca'`
3. weight models if `em.algo = 'EMwmean'`

*Note that metrics are not combined together, and one ensemble model is built for each metric provided.*

**metric.select.table** if `metric.select = 'user.defined'`, this parameter allows to use evaluation metrics other than those calculated within **biomod2**. It must be a `data.frame` containing as many columns as `models.chosen` with matching names, and as many rows as evaluation metrics to be used. The number of rows must match the length of `metric.select.thresh`, and values will be compared to those defined in `metric.select.thresh` to remove *low quality* single models from the ensemble model building.

**metric.select.dataset** by default, *validation* datasets will be used, unless no validation is available (no cross-validation) in which case *calibration* datasets will be used

#### Concerning ensemble algorithms :

6 modeling techniques are currently available :

**EMmedian** median of probabilities over the selected models

Less sensitive to outliers than the mean

**EMmean** mean of probabilities over the selected models

**EMwmean** weighted mean of probabilities over the selected models

Probabilities are weighted according to their model evaluation scores obtained when building the `bm.out` object with the `BIOMOD_Modeling` function (*better a model is, more importance it has in the ensemble*) and summed.

The `EMwmean.decay` is the ratio between a weight and the next or previous one.

The formula is :  $W = W(-1) * EMwmean.decay$ .

*For example, with the value of 1.6 and 4 weights wanted, the relative importance of the weights will be 1 / 1.6 / 2.56 (=1.6\*1.6) / 4.096 (=2.56\*1.6) from the weakest to the strongest, and gives 0.11 / 0.17 / 0.275 / 0.445 considering that the sum of the weights is equal to one. The lower the `EMwmean.decay`, the smoother the differences between the weights enhancing a weak discrimination between models.*

If `EMwmean.decay = 'proportional'`, the weights are assigned to each model proportionally to their evaluation scores. The discrimination is fairer than using the *decay* method where close scores can have strongly diverging weights, while the proportional method would assign them similar weights.

It is also possible to define the `EMwmean.decay` parameter as a function that will be applied to single models scores and transform them into weights.

*For example, if `EMwmean.decay = function(x) {x^2}`, the squared of evaluation score of each model will be used to weight the models predictions.*

**EMca** committee averaging over the selected models

Probabilities are first transformed into binary data according to the threshold defined when building the `bm.out` object with the `BIOMOD_Modeling` function (maximizing the evaluation metric score over the *calibration* dataset). The committee averaging score is obtained by taking the average of these binary predictions.

It is built on the analogy of a simple vote :

- each single model votes for the species being either present (1) or absent (0)
- the sum of 1 is then divided by the number of single models *voting*

The interesting feature of this measure is that it gives both a prediction and a measure of uncertainty. When the prediction is close to 0 or 1, it means that all models agree to predict 0 or 1 respectively. When the prediction is around 0.5, it means that half the models predict 1 and the other half 0.

*Note that this is for binary data only.*

**EMci** confidence interval around the mean of probabilities of the selected models

It creates 2 *ensemble* models :

- *LOWER* : there is less than  $100 * EMci.alpha / 2$  % of chance to get probabilities lower than the given ones
- *UPPER* : there is less than  $100 * EMci.alpha / 2$  % of chance to get probabilities upper than the given ones

These intervals are calculated with the following function :

$$I_c = [\bar{x} - \frac{t_{\alpha}sd}{\sqrt{n}}; \bar{x} + \frac{t_{\alpha}sd}{\sqrt{n}}]$$

**EMcv** coefficient of variation (sd / mean) of probabilities over the selected models

This is the only *ensemble* model that might not be over the same scale than the others, as CV is a measure of uncertainty rather a measure of probability of occurrence. It will be evaluated like all other ensemble models although its interpretation will be obviously different. If the CV gets a high evaluation score, it means that the uncertainty is high where the species is observed (which might not be a good feature of the model). *The lower is the score, the better are the models.*

**EMmode** mode of the predictions over the selected models

For multiclass and ordinal data, EMmode will return the most frequent class found for each point. This is the only *ensemble* model that will return categorical data and not numeric values.

**EMfreq** mode frequency of the predictions over the selected models

For multiclass and ordinal data, EMfreq will return the frequency of the mode found for each point. This is a way of assessing the uncertainty between models: the higher the frequency, the lower the uncertainty.

## Value

A `BIOMOD.ensemble.models.out` object containing models outputs, or links to saved outputs. Models outputs are stored out of R (for memory storage reasons) in 2 different folders created in the current working directory :

1. a *models* folder, named after the `resp.name` argument of `BIOMOD_FormatingData`, and containing all ensemble models
2. a *hidden* folder, named `.BIOMOD_DATA`, and containing outputs related files (original dataset, calibration lines, pseudo-absences selected, predictions, variables importance, evaluation values...), that can be retrieved with `get_[...]` or `load` functions, and used by other **biomod2** functions, like `BIOMOD_EnsembleForecasting`

## Author(s)

Wilfried Thuiller, Damien Georges, Robin Engler

## See Also

`BIOMOD_FormatingData`, `bm_ModelingOptions`, `bm_CrossValidation`, `bm_VariablesImportance`, `BIOMOD_Modeling`, `BIOMOD_EnsembleForecasting`, `bm_PlotEvalMean`, `bm_PlotEvalBoxplot`, `bm_PlotVarImpBoxplot`, `bm_PlotResponseCurves`

Other Main functions: `BIOMOD_EnsembleForecasting()`, `BIOMOD_FormatingData()`, `BIOMOD_LoadModels()`, `BIOMOD_Modeling()`, `BIOMOD_Projection()`, `BIOMOD_RangeSize()`

## Examples

```
library(terra)

# Load species occurrences (6 species available)
```

```

data(DataSpecies)
head(DataSpecies)

# Select the name of the studied species
myRespName <- 'GuloGulo'

# Get corresponding presence/absence data
myResp <- as.numeric(DataSpecies[, myRespName])

# Get corresponding XY coordinates
myRespXY <- DataSpecies[, c('X_WGS84', 'Y_WGS84')]

# Load environmental variables extracted from BIOCLIM (bio_3, bio_4, bio_7, bio_11 & bio_12)
data(bioclim_current)
myExpl <- terra::rast(bioclim_current)

## ----- #
file.out <- paste0(myRespName, "/", myRespName, ".AllModels.models.out")
if (file.exists(file.out)) {
  myBiomodModelOut <- get(load(file.out))
} else {

  # Format Data with true absences
  myBiomodData <- BIOMOD_FormatingData(resp.name = myRespName,
                                     resp.var = myResp,
                                     resp.xy = myRespXY,
                                     expl.var = myExpl)

  # Model single models
  myBiomodModelOut <- BIOMOD_Modeling(bm.format = myBiomodData,
                                     modeling.id = 'AllModels',
                                     models = c('RF', 'GLM'),
                                     CV.strategy = 'random',
                                     CV.nb.rep = 2,
                                     CV.perc = 0.8,
                                     OPT.strategy = 'bigboss',
                                     metric.eval = c('TSS', 'AUCroc'),
                                     var.import = 3,
                                     seed.val = 42)
}

## ----- #
# Model ensemble models
myBiomodEM <- BIOMOD_EnsembleModeling(bm.mod = myBiomodModelOut,
                                     models.chosen = 'all',
                                     em.by = 'all',
                                     em.algo = c('EMmean', 'EMca'),
                                     metric.select = c('TSS'),
                                     metric.select.thresh = c(0.7),
                                     metric.eval = c('TSS', 'AUCroc'),
                                     var.import = 3,

```

```

seed.val = 42)

myBiomodEM

# Get evaluation scores & variables importance
get_evaluations(myBiomodEM)
get_variables_importance(myBiomodEM)

# Represent evaluation scores
bm_PlotEvalMean(bm.out = myBiomodEM, dataset = 'calibration')
bm_PlotEvalBoxplot(bm.out = myBiomodEM, group.by = c('algo', 'algo'))

# # Represent variables importance
# bm_PlotVarImpBoxplot(bm.out = myBiomodEM, group.by = c('expl.var', 'algo', 'algo'))
# bm_PlotVarImpBoxplot(bm.out = myBiomodEM, group.by = c('expl.var', 'algo', 'merged.by.PA'))
# bm_PlotVarImpBoxplot(bm.out = myBiomodEM, group.by = c('algo', 'expl.var', 'merged.by.PA'))

# # Represent response curves
# bm_PlotResponseCurves(bm.out = myBiomodEM,
#                         models.chosen = get_built_models(myBiomodEM),
#                         fixed.var = 'median')
# bm_PlotResponseCurves(bm.out = myBiomodEM,
#                         models.chosen = get_built_models(myBiomodEM),
#                         fixed.var = 'min')
# bm_PlotResponseCurves(bm.out = myBiomodEM,
#                         models.chosen = get_built_models(myBiomodEM, algo = 'EMmean'),
#                         fixed.var = 'median',
#                         do.bivariate = TRUE)

```

---

|                      |                                                                                                |
|----------------------|------------------------------------------------------------------------------------------------|
| BIOMOD_FormatingData | <i>Format input data, and select pseudo-absences if wanted, for usage in</i><br><b>biomod2</b> |
|----------------------|------------------------------------------------------------------------------------------------|

---

## Description

This function gathers together all input data needed (*xy, presences/absences, explanatory variables, and the same for evaluation data if available*) to run **biomod2** models. It allows to select pseudo-absences if no absence data is available, with different strategies (see Details).

## Usage

```

BIOMOD_FormatingData(
  resp.name,
  resp.var,
  resp.xy = NULL,
  expl.var,
  dir.name = ".",
  data.type = "binary",

```

```

eval.resp.var = NULL,
eval.resp.xy = NULL,
eval.expl.var = NULL,
PA.strategy = NULL,
PA.nb.rep = NULL,
PA.nb.absences = NULL,
PA.dist.min = 0,
PA.dist.max = NULL,
PA.sre.quant = NULL,
PA.fact.aggr = NULL,
PA.user.table = NULL,
na.rm = TRUE,
filter.raster = FALSE,
seed.val = NULL
)

```

### Arguments

|               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|---------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| resp.name     | a character corresponding to the species name                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| resp.var      | <p>a vector, a <a href="#">SpatVector</a> without associated data (<i>if presence-only</i>), or a <a href="#">SpatVector</a> object containing binary data (1 : presence, 0 : absence, NA : indeterminate) or other data (see <code>data.type</code> and <code>Details</code>) for a single species that will be used to build the species distribution model(s)</p> <p><i>Note that old format from <b>sp</b> are still supported such as <code>SpatialPoints</code> (if presence-only) or <code>SpatialPointsDataFrame</code> object containing binary data or other data.</i></p> |
| resp.xy       | <p>(optional, default NULL)</p> <p>If <code>resp.var</code> is a vector, a 2-columns matrix or <code>data.frame</code> containing the corresponding X and Y coordinates that will be used to build the species distribution model(s)</p>                                                                                                                                                                                                                                                                                                                                             |
| expl.var      | <p>a matrix, <code>data.frame</code>, <a href="#">SpatVector</a> or <a href="#">SpatRaster</a> object containing the explanatory variables (in columns or layers) that will be used to build the species distribution model(s)</p> <p><i>Note that old format from <b>raster</b> and <b>sp</b> are still supported such as <code>RasterStack</code> and <code>SpatialPointsDataFrame</code> objects.</i></p>                                                                                                                                                                         |
| dir.name      | <p>(optional, default .)</p> <p>A character corresponding to the modeling folder</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| data.type     | <p>a character, corresponding to the response data type to be used, must be either binary, count, multiclass, ordinal, relative, or abundance, and match the data contained in <code>resp.var</code></p> <p><i>If not provided, biomod2 will try to guess.</i></p>                                                                                                                                                                                                                                                                                                                   |
| eval.resp.var | <p>(optional, default NULL)</p> <p>A vector or a <a href="#">SpatVector</a> object containing binary data (1 : presence, 0 : absence) for a single species that will be used to evaluate the species distribution model(s) with independent data</p> <p><i>Note that old format from <b>sp</b> are still supported such as <code>SpatialPoints</code> (if presence-only) or <code>SpatialPointsDataFrame</code> object containing binary data.</i></p>                                                                                                                               |

|                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| eval.resp.xy   | (optional, default NULL)<br>If resp.var is a vector, a 2-columns matrix or data.frame containing the corresponding X and Y coordinates that will be used to evaluate the species distribution model(s) with independent data                                                                                                                                                                                                                                       |
| eval.expl.var  | (optional, default NULL)<br>A matrix, data.frame, <a href="#">SpatVector</a> or <a href="#">SpatRaster</a> object containing the explanatory variables (in columns or layers) that will be used to evaluate the species distribution model(s) with independent data.<br><i>Note that old format from <b>raster</b> and <b>sp</b> are still supported such as RasterStack and SpatialPointsDataFrame objects.</i>                                                   |
| PA.strategy    | (optional, default NULL)<br>If pseudo-absence selection, a character defining the strategy that will be used to select the pseudo-absence points. Must be random, sre, disk or user.defined (see Details)                                                                                                                                                                                                                                                          |
| PA.nb.rep      | (optional, default NULL)<br>If pseudo-absence selection, an integer corresponding to the number of sets (repetitions) of pseudo-absence points that will be drawn                                                                                                                                                                                                                                                                                                  |
| PA.nb.absences | (optional, default NULL)<br>If pseudo-absence selection, and PA.strategy = 'random' or PA.strategy = 'sre' or PA.strategy = 'disk', an integer corresponding to the number of pseudo-absence points that will be selected for each pseudo-absence repetition (true absences included).<br>It can also be a vector of the same length as PA.nb.rep containing integer values corresponding to the different numbers of pseudo-absences to be selected (see Details) |
| PA.dist.min    | (optional, default 0)<br>If pseudo-absence selection and PA.strategy = 'disk', a numeric defining the minimal distance to presence points used to make the disk pseudo-absence selection (in the same projection system units as resp.xy and expl.var, see Details)                                                                                                                                                                                                |
| PA.dist.max    | (optional, default NULL)<br>If pseudo-absence selection and PA.strategy = 'disk', a numeric defining the maximal distance to presence points used to make the disk pseudo-absence selection (in the same projection system units as resp.xy and expl.var, see Details)                                                                                                                                                                                             |
| PA.sre.quant   | (optional, default NULL)<br>If pseudo-absence selection and PA.strategy = 'sre', a numeric between 0 and 0.5 defining the half-quantile used to make the sre pseudo-absence selection (see Details)                                                                                                                                                                                                                                                                |
| PA.fact.aggr   | (optional, default NULL)<br>If pseudo-absence selection and PA.strategy = 'random' or PA.strategy = 'disk', an integer defining the factor of aggregation to reduce the spatial resolution of the environmental variables                                                                                                                                                                                                                                          |
| PA.user.table  | (optional, default NULL)<br>If pseudo-absence selection and PA.strategy = 'user.defined', a matrix or data.frame with as many rows as resp.var values, as many columns as                                                                                                                                                                                                                                                                                          |

|               |                                                                                                                                                                               |
|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|               | PA.nb.rep, and containing TRUE or FALSE values defining which points will be used to build the species distribution model(s) for each repetition (see Details)                |
| na.rm         | (optional, default TRUE)<br>A logical value defining whether points having one or several missing values for explanatory variables should be removed from the analysis or not |
| filter.raster | (optional, default FALSE)<br>If expl.var is of raster type, a logical value defining whether resp.var is to be filtered when several points occur in the same raster cell     |
| seed.val      | (optional, default NULL)<br>An integer value corresponding to the new seed value to be set                                                                                    |

### Details

This function gathers and formats all input data needed to run **biomod2** models. It supports different kind of inputs (e.g. matrix, [SpatVector](#), [SpatRaster](#)) and provides different methods to select pseudo-absences if needed.

#### Concerning explanatory variables and XY coordinates :

- if [SpatRaster](#), RasterLayer or RasterStack provided for expl.var or eval.expl.var, **biomod2** will extract the corresponding values from XY coordinates provided :
  - either through resp.xy or eval.resp.xy respectively
  - or through resp.var or eval.resp.var, if provided as [SpatVector](#) or SpatialPointsDataFrame

*Be sure to give the objects containing XY coordinates in the same projection system than the raster objects !*

- if data.frame or matrix provided for expl.var or eval.expl.var, **biomod2** will simply merge it (cbind) with resp.var without considering XY coordinates.  
*Be sure to give explanatory and response values in the same row order !*

#### Concerning pseudo-absence selection (see [bm\\_PseudoAbsences](#)) :

*Only in the case of binary data !*

- if both presence and absence data are available : PA.nb.rep = 0 and no pseudo-absence will be selected.
- if no absence data is available, several pseudo-absence repetitions are recommended (to estimate the effect of pseudo-absence selection), as well as high number of pseudo-absence points.  
*Be sure not to select more pseudo-absence points than maximum number of pixels in the studied area !*
- it is possible to create several pseudo-absence repetitions *with different number of points*, BUT with the same sampling strategy. PA.nb.absences must contain as many values as the number of sets of pseudo-absences (PA.nb.rep).

**Response variable biomod2** models single species at a time (no multi-species).

Hence, `resp.var` must be a uni-dimensional object, either :

- a vector, a one-column matrix or `data.frame`, a [SpatVector](#) (*without associated data - if presence-only*)
- a `SpatialPoints` (*if presence-only*)
- a `SpatialPointsDataFrame` or [SpatVector](#) object

If `resp.var` is a non-spatial object (vector, matrix or `data.frame`), XY coordinates must be provided through `resp.xy`.

Different data types are available, and require different values :

**binary** 1 : presences, 0 : true absences or NA : no information point (can be used to select pseudo-absences)

*If no true absences are available, pseudo-absence selection must be done.*

**count** positive integer values

**multiclass** factor values

**ordinal** ordered factor values

**relative** numeric values between 0 and 1

**abundance** positive numeric values

**Explanatory variables** Factorial variables are allowed, but might lead to some pseudo-absence strategy or models omissions (e.g. `sre`).

**Evaluation data** Although **biomod2** provides tools to automatically divide dataset into calibration and validation parts through the modeling process (see `CV.[. .]` parameters in [BIOMOD\\_Modeling](#) function ; or [bm\\_CrossValidation](#) function), it is also possible (and strongly advised) to directly provide two independent datasets, one for calibration/validation and one for evaluation

**Pseudo-absence selection (see [bm\\_PseudoAbsences](#))** *Only in the case of binary data !*

If no true absences are available, pseudo-absences must be selected from the *background data*, meaning data there is no information whether the species of interest occurs or not. It corresponds either to the remaining pixels of the `expl.var` (if provided as a [SpatRaster](#) or `RasterStack`) or to the points identified as NA in `resp.var` (if `expl.var` provided as a matrix or `data.frame`).

Several methods are available to do this selection :

**random** all points of initial background are pseudo-absence candidates. `PA.nb.absences` are drawn randomly, for each `PA.nb.rep` requested.

**sre** pseudo-absences have to be selected in conditions (combination of explanatory variables) that differ in a defined proportion (`PA.sre.quant`) from those of presence points. A *Surface Range Envelop* model is first run over the species of interest (see [bm\\_SRE](#)), and pseudo-absences are selected outside this envelop.

*This case is appropriate when all the species climatic niche has been sampled, otherwise it may lead to over-optimistic model evaluations and predictions !*

**disk** pseudo-absences are selected within circles around presence points defined by `PA.dist.min` and `PA.dist.max` distance values (in the same projection system units as `coord` and `expl.var`). It allows to select pseudo-absence points that are not too close to (avoid same niche and pseudo-replication) or too far (localized sampling strategy) from presences.

**user.defined** pseudo-absences are defined in advance and given as `data.frame` through the `PA.user.table` parameter.

**Value**

A `BIOMOD.formated.data` or `BIOMOD.formated.data.PA` object that can be used to build species distribution model(s) with the `BIOMOD_Modeling` function.

`print/show`, `plot` and `summary` functions are available to have a summary of the created object.

**Author(s)**

Damien Georges, Wilfried Thuiller

**See Also**

`bm_PseudoAbsences`, `BIOMOD_Modeling`

Other Main functions: `BIOMOD_EnsembleForecasting()`, `BIOMOD_EnsembleModeling()`, `BIOMOD_LoadModels()`, `BIOMOD_Modeling()`, `BIOMOD_Projection()`, `BIOMOD_RangeSize()`

**Examples**

```
library(terra)

# Load species occurrences (6 species available)
data(DataSpecies)
head(DataSpecies)

# Select the name of the studied species
myRespName <- 'GuloGulo'

# Get corresponding presence/absence data
myResp <- as.numeric(DataSpecies[, myRespName])

# Get corresponding XY coordinates
myRespXY <- DataSpecies[, c('X_WGS84', 'Y_WGS84')]

# Load environmental variables extracted from BIOCLIM (bio_3, bio_4, bio_7, bio_11 & bio_12)
data(bioclim_current)
myExpl <- terra::rast(bioclim_current)

# -----#
# Format Data with true absences
myBiomodData <- BIOMOD_FormatingData(resp.name = myRespName,
                                     resp.var = myResp,
                                     resp.xy = myRespXY,
                                     expl.var = myExpl)

myBiomodData
summary(myBiomodData)
plot(myBiomodData)

# -----#
# # Transform true absences into potential pseudo-absences
```

```

# myResp.PA <- ifelse(myResp == 1, 1, NA)
#
# # Format Data with pseudo-absences : random method
# myBiomodData.r <- BIOMOD_FormatingData(resp.name = myRespName,
#                                       resp.var = myResp.PA,
#                                       resp.xy = myRespXY,
#                                       expl.var = myExpl,
#                                       PA.nb.rep = 4,
#                                       PA.nb.absences = 1000,
#                                       PA.strategy = 'random')
#
# # Format Data with pseudo-absences : disk method
# myBiomodData.d <- BIOMOD_FormatingData(resp.name = myRespName,
#                                       resp.var = myResp.PA,
#                                       resp.xy = myRespXY,
#                                       expl.var = myExpl,
#                                       PA.nb.rep = 4,
#                                       PA.nb.absences = 500,
#                                       PA.strategy = 'disk',
#                                       PA.dist.min = 5,
#                                       PA.dist.max = 35)
#
# # Format Data with pseudo-absences : SRE method
# myBiomodData.s <- BIOMOD_FormatingData(resp.name = myRespName,
#                                       resp.var = myResp.PA,
#                                       resp.xy = myRespXY,
#                                       expl.var = myExpl,
#                                       PA.nb.rep = 4,
#                                       PA.nb.absences = 1000,
#                                       PA.strategy = 'sre',
#                                       PA.sre.quant = 0.025)
#
# # Format Data with pseudo-absences : user.defined method
# myPatable <- data.frame(PA1 = ifelse(myResp == 1, TRUE, FALSE),
#                         PA2 = ifelse(myResp == 1, TRUE, FALSE))
# for (i in 1:ncol(myPatable)) myPatable[sample(which(myPatable[, i] == FALSE), 500), i] = TRUE
# myBiomodData.u <- BIOMOD_FormatingData(resp.name = myRespName,
#                                       resp.var = myResp.PA,
#                                       resp.xy = myRespXY,
#                                       expl.var = myExpl,
#                                       PA.strategy = 'user.defined',
#                                       PA.user.table = myPatable)
#
# myBiomodData.r
# myBiomodData.d
# myBiomodData.s
# myBiomodData.u
# plot(myBiomodData.r)
# plot(myBiomodData.d)
# plot(myBiomodData.s)
# plot(myBiomodData.u)

```

```

# -----#
# # Select multiple sets of pseudo-absences
#
# # Transform true absences into potential pseudo-absences
# myResp.PA <- ifelse(myResp == 1, 1, NA)
#
# # Format Data with pseudo-absences : random method
# myBiomodData.multi <- BIOMOD_FormatingData(resp.name = myRespName,
#                                           resp.var = myResp.PA,
#                                           resp.xy = myRespXY,
#                                           expl.var = myExpl,
#                                           PA.nb.rep = 4,
#                                           PA.nb.absences = c(1000, 500, 500, 200),
#                                           PA.strategy = 'random')
# myBiomodData.multi
# summary(myBiomodData.multi)
# plot(myBiomodData.multi)

```

---

BIOMOD\_LoadModels

*Load species distribution models built with **biomod2***


---

## Description

This function loads individual models built with [BIOMOD\\_Modeling](#) or [BIOMOD\\_EnsembleModeling](#) functions.

## Usage

```

BIOMOD_LoadModels(
  bm.out,
  full.name = NULL,
  PA = NULL,
  run = NULL,
  algo = NULL,
  merged.by.PA = NULL,
  merged.by.run = NULL,
  merged.by.algo = NULL,
  filtered.by = NULL
)

```

## Arguments

**bm.out** a [BIOMOD.models.out](#) or [BIOMOD.ensemble.models.out](#) object that can be obtained with the [BIOMOD\\_Modeling](#) or [BIOMOD\\_EnsembleModeling](#) functions

|                |                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| full.name      | <i>(optional, default NULL)</i><br>A vector containing model names to be kept, must be either all or a sub-selection of model names that can be obtained with the <a href="#">get_built_models</a> function applied to <code>bm.out</code>                                                                                                                                                                                          |
| PA             | <i>(optional, default NULL)</i><br>A vector containing pseudo-absence set to be loaded, must be among PA1, PA2, ..., allData                                                                                                                                                                                                                                                                                                        |
| run            | <i>(optional, default NULL)</i><br>A vector containing repetition set to be loaded, must be among RUN1, RUN2, ..., allRun                                                                                                                                                                                                                                                                                                           |
| algo           | <i>(optional, default NULL)</i><br>A character containing algorithm to be loaded, must be either ANN, CTA, FDA, GAM, GBM, GLM, MARS, MAXENT, MAXNET, RF, RFd, SRE, XGBOOST                                                                                                                                                                                                                                                          |
| merged.by.PA   | <i>(optional, default NULL)</i><br>A vector containing merged pseudo-absence set to be loaded, must be among PA1, PA2, ..., mergedData                                                                                                                                                                                                                                                                                              |
| merged.by.run  | <i>(optional, default NULL)</i><br>A vector containing merged repetition set to be loaded, must be among RUN1, RUN2, ..., mergedRun                                                                                                                                                                                                                                                                                                 |
| merged.by.algo | <i>(optional, default NULL)</i><br>A character containing merged algorithm to be loaded, must be among ANN, CTA, FDA, GAM, GBM, GLM, MARS, MAXENT, MAXNET, RF, RFd, SRE, XGBOOST, mergedAlgo                                                                                                                                                                                                                                        |
| filtered.by    | <i>(optional, default NULL)</i><br>A vector containing evaluation metric selected to filter single models to build the ensemble models, must be among AUCroc, AUCprg, TSS, KAPPA, ACCURACY, BIAS, POD, FAR, POFD, SR, CSI, ETS, OR, ORSS, BOYCE, MPA ( <i>binary data</i> ), RMSE, MAE, MSE, Rsquared, Rsquared_aj, Max_error ( <i>abundance / count / relative data</i> ), Accuracy, Recall, Precision, F1 ( <i>ordinal data</i> ) |

## Details

This function might be of particular use to load models and make response plot analyses.

Running the function providing only `bm.out` argument will load all models built by the [BIOMOD\\_Modeling](#) or [BIOMOD\\_EnsembleModeling](#) function, but a subselection of models can be done using the additional arguments (`full.name`, `PA`, `run`, `algo`, `merged.by.PA`, `merged.by.run`, `merged.by.algo`, `filtered.by`).

## Value

A vector containing the names of the loaded models.

## Author(s)

Damien Georges

**See Also**

[BIOMOD\\_Modeling](#), [BIOMOD\\_EnsembleModeling](#)

Other Main functions: [BIOMOD\\_EnsembleForecasting\(\)](#), [BIOMOD\\_EnsembleModeling\(\)](#), [BIOMOD\\_FormatingData\(\)](#), [BIOMOD\\_Modeling\(\)](#), [BIOMOD\\_Projection\(\)](#), [BIOMOD\\_RangeSize\(\)](#)

**Examples**

```
library(terra)

# Load species occurrences (6 species available)
data(DataSpecies)
head(DataSpecies)

# Select the name of the studied species
myRespName <- 'GuloGulo'

# Get corresponding presence/absence data
myResp <- as.numeric(DataSpecies[, myRespName])

# Get corresponding XY coordinates
myRespXY <- DataSpecies[, c('X_WGS84', 'Y_WGS84')]

# Load environmental variables extracted from BIOCLIM (bio_3, bio_4, bio_7, bio_11 & bio_12)
data(bioclim_current)
myExpl <- terra::rast(bioclim_current)

# -----
file.out <- paste0(myRespName, "/", myRespName, ".AllModels.models.out")
if (file.exists(file.out)) {
  myBiomodModelOut <- get(load(file.out))
} else {

  # Format Data with true absences
  myBiomodData <- BIOMOD_FormatingData(resp.name = myRespName,
                                       resp.var = myResp,
                                       resp.xy = myRespXY,
                                       expl.var = myExpl)

  # Model single models
  myBiomodModelOut <- BIOMOD_Modeling(bm.format = myBiomodData,
                                     modeling.id = 'AllModels',
                                     models = c('RF', 'GLM'),
                                     CV.strategy = 'random',
                                     CV.nb.rep = 2,
                                     CV.perc = 0.8,
                                     OPT.strategy = 'bigboss',
                                     metric.eval = c('TSS', 'AUCroc'),
                                     var.import = 3,
                                     seed.val = 42)
}
```

```
# -----
# Loading some models built
BIOMOD_LoadModels(bm.out = myBiomodModelOut, algo = 'RF')
```

---

BIOMOD\_Modeling

---

*Run a range of species distribution models*


---

## Description

This function allows to calibrate and evaluate a range of modeling techniques for a given species distribution. The dataset can be split up in calibration/validation parts, and the predictive power of the different models can be estimated using a range of evaluation metrics (see Details).

## Usage

```
BIOMOD_Modeling(
  bm.format,
  modeling.id,
  models = c("ANN", "CTA", "DNN", "FDA", "GAM", "GBM", "GLM", "MARS", "MAXENT", "MAXNET",
    "RF", "RFd", "SRE", "XGBOOST"),
  models.pa = NULL,
  CV.strategy = NULL,
  CV.nb.rep = NULL,
  CV.perc = NULL,
  CV.k = NULL,
  CV.balance = NULL,
  CV.env.var = NULL,
  CV.strat = NULL,
  CV.user.table = NULL,
  CV.do.full.models = NULL,
  OPT.strategy = "default",
  OPT.user.val = NULL,
  OPT.user.base = NULL,
  OPT.user = NULL,
  metric.eval = NULL,
  var.import = 0,
  weights = NULL,
  prevalence = 0.5,
  scale.models = FALSE,
  nb.cpu = 1,
  seed.val = NULL,
  do.progress = TRUE
)
```

**Arguments**

|                                |                                                                                                                                                                                                                                                                             |
|--------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>bm.format</code>         | a <code>BIOMOD.formated.data</code> or <code>BIOMOD.formated.data.PA</code> object returned by the <code>BIOMOD_FormatingData</code> function                                                                                                                               |
| <code>modeling.id</code>       | a character corresponding to the name (ID) of the simulation set ( <i>a random number by default</i> )                                                                                                                                                                      |
| <code>models</code>            | a vector containing model names to be computed, must be among ANN, CTA, DNN, FDA, GAM, GBM, GLM, MARS, MAXENT, MAXNET, RF, RFd, SRE, XGBOOST                                                                                                                                |
| <code>models.pa</code>         | ( <i>optional, default NULL</i> )<br>A list containing for each model a vector defining which pseudo-absence datasets are to be used, must be among <code>colnames(bm.format@PA.table)</code>                                                                               |
| <code>CV.strategy</code>       | ( <i>optional, default NULL</i> )<br>A character corresponding to the cross-validation selection strategy, must be among <code>random</code> , <code>kfold</code> , <code>block</code> , <code>strat</code> , <code>env</code> or <code>user.defined</code>                 |
| <code>CV.nb.rep</code>         | ( <i>optional, default NULL</i> )<br>If <code>strategy = 'random'</code> or <code>strategy = 'kfold'</code> , an integer corresponding to the number of sets (repetitions) of cross-validation points that will be drawn                                                    |
| <code>CV.perc</code>           | ( <i>optional, default NULL</i> )<br>If <code>strategy = 'random'</code> , a numeric between 0 and 1 defining the percentage of data that will be kept for calibration                                                                                                      |
| <code>CV.k</code>              | ( <i>optional, default NULL</i> )<br>If <code>strategy = 'kfold'</code> or <code>strategy = 'strat'</code> or <code>strategy = 'env'</code> , an integer corresponding to the number of partitions                                                                          |
| <code>CV.balance</code>        | ( <i>optional, default NULL</i> )<br>If <code>strategy = 'strat'</code> or <code>strategy = 'env'</code> , a character corresponding to how data will be balanced between partitions, must be either <code>presences</code> or <code>absences</code>                        |
| <code>CV.env.var</code>        | ( <i>optional, default NULL</i> )<br>If <code>strategy = 'env'</code> , a character corresponding to the environmental variables used to build the partition (all available variables by default), and for which <code>CV.k</code> partitions will be built                 |
| <code>CV.strat</code>          | ( <i>optional, default NULL</i> )<br>If <code>strategy = 'strat'</code> , a character corresponding to how data will be partitioned along gradient, must be among <code>x</code> , <code>y</code> , <code>both</code>                                                       |
| <code>CV.user.table</code>     | ( <i>optional, default NULL</i> )<br>If <code>strategy = 'user.defined'</code> , a matrix or data.frame defining for each repetition (in columns) which observation lines should be used for models calibration ( <code>TRUE</code> ) and validation ( <code>FALSE</code> ) |
| <code>CV.do.full.models</code> | ( <i>optional, default NULL</i> )<br>A logical value defining whether models should be also calibrated and validated over the whole dataset (and pseudo-absence datasets) or not                                                                                            |
| <code>OPT.strategy</code>      | ( <i>default 'default'</i> )<br>A character corresponding to the method to select models' parameters values, must be either <code>default</code> , <code>bigboss</code> , <code>user.defined</code> , <code>tuned</code>                                                    |

|                            |                                                                                                                                                                                                                                                                                                                                                                   |
|----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>OPT.user.val</code>  | <i>(optional, default NULL)</i><br>A list containing parameters values for some (all) models                                                                                                                                                                                                                                                                      |
| <code>OPT.user.base</code> | <i>(optional, default NULL)</i><br>A character, default or bigboss used when <code>OPT.strategy = 'user.defined'</code> .<br>It sets the bases of parameters to be modified by user defined values.                                                                                                                                                               |
| <code>OPT.user</code>      | <i>(optional, default NULL)</i><br>A <code>BIOMOD.models.options</code> object returned by the <code>bm_ModelingOptions</code> function                                                                                                                                                                                                                           |
| <code>metric.eval</code>   | a vector containing evaluation metric names to be used, must be among AUCroc, AUCprg, TSS, KAPPA, ACCURACY, BIAS, POD, FAR, POFD, SR, CSI, ETS, OR, ORSS, BOYCE, MPA ( <i>binary data</i> ), RMSE, MAE, MSE, Rsquared, Rsquared_aj, Max_error ( <i>abundance / count / relative data</i> ), Accuracy, Recall, Precision, F1 ( <i>multi-class / ordinal data</i> ) |
| <code>var.import</code>    | <i>(optional, default 0)</i><br>An integer corresponding to the number of permutations to be done for each variable to estimate variable importance                                                                                                                                                                                                               |
| <code>weights</code>       | <i>(optional, default NULL)</i><br>A vector of numeric values corresponding to observation weights (one per observation, see Details)                                                                                                                                                                                                                             |
| <code>prevalence</code>    | <i>(optional, default 0.5)</i><br>A numeric between 0 and 1 corresponding to the species prevalence to build 'weighted response weights' (see Details)                                                                                                                                                                                                            |
| <code>scale.models</code>  | <i>(optional, default FALSE)</i><br>A logical value defining whether all models predictions should be scaled with a binomial GLM or not                                                                                                                                                                                                                           |
| <code>nb.cpu</code>        | <i>(optional, default 1)</i><br>An integer value corresponding to the number of computing resources to be used to parallelize the single models computation                                                                                                                                                                                                       |
| <code>seed.val</code>      | <i>(optional, default NULL)</i><br>An integer value corresponding to the new seed value to be set                                                                                                                                                                                                                                                                 |
| <code>do.progress</code>   | <i>(optional, default TRUE)</i><br>A logical value defining whether the progress bar is to be rendered or not                                                                                                                                                                                                                                                     |

## Details

**bm.format** If pseudo-absences have been added to the original dataset (see [BIOMOD\\_FormatingData](#)),  $PA.nb.rep * (nb.rep + 1)$  models will be created.

**models** The set of models to be calibrated on the data. 12 modeling techniques are currently available :

- ANN : Artificial Neural Network ([nnet](#))
- CTA : Classification Tree Analysis ([rpart](#))
- DNN : Deep Neural Network ([cito](#))
- FDA : Flexible Discriminant Analysis ([fda](#))
- GAM : Generalized Additive Model ([gam](#), [gam](#) or [bam](#))  
(see [bm\\_ModelingOptions](#) for details on algorithm selection)

- GBM : Generalized Boosting Model, or usually called Boosted Regression Trees ([gbm](#))
- GLM : Generalized Linear Model ([glm](#))
- MARS : Multiple Adaptive Regression Splines ([earth](#))
- MAXENT : Maximum Entropy ([see Maxent website](#))
- MAXNET : Maximum Entropy ([maxnet](#))
- RF : Random Forest ([randomForest](#))
- RFd : Random Forest downsampled ([randomForest](#))
- SRE : Surface Range Envelop or usually called BIOCLIM ([bm\\_SRE](#))
- XGBOOST : eXtreme Gradient Boosting Training ([xgboost](#))

|                              | ANN | CTA | DNN | FDA | GAM | GBM | GLM | MARS | MAXENT | MAXNET |
|------------------------------|-----|-----|-----|-----|-----|-----|-----|------|--------|--------|
| binary                       | x   | x   | x   | x   | x   | x   | x   | x    | x      | x      |
| multiclass                   |     | x   | x   | x   |     |     |     | x    |        |        |
| ordinal                      |     | x   | x   | x   | x   |     | x   | x    |        |        |
| abundance / count / relative |     | x   | x   |     | x   | x   | x   | x    |        |        |

**models.pa** Different models might respond differently to different numbers of pseudo-absences. It is possible to create sets of pseudo-absences with different numbers of points (see [BIOMOD\\_FormatingData](#)) and to assign only some of these datasets to each single model.

**CV**[... parameters] Different methods are available to calibrate/validate the single models (see [bm\\_CrossValidation](#)).

**OPT**[... parameters] Different methods are available to parameterize the single models (see [bm\\_ModelingOptions](#) and [BIOMOD.options.dataset](#)).

- **default** : only default parameter values of default parameters of the single models functions are retrieved. Nothing is changed so it might not give good results.
- **bigboss** : uses parameters pre-defined by **biomod2** team and that are available in the dataset [OptionsBigboss](#).  
*to be optimized in near future*
- **user.defined** : updates default or bigboss parameters with some parameters values defined by the user (but matching the format of a [BIOMOD.models.options](#) object)
- **tuned** : calling the [bm\\_Tuning](#) function to try and optimize some default values

**metric.eval** Please refer to [JWGFVR website \("Forecast verification - methods, issues and FAQ"\)](#) to get detailed description (simple/complex metrics).

Several evaluation metrics can be selected.

Optimal value of each method can be obtained with the [get\\_optim\\_value](#) function.

**simple** • **POD** : Probability of detection (hit rate)

- **FAR** : False alarm ratio
- **POFD** : Probability of false detection (fall-out)
- **SR** : Success ratio
- **ACCURACY** : Accuracy (fraction correct)
- **BIAS** : Bias score (frequency bias)

**complex** • **AUCroc** : Area Under Curve of Relative operating characteristic

- **AUCprg** : Area Under Curve of Precision-Recall-Gain curve
- **TSS** : True skill statistic (Hanssen and Kuipers discriminant, Peirce's skill score)

- KAPPA : Cohen's Kappa (Heidke skill score)
- OR : Odds Ratio
- ORSS : Odds ratio skill score (Yule's Q)
- CSI : Critical success index (threat score)
- ETS : Equitable threat score (Gilbert skill score)

**presence-only** • BOYCE : Boyce index

- MPA : Minimal predicted area (cutoff optimizing MPA to predict 90% of presences)

**abundance / count / relative data** • RMSE : Root Mean Square Error

- MSE : Mean Square Error
- MAE : Mean Absolute Error
- Rsquared : R squared
- Rsquared\_adj : R squared adjusted
- Max\_error : Maximum error

**multiclass/ordinal data** • Accuracy : Accuracy

- Recall : Macro average Recall
- Precision : Macro average Precision
- F1 : Macro F1 score

Results after modeling can be obtained through the `get_evaluations` function.

Evaluation metric are calculated on the calibrating data (column calibration), on the cross-validation data (column validation) or on the evaluation data (column evaluation).

*For cross-validation data, see CV.[...] parameters in BIOMOD\_Modeling function.*

*For evaluation data, see eval.[...] parameters in BIOMOD\_FormatingData.*

**var.import** A value characterizing how much each variable has an impact on each model predictions can be calculated by randomizing the variable of interest and computing the correlation between original and shuffled variables (see `bm_VariablesImportance`).

**weights & prevalence** More or less weight can be given to some specific observations.

Automatically created weights will be integer values to prevent some modeling issues.

*Note that DNN, MAXENT, MAXNET and SRE models do not take weights into account.*

- If prevalence = 0.5 (the default), presences and absences will be weighted equally (*i.e. the weighted sum of presences equals the weighted sum of absences*).
- If prevalence is set below (above) 0.5, more weight will be given to absences (presences).
- If weights is defined, prevalence argument will be ignored (*EXCEPT for MAXENT*).

**scale.models** A binomial GLM is created to scale predictions from 0 to 1.

SRE is never scaled, and ANN and FDA categorical models always are.

*Note that it may lead to reduction in projected scale amplitude.*

**This parameter is quite experimental and it is recommended not to use it.** It was developed in the idea to ensure comparable predictions by removing the scale prediction effect (*the more extended projections are, the more they influence ensemble forecasting results*).

## Value

A `BIOMOD.models.out` object containing models outputs, or links to saved outputs.

Models outputs are stored out of R (for memory storage reasons) in 2 different folders created in the current working directory :



```

# ----- #
# Model single models
myBiomodModelOut <- BIOMOD_Modeling(bm.format = myBiomodData,
                                   modeling.id = 'AllModels',
                                   models = c('RF', 'GLM'),
                                   CV.strategy = 'random',
                                   CV.nb.rep = 2,
                                   CV.perc = 0.8,
                                   OPT.strategy = 'bigboss',
                                   metric.eval = c('TSS', 'AUCroc'),
                                   var.import = 2,
                                   seed.val = 42)

myBiomodModelOut

# Get evaluation scores & variables importance
get_evaluations(myBiomodModelOut)
get_variables_importance(myBiomodModelOut)

# Represent evaluation scores
bm_PlotEvalMean(bm.out = myBiomodModelOut, dataset = 'calibration')
bm_PlotEvalMean(bm.out = myBiomodModelOut, dataset = 'validation')
bm_PlotEvalBoxplot(bm.out = myBiomodModelOut, group.by = c('algo', 'run'))

# # Represent variables importance
# bm_PlotVarImpBoxplot(bm.out = myBiomodModelOut, group.by = c('expl.var', 'algo', 'algo'))
# bm_PlotVarImpBoxplot(bm.out = myBiomodModelOut, group.by = c('expl.var', 'algo', 'run'))
# bm_PlotVarImpBoxplot(bm.out = myBiomodModelOut, group.by = c('algo', 'expl.var', 'run'))

# # Represent response curves
# mods <- get_built_models(myBiomodModelOut, run = 'RUN1')
# bm_PlotResponseCurves(bm.out = myBiomodModelOut,
#                        models.chosen = mods,
#                        fixed.var = 'median')
# bm_PlotResponseCurves(bm.out = myBiomodModelOut,
#                        models.chosen = mods,
#                        fixed.var = 'min')
# mods <- get_built_models(myBiomodModelOut, full.name = 'GuloGulo_allData_RUN2_RF')
# bm_PlotResponseCurves(bm.out = myBiomodModelOut,
#                        models.chosen = mods,
#                        fixed.var = 'median',
#                        do.bivariate = TRUE)

```

---

BIOMOD\_Projection

---

*Project a range of calibrated species distribution models onto new environment*


---

## Description

This function allows to project a range of models built with the [BIOMOD\\_Modeling](#) function onto new environmental data (*which can represent new areas, resolution or time scales for example*).

**Usage**

```

BIOMOD_Projection(
  bm.mod,
  proj.name,
  new.env,
  new.env.xy = NULL,
  models.chosen = "all",
  metric.binary = NULL,
  metric.filter = NULL,
  build.clamping.mask = TRUE,
  nb.cpu = 1,
  seed.val = NULL,
  ...
)

```

**Arguments**

|               |                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| bm.mod        | a <a href="#">BIOMOD.models.out</a> object returned by the <a href="#">BIOMOD_Modeling</a> function                                                                                                                                                                                                                                                                                                                                                       |
| proj.name     | a character corresponding to the name (ID) of the projection set ( <i>a new folder will be created within the simulation folder with this name</i> )                                                                                                                                                                                                                                                                                                      |
| new.env       | A matrix, data.frame or <a href="#">SpatRaster</a> object containing the new explanatory variables (in columns or layers, with names matching the variables names given to the <a href="#">BIOMOD_FormatingData</a> function to build bm.mod) that will be used to project the species distribution model(s)<br><i>Note that old format from <b>raster</b> are still supported such as RasterStack objects.</i>                                           |
| new.env.xy    | (optional, default NULL)<br>If new.env is a matrix or a data.frame, a 2-columns matrix or data.frame containing the corresponding X and Y coordinates that will be used to project the species distribution model(s)                                                                                                                                                                                                                                      |
| models.chosen | a vector containing model names to be kept, must be either all or a sub-selection of model names that can be obtained with the <a href="#">get_built_models</a> function applied to bm.mod                                                                                                                                                                                                                                                                |
| metric.binary | (optional, default NULL)<br>A vector containing evaluation metric names to be used to transform prediction values into binary values based on models evaluation scores obtained with the <a href="#">BIOMOD_Modeling</a> function. Must be among all (same evaluation metrics than those of bm.mod) or POD, FAR, POFD, SR, ACCURACY, BIAS, AUCroc, AUCprg, TSS, KAPPA, OR, ORSS, CSI, ETS, BOYCE, MPA<br><i>Note that this is for binary data only.</i>   |
| metric.filter | (optional, default NULL)<br>A vector containing evaluation metric names to be used to transform prediction values into filtered values based on models evaluation scores obtained with the <a href="#">BIOMOD_Modeling</a> function. Must be among all (same evaluation metrics than those of bm.mod) or POD, FAR, POFD, SR, ACCURACY, BIAS, AUCroc, AUCprg, TSS, KAPPA, OR, ORSS, CSI, ETS, BOYCE, MPA<br><i>Note that this is for binary data only.</i> |

|                                  |                                                                                                                                                             |
|----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>build.clamping.mask</code> | <i>(optional, default TRUE)</i><br>A logical value defining whether a clamping mask should be built and saved on hard drive or not (see Details)            |
| <code>nb.cpu</code>              | <i>(optional, default 1)</i><br>An integer value corresponding to the number of computing resources to be used to parallelize the single models computation |
| <code>seed.val</code>            | <i>(optional, default NULL)</i><br>An integer value corresponding to the new seed value to be set                                                           |
| <code>...</code>                 | <i>(optional, see Details)</i>                                                                                                                              |

### Details

If `models.chosen = 'all'`, projections are done for all calibration and pseudo-absences runs if applicable.

These projections may be used later by the [BIOMOD\\_EnsembleForecasting](#) function.

If `build.clamping.mask = TRUE`, a raster file will be saved within the projection folder. This mask values will correspond to the number of variables in each pixel that are out of their calibration / validation range, identifying locations where predictions are uncertain.

... can take the following values :

**omit.na** *(optional, default TRUE)* :

a logical value defining whether all not fully referenced environmental points will get NA as predictions or not

**digits** *(optional, default 0)* :

an integer value corresponding to the number of digits of the predictions

**on\_0\_1000** *(optional, default TRUE)* :

a logical value defining whether 0 - 1 probabilities are to be converted to 0 - 1000 scale to save memory on backup

**keep.in.memory** *(optional, default TRUE)* :

a logical value defining whether all projections are to be kept loaded at once in memory, or only links pointing to hard drive are to be returned

**do.stack** *(optional, default TRUE)* :

a logical value defining whether all projections are to be saved as one [SpatRaster](#) object or several [SpatRaster](#) files *(the default if projections are too heavy to be all loaded at once in memory)*

**output.format** *(optional, default .RData or .tif)* :

a character value corresponding to the projections saving format on hard drive, must be either `.grd`, `.img`, `.tif` or `.RData` (the default if `new.env` is given as `matrix` or `data.frame`)

**compress** *(optional, default TRUE)* :

a logical or a character value defining whether and how objects should be compressed when saved on hard drive. Must be either `TRUE`, `FALSE`, `gzip` (for Windows OS) or `xz` (for other OS)

**overwrite** (optional, default `do.stack`) :

a logical defining whether pre-existing projections with same modeling ID and project name should be replaced or not

### Value

A `BIOMOD.projection.out` object containing models projections, or links to saved outputs. Models projections are stored out of R (for memory storage reasons) in `proj.name` folder created in the current working directory :

1. the output is a `data.frame` if `new.env` is a `matrix` or a `data.frame`
2. it is a `SpatRaster` if `new.env` is a `SpatRaster` (or several `SpatRaster` objects, if `new.env` is too large)
3. raw projections, as well as binary and filtered projections (if asked), are saved in the `proj.name` folder

### Author(s)

Wilfried Thuiller, Damien Georges

### See Also

`BIOMOD_Modeling`, `BIOMOD_EnsembleModeling`, `BIOMOD_RangeSize`

Other Main functions: `BIOMOD_EnsembleForecasting()`, `BIOMOD_EnsembleModeling()`, `BIOMOD_FormatingData()`, `BIOMOD_LoadModels()`, `BIOMOD_Modeling()`, `BIOMOD_RangeSize()`

### Examples

```
library(terra)

# Load species occurrences (6 species available)
data(DataSpecies)
head(DataSpecies)

# Select the name of the studied species
myRespName <- 'GuloGulo'

# Get corresponding presence/absence data
myResp <- as.numeric(DataSpecies[, myRespName])

# Get corresponding XY coordinates
myRespXY <- DataSpecies[, c('X_WGS84', 'Y_WGS84')]

# Load environmental variables extracted from BIOCLIM (bio_3, bio_4, bio_7, bio_11 & bio_12)
data(bioclim_current)
myExpl <- terra::rast(bioclim_current)

# -----#
file.out <- paste0(myRespName, "/", myRespName, ".AllModels.models.out")
```

```

if (file.exists(file.out)) {
  myBiomodModelOut <- get(load(file.out))
} else {

  # Format Data with true absences
  myBiomodData <- BIOMOD_FormatingData(resp.name = myRespName,
                                       resp.var = myResp,
                                       resp.xy = myRespXY,
                                       expl.var = myExpl)

  # Model single models
  myBiomodModelOut <- BIOMOD_Modeling(bm.format = myBiomodData,
                                     modeling.id = 'AllModels',
                                     models = c('RF', 'GLM'),
                                     CV.strategy = 'random',
                                     CV.nb.rep = 2,
                                     CV.perc = 0.8,
                                     OPT.strategy = 'bigboss',
                                     metric.eval = c('TSS', 'AUCroc'),
                                     var.import = 3,
                                     seed.val = 42)
}

# -----#
# Project single models
file.proj <- paste0(myRespName, "/proj_Current/", myRespName, ".Current.projection.out")
if (file.exists(file.proj)) {
  myBiomodProj <- get(load(file.proj))
} else {
  myBiomodProj <- BIOMOD_Projection(bm.mod = myBiomodModelOut,
                                   proj.name = 'Current',
                                   new.env = myExpl,
                                   models.chosen = 'all')
}
myBiomodProj
plot(myBiomodProj)

```

---

BIOMOD\_RangeSize

---

*Analyze the range size differences between projections of species distribution models*


---

## Description

This function allows to calculate the absolute number of locations (pixels) lost, stable and gained, as well as the corresponding relative proportions, between two (or more) binary projections of (ensemble) species distribution models (*which can represent new time scales or environmental scenarios for example*).

**Usage**

```
BIOMOD_RangeSize(
  proj.current,
  proj.future,
  models.chosen = "all",
  metric.binary = NULL
)
```

**Arguments**

**proj.current** a BIOMOD.projection.out object containing the initial projection(s) of the (ensemble) species distribution model(s)

**proj.future** a BIOMOD.projection.out object containing the final binary projection(s) of the (ensemble) species distribution model(s)

**models.chosen** a vector containing model names to be kept, must be either all or a sub-selection of model names that can be obtained with the [get\\_projected\\_models](#) function

**metric.binary** (*optional, default NULL*)  
A vector containing evaluation metric selected to transform predictions into binary values, must be among POD, FAR, POFD, SR, ACCURACY, BIAS, AUCroc, AUCprg, TSS, KAPPA, OR, ORSS, CSI, ETS, BOYCE, MPA

**Value**

A BIOMOD.rangesize.out containing principally two objects :

**Compt.By.Species** a data.frame containing the summary of range change for each comparison

- **Loss** : number of pixels predicted to be lost
- **Stable\_Abs** : number of pixels not currently occupied and not predicted to be
- **Stable\_Pres** : number of pixels currently occupied and predicted to remain occupied
- **Gain** : number of pixels predicted to be gained
- **PercLoss** : percentage of pixels currently occupied and predicted to be lost ( $\text{Loss} / (\text{Loss} + \text{Stable\_Pres})$ )
- **PercGain** : percentage of pixels predicted to be gained compare to the number of pixels currently occupied ( $\text{Gain} / (\text{Loss} + \text{Stable\_Pres})$ )
- **SpeciesRangeChange** : percentage of pixels predicted to change (loss or gain) compare to the number of pixels currently occupied ( $\text{PercGain} - \text{PercLoss}$ )
- **CurrentRangeSize** : number of pixels currently occupied
- **FutureRangeSize0Disp** : number of pixels predicted to be occupied, assuming no migration
- **FutureRangeSize1Disp** : number of pixels predicted to be occupied, assuming migration

**loss.gain** an object in the same form than the input data (proj.current and proj.future) and containing a value for each point/pixel of each comparison among :

- -2 : predicted to be lost



```

                                resp.xy = myRespXY,
                                expl.var = myExpl)

# Model single models
myBiomodModelOut <- BIOMOD_Modeling(bm.format = myBiomodData,
                                   modeling.id = 'AllModels',
                                   models = c('RF', 'GLM'),
                                   CV.strategy = 'random',
                                   CV.nb.rep = 2,
                                   CV.perc = 0.8,
                                   OPT.strategy = 'bigboss',
                                   metric.eval = c('TSS', 'AUCroc'),
                                   var.import = 3,
                                   seed.val = 42)
}

models.proj <- get_built_models(myBiomodModelOut, algo = "RF")
# Project single models
myBiomodProj <- BIOMOD_Projection(bm.mod = myBiomodModelOut,
                                 proj.name = 'CurrentRangeSize',
                                 new.env = myExpl,
                                 models.chosen = models.proj,
                                 metric.binary = 'all',
                                 build.clamping.mask = TRUE)

# ----- #
# Load environmental variables extracted from BIOCLIM (bio_3, bio_4, bio_7, bio_11 & bio_12)
data(bioclim_future)
myExplFuture <- terra::rast(bioclim_future)

# Project onto future conditions
myBiomodProjectionFuture <- BIOMOD_Projection(bm.mod = myBiomodModelOut,
                                              proj.name = 'FutureRangeSize',
                                              new.env = myExplFuture,
                                              models.chosen = models.proj,
                                              metric.binary = 'TSS')

# Compute differences
myBiomodRangeSize <- BIOMOD_RangeSize(proj.current = myBiomodProj,
                                      proj.future = myBiomodProjectionFuture,
                                      metric.binary = "TSS")

# Represent main results
bm_PlotRangeSize(bm.range = myBiomodRangeSize)

```

## Description

This function allows to produce summary report or ODMAP table from a **biomod2** simulation folder.

## Usage

```
BIOMOD_Report(
  bm.out,
  strategy = "report",
  params.color = list(color1 = "#eb4034", color2 = "#e0918b", color3 = "#658f70"),
  params.ODMAP = list(O.mod.objective = NULL, O.boundary = NULL, O.obs.type = NULL,
    O.pred.type = NULL, D.eco.level = NULL, D.samp.design = NULL)
)
```

## Arguments

|              |                                                                                                                                                                                                                                                                                                                                                                          |
|--------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| bm.out       | a <a href="#">BIOMOD.formated.data</a> or <a href="#">BIOMOD.formated.data.PA</a> object returned by the <a href="#">BIOMOD_FormattingData</a> function ; or a <a href="#">BIOMOD.models.out</a> or <a href="#">BIOMOD.ensemble.models.out</a> object that can be obtained with the <a href="#">BIOMOD_Modeling</a> or <a href="#">BIOMOD_EnsembleModeling</a> functions |
| strategy     | a character defining the type of summary file that will be produced, must be report, ODMAP or code (see Details)                                                                                                                                                                                                                                                         |
| params.color | a list containing 3 color values to custom the reports                                                                                                                                                                                                                                                                                                                   |
| params.ODMAP | a list containing values of some ODMAP fields to be filled in from pre-existing choices (see Details)                                                                                                                                                                                                                                                                    |

## Details

This function gathers and formats all objects contained in one **biomod2** modeling folder to produce, based on Rmarkdown templates, standardized reports to help the user :

- summarize its modeling results
- share them through standardized informations through ODMAP protocol
- provide reproducible code

**Type of report** Different data types are available, and require different values :

**report** **biomod2** provides functions to summarize the information, such as print, plot or summary methods adapted to `BIOMOD.[...].out` objects, as well as `get_[...]` and `bm_Plot[...]` functions. All these are called here and applied to objects contained in the provided modeling folder.

**ODMAP** following Zurell et al. 2020, ODMAP (Overview, Data, Model, Assessment and Prediction) protocol aims to standardize documentation of modeling to help improve both transparency and reproducibility of results. [ODMAP v1.0 website](#) provides an application to fill this type of report. **biomod2** tries here to help one user to pre-fill the fields of this protocol.

**code** call slot contained within `BIOMOD.formated.data`, `BIOMOD.models.out`, `BIOMOD.projection.out` and `BIOMOD.ensemble.models.out` objects keep in memory the R command used to obtain them. All these calls are gathered here in one summary file.

### Value

A standardized .html file obtained from an Rmarkdown template, and a .csv table in the case of ODMAP report.

### Author(s)

Maya Guéguen

### References

- Zurell D, Franklin J, König C, Bouchet PJ, Serra-Diaz JM, Dormann CF, Elith J, Fandos Guzman G, Feng X, Guillera-Arroita G, Guisan A, Leitão PJ, Lahoz-Monfort JJ, Park DS, Peterson AT, Rapacciuolo G, Schmatz DR, Schröder B, Thuiller W, Yates KL, Zimmermann NE, Merow C (2020). *A standard protocol for describing species distribution models*. *Ecography* 43: 1261-1277. doi:10.1111/ecog.04960

### See Also

`ODMAP`, `match.call`

### Examples

```
library(terra)

# Load species occurrences (6 species available)
data(DataSpecies)
head(DataSpecies)

# Select the name of the studied species
myRespName <- 'GuloGulo'

# Get corresponding presence/absence data
myResp <- as.numeric(DataSpecies[, myRespName])

# Get corresponding XY coordinates
myRespXY <- DataSpecies[, c('X_WGS84', 'Y_WGS84')]

# Load environmental variables extracted from BIOCLIM (bio_3, bio_4, bio_7, bio_11 & bio_12)
data(bioclim_current)
myExpl <- terra::rast(bioclim_current)

# ----- #
file.out <- paste0(myRespName, "/", myRespName, ".AllModels.models.out")
if (file.exists(file.out)) {
```



```
# ----- #
# Compile summary reports
# BIOMOD_Report(bm.out = myBiomodModelOut, strategy = 'report')
# BIOMOD_Report(bm.out = myBiomodProj, strategy = 'report')
# BIOMOD_Report(bm.out = myBiomodEM, strategy = 'report')

# BIOMOD_Report(bm.out = myBiomodModelOut, strategy = 'ODMAP')
# BIOMOD_Report(bm.out = myBiomodModelOut, strategy = 'code')
```

---

|                        |                                                                                    |
|------------------------|------------------------------------------------------------------------------------|
| biomod2_ensemble_model | <i>Ensemble model output object class (when running BIOMOD_EnsembleModeling())</i> |
|------------------------|------------------------------------------------------------------------------------|

---

## Description

Class created by [BIOMOD\\_EnsembleModeling](#)

## Usage

```
## S4 method for signature 'biomod2_ensemble_model'
show(object)
```

## Arguments

object            a [biomod2\\_ensemble\\_model](#) object

## Details

biomod2\_model is the basic object for **biomod2** ensemble species distribution models. All listed classes below are derived from biomod2\_model, and have a model\_class slot specific value :

- biomod2\_ensemble\_model : model\_class is EM
- EMmean\_biomod2\_model : model\_class is EMmean
- EMmedian\_biomod2\_model : model\_class is EMmedian
- EMcv\_biomod2\_model : model\_class is EMcv
- EMci\_biomod2\_model : model\_class is EMci
- EMca\_biomod2\_model : model\_class is EMca
- EMwmean\_biomod2\_model : model\_class is EMwmean
- EMmode\_biomod2\_model : model\_class is EMmode
- EMfreq\_biomod2\_model : model\_class is EMfreq

**Slots**

`modeling.id` a character corresponding to the name (ID) of the simulation set  
`model_name` a character corresponding to the model name  
`model_class` a character corresponding to the model class  
`model_options` a list containing the model options  
`model` the corresponding model object  
`scaling_model` the corresponding scaled model object  
`dir_name` a character corresponding to the modeling folder  
`resp_name` a character corresponding to the species name  
`expl_var_names` a vector containing names of explanatory variables  
`expl_var_type` a vector containing classes of explanatory variables  
`expl_var_range` a list containing ranges of explanatory variables  
`model_evaluation` a `data.frame` containing the model evaluations  
`model_variables_importance` a `data.frame` containing the model variables importance

**Author(s)**

Damien Georges

**See Also**

[biomod2\\_model](#), [BIOMOD\\_EnsembleModeling](#)

Other Toolbox objects: [BIOMOD.ensemble.models.out](#), [BIOMOD.formated.data\(\)](#), [BIOMOD.formated.data.PA\(\)](#), [BIOMOD.models.options](#), [BIOMOD.models.out](#), [BIOMOD.options.dataset\(\)](#), [BIOMOD.options.default\(\)](#), [BIOMOD.projection.out](#), [BIOMOD.rangesize.out](#), [BIOMOD.stored.data](#), [biomod2\\_model](#)

**Examples**

```

showClass("biomod2_ensemble_model")
showClass("EMmean_biomod2_model")
showClass("EMmedian_biomod2_model")
showClass("EMcv_biomod2_model")
showClass("EMci_biomod2_model")
showClass("EMca_biomod2_model")
showClass("EMwmean_biomod2_model")
showClass("EMmode_biomod2_model")
showClass("EMfreq_biomod2_model")

```

---

|               |                                                                          |
|---------------|--------------------------------------------------------------------------|
| biomod2_model | <i>Single model output object class (when running BIOMOD_Modeling())</i> |
|---------------|--------------------------------------------------------------------------|

---

## Description

Class created by `BIOMOD_Modeling` and `bm_RunModel`

## Usage

```
## S4 method for signature 'biomod2_model'
show(object)
```

## Arguments

object            a `biomod2_model` object

## Details

`biomod2_model` is the basic object for **biomod2** single species distribution models.  
All listed classes below are derived from `biomod2_model`, and have a `model_class` slot specific value :

- `ANN_biomod2_model` : `model_class` is ANN
- `CTA_biomod2_model` : `model_class` is CTA
- `DNN_biomod2_model` : `model_class` is DNN
- `FDA_biomod2_model` : `model_class` is FDA
- `GBM_biomod2_model` : `model_class` is GBM
- `GLM_biomod2_model` : `model_class` is GLM
- `MARS_biomod2_model` : `model_class` is MARS
- `MAXENT_biomod2_model` : `model_class` is MAXENT
- `MAXNET_biomod2_model` : `model_class` is MAXNET
- `RF_biomod2_model` : `model_class` is RF
- `RFd_biomod2_model` : `model_class` is RFd
- `SRE_biomod2_model` : `model_class` is SRE

## Slots

`model_name` a character corresponding to the model name  
`model_class` a character corresponding to the model class  
`model_type` a character corresponding to the type of data  
`model_options` a list containing the model options  
`model` the corresponding model object  
`scaling_model` the corresponding scaled model object

`levels_factor` the levels of the original data for ordinal and multiclass  
`dir_name` a character corresponding to the modeling folder  
`resp_name` a character corresponding to the species name  
`expl_var_names` a vector containing names of explanatory variables  
`expl_var_type` a vector containing classes of explanatory variables  
`expl_var_range` a list containing ranges of explanatory variables  
`model_evaluation` a data.frame containing the model evaluations  
`model_variables_importance` a data.frame containing the model variables importance

### Author(s)

Damien Georges

### See Also

[BIOMOD\\_Modeling](#), [bm\\_RunModel](#)

Other Toolbox objects: [BIOMOD.ensemble.models.out](#), [BIOMOD.formated.data\(\)](#), [BIOMOD.formated.data.PA\(\)](#), [BIOMOD.models.options](#), [BIOMOD.models.out](#), [BIOMOD.options.dataset\(\)](#), [BIOMOD.options.default\(\)](#), [BIOMOD.projection.out](#), [BIOMOD.rangesize.out](#), [BIOMOD.stored.data](#), [biomod2\\_ensemble\\_model](#)

### Examples

```

showClass("biomod2_model")
showClass("ANN_biomod2_model")
showClass("CTA_biomod2_model")
showClass("DNN_biomod2_model")
showClass("FDA_biomod2_model")
showClass("GAM_biomod2_model")
showClass("GBM_biomod2_model")
showClass("GLM_biomod2_model")
showClass("MARS_biomod2_model")
showClass("MAXENT_biomod2_model")
showClass("MAXNET_biomod2_model")
showClass("RF_biomod2_model")
showClass("RFd_biomod2_model")
showClass("SRE_biomod2_model")

```

---

bm\_BinaryTransformation

*Convert probability values into binary values using a predefined threshold*

---

### Description

This internal **biomod2** function allows to convert probability (not necessary between 0 and 1) values into binary presence-absence (0 or 1) values according to a predefined threshold (see Details).

**Usage**

```
bm_BinaryTransformation(data, threshold, do.filtering = FALSE)

## S4 method for signature 'data.frame'
bm_BinaryTransformation(data, threshold, do.filtering = FALSE)

## S4 method for signature 'matrix'
bm_BinaryTransformation(data, threshold, do.filtering = FALSE)

## S4 method for signature 'numeric'
bm_BinaryTransformation(data, threshold, do.filtering = FALSE)

## S4 method for signature 'SpatRaster'
bm_BinaryTransformation(data, threshold, do.filtering = FALSE)
```

**Arguments**

|              |                                                                                                                                      |
|--------------|--------------------------------------------------------------------------------------------------------------------------------------|
| data         | a vector, a matrix, data.frame, or a <a href="#">SpatRaster</a> containing the data to be converted                                  |
| threshold    | a numeric or a vector of numeric corresponding to the threshold used to convert the given data (see Details)                         |
| do.filtering | ( <i>optional, default FALSE</i> )<br>A logical value defining whether filtered data should be returned, or binary one (see Details) |

**Details**

If data is a vector, threshold should be a single numeric value.

If data is a matrix, data.frame or [SpatRaster](#), threshold should be a vector containing as many values as the number of columns or layers contained in data. If only one numeric value is given, the same threshold will be applied to all columns or layers.

If do.filtering = FALSE, binary (0 or 1) values are returned.

If do.filtering = TRUE, values will be *filtered* according to threshold, meaning that :

- data < threshold will return 0
- data >= threshold will return the actual values of data (not transformed in 1)

**Value**

An object of the same class than data and containing either binary (0 or 1) values, or filtered values.

**Author(s)**

Wilfried Thuiller, Damien Georges

**See Also**

[BIOMOD\\_Projection](#), [BIOMOD\\_EnsembleForecasting](#)

Other Secondary functions: [bm\\_CrossValidation\(\)](#), [bm\\_FindOptimStat\(\)](#), [bm\\_MakeFormula\(\)](#), [bm\\_ModelAnalysis\(\)](#), [bm\\_ModelingOptions\(\)](#), [bm\\_PlotEvalBoxplot\(\)](#), [bm\\_PlotEvalMean\(\)](#), [bm\\_PlotRangeSize\(\)](#), [bm\\_PlotResponseCurves\(\)](#), [bm\\_PlotVarImpBoxplot\(\)](#), [bm\\_PseudoAbsences\(\)](#), [bm\\_RangeSize\(\)](#), [bm\\_RunModelsLoop\(\)](#), [bm\\_SRE\(\)](#), [bm\\_SampleBinaryVector\(\)](#), [bm\\_SampleFactorLevels\(\)](#), [bm\\_Tuning\(\)](#), [bm\\_VariablesImportance\(\)](#)

**Examples**

```
## Generate a 0-1000 vector (normal distribution)
vec.d <- rnorm(100, 500, 100)

## From continuous to binary / filtered vector
vec.d_bin <- bm_BinaryTransformation(data = vec.d, threshold = 500)
vec.d_filt <- bm_BinaryTransformation(data = vec.d, threshold = 500, do.filtering = TRUE)
cbind(vec.d, vec.d_bin, vec.d_filt)
```

---

|                    |                                     |
|--------------------|-------------------------------------|
| bm_CrossValidation | <i>Build cross-validation table</i> |
|--------------------|-------------------------------------|

---

**Description**

This internal **biomod2** function allows to build a cross-validation table according to 6 different methods : random, kfold, block, strat, env or user.defined (see Details).

**Usage**

```
bm_CrossValidation(
  bm.format,
  strategy,
  nb.rep = NULL,
  perc = NULL,
  k = NULL,
  balance = NULL,
  strat = NULL,
  env.var = NULL,
  user.table = NULL,
  do.full.models = FALSE,
  seed.val = NULL
)

bm_CrossValidation_user.defined(bm.format, ...)

## S4 method for signature 'BIOMOD.formated.data'
```

```
bm_CrossValidation_user.defined(bm.format, user.table)

## S4 method for signature 'BIOMOD.formated.data.PA'
bm_CrossValidation_user.defined(bm.format, user.table)

bm_CrossValidation_random(bm.format, ...)

## S4 method for signature 'BIOMOD.formated.data'
bm_CrossValidation_random(bm.format, nb.rep, perc)

## S4 method for signature 'BIOMOD.formated.data.PA'
bm_CrossValidation_random(bm.format, nb.rep, perc)

bm_CrossValidation_kfold(bm.format, ...)

## S4 method for signature 'BIOMOD.formated.data'
bm_CrossValidation_kfold(bm.format, nb.rep, k)

## S4 method for signature 'BIOMOD.formated.data.PA'
bm_CrossValidation_kfold(bm.format, nb.rep, k)

bm_CrossValidation_block(bm.format, ...)

## S4 method for signature 'BIOMOD.formated.data'
bm_CrossValidation_block(bm.format)

## S4 method for signature 'BIOMOD.formated.data.PA'
bm_CrossValidation_block(bm.format)

bm_CrossValidation_strat(bm.format, ...)

## S4 method for signature 'BIOMOD.formated.data'
bm_CrossValidation_strat(bm.format, balance, strat, k)

## S4 method for signature 'BIOMOD.formated.data.PA'
bm_CrossValidation_strat(bm.format, balance, strat, k)

bm_CrossValidation_env(bm.format, ...)

## S4 method for signature 'BIOMOD.formated.data'
bm_CrossValidation_env(bm.format, balance, k, env.var)

## S4 method for signature 'BIOMOD.formated.data.PA'
bm_CrossValidation_env(bm.format, balance, k, env.var)
```

## Arguments

|           |                                                                                                                                                        |
|-----------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| bm.format | a <a href="#">BIOMOD.formated.data</a> or <a href="#">BIOMOD.formated.data.PA</a> object returned by the <a href="#">BIOMOD_FormatingData</a> function |
|-----------|--------------------------------------------------------------------------------------------------------------------------------------------------------|

|                |                                                                                                                                                                                                                                                                  |
|----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| strategy       | a character corresponding to the cross-validation selection strategy, must be among random, kfold, block, strat, env or user.defined                                                                                                                             |
| nb.rep         | (optional, default NULL)<br>If strategy = 'random' or strategy = 'kfold', an integer corresponding to the number of sets (repetitions) of cross-validation points that will be drawn                                                                             |
| perc           | (optional, default NULL)<br>If strategy = 'random', a numeric between 0 and 1 defining the percentage of data that will be kept for calibration                                                                                                                  |
| k              | (optional, default NULL)<br>If strategy = 'kfold' or strategy = 'strat' or strategy = 'env', an integer corresponding to the number of partitions                                                                                                                |
| balance        | (optional, default NULL)<br>If strategy = 'strat' or strategy = 'env', a character corresponding to how data will be balanced between partitions, must be either presences or absence                                                                            |
| strat          | (optional, default NULL)<br>If strategy = 'env', a character corresponding to how data will be partitioned along gradient, must be among x, y, both                                                                                                              |
| env.var        | (optional)<br>If strategy = 'env', a character corresponding to the environmental variables used to build the partition. k partitions will be built for each environmental variables. <i>By default the function uses all environmental variables available.</i> |
| user.table     | (optional, default NULL)<br>If strategy = 'user.defined', a matrix or data.frame defining for each repetition (in columns) which observation lines should be used for models calibration (TRUE) and validation (FALSE)                                           |
| do.full.models | (optional, default FALSE)<br>A logical value defining whether models should be also calibrated and validated over the whole dataset (and pseudo-absence datasets) or not                                                                                         |
| seed.val       | (optional, default NULL)<br>An integer value corresponding to the new seed value to be set                                                                                                                                                                       |
| ...            | (optional, one or several of the listed above arguments depending on the selected method)                                                                                                                                                                        |

## Details

Several parameters are available within the function and some of them can be used with different cross-validation strategies :

| ..... | random | kfold | block | strat | env |

---

|         |        |       |       |       |     |
|---------|--------|-------|-------|-------|-----|
| nb.rep. | x..... | x.... | ..... | ..... | ... |
| perc... | x..... | ..... | ..... | ..... | ... |
| k.....  | .....  | x.... | ..... | x.... | x.. |
| balance | .....  | ..... | ..... | x.... | x.. |
| strat.. | .....  | ..... | ..... | x.... | ... |

### Concerning column names of matrix output :

The number of columns depends on the strategy selected. The column names are given *a posteriori* of the selection, ranging from 1 to the number of columns. If `do.full.models = TRUE`, columns merging runs (and/or pseudo-absence datasets) are added at the end.

### Concerning cross-validation strategies :

**random** Most simple method to calibrate and validate a model is to split the original dataset in two datasets : one to calibrate the model and the other one to validate it. The splitting can be repeated `nb.rep` times.

**k-fold** The k-fold method splits the original dataset in k datasets of equal sizes : each part is used successively as the validation dataset while the other k-1 parts are used for the calibration, leading to k calibration/validation ensembles. This multiple splitting can be repeated `nb.rep` times.

**block** It may be used to test for model overfitting and to assess transferability in geographic space. block stratification was described in *Muscarella et al. 2014* (see References). Four bins of equal size are partitioned (bottom-left, bottom-right, top-left and top-right).

**stratified** It may be used to test for model overfitting and to assess transferability in geographic space. x and y stratification was described in *Wenger and Olden 2012* (see References). y stratification uses k partitions along the y-gradient, x stratification does the same for the x-gradient. both returns 2k partitions: k partitions stratified along the x-gradient and k partitions stratified along the y-gradient.

**environmental** It may be used to test for model overfitting and to assess transferability in environmental space. It returns k partitions for each variable given in `env.var`.

**user-defined** Allow the user to give its own crossvalidation table. For a presence-absence dataset, column names must be formatted as: `_allData_RUNx` with x an integer. For a presence-only dataset for which several pseudo-absence dataset were generated, column names must be formatted as: `_PAx_RUNy` with x an integer and PAx an existing pseudo-absence dataset and y an integer

### Concerning balance parameter :

If `balance = 'presences'`, presences are divided (balanced) equally over the partitions (e.g. *Fig. 1b in Muscarella et al. 2014*). Absences or pseudo-absences will however be unbalanced over the partitions especially if the presences are clumped on an edge of the study area.

If `balance = 'absences'`, absences (resp. pseudo-absences or background) are divided (balanced) as equally as possible between the partitions (geographical balanced bins given that absences are spread over the study area equally, approach similar to *Fig. 1 in Wenger et Olden 2012*). Presences will however be unbalanced over the partitions especially if the presences are clumped on an edge of the study area.

**Value**

A matrix or data.frame defining for each repetition (in columns) which observation lines should be used for models calibration (TRUE) and validation (FALSE).

**Author(s)**

Maya Guéguen

**References**

- Muscarella R, Galante PJ, Soley-Guardia M, Boria RA, Kass JM, Uriarte M, Anderson RP (2014). *ENMeval: An R package for conducting spatially independent evaluations and estimating optimal model complexity for Maxent ecological niche models*. Methods in Ecology and Evolution, 5, 1198-1205. doi:10.1111/2041210X.12261
- Wenger SJ and Olden JD (2012). *Assessing transferability of ecological models: an under-appreciated aspect of statistical validation*. Methods in Ecology and Evolution, 3, 260-267. doi:10.1111/j.2041210X.2011.00170.x

**See Also**

`get.block`, `kfold`, `BIOMOD_FormatingData`, `BIOMOD_Modeling`

Other Secondary functions: `bm_BinaryTransformation()`, `bm_FindOptimStat()`, `bm_MakeFormula()`, `bm_ModelAnalysis()`, `bm_ModelingOptions()`, `bm_PlotEvalBoxplot()`, `bm_PlotEvalMean()`, `bm_PlotRangeSize()`, `bm_PlotResponseCurves()`, `bm_PlotVarImpBoxplot()`, `bm_PseudoAbsences()`, `bm_RangeSize()`, `bm_RunModelsLoop()`, `bm_SRE()`, `bm_SampleBinaryVector()`, `bm_SampleFactorLevels()`, `bm_Tuning()`, `bm_VariablesImportance()`

**Examples**

```
library(terra)

# Load species occurrences (6 species available)
data(DataSpecies)
head(DataSpecies)

# Select the name of the studied species
myRespName <- 'GuloGulo'

# Get corresponding presence/absence data
myResp <- as.numeric(DataSpecies[, myRespName])

# Get corresponding XY coordinates
myRespXY <- DataSpecies[, c('X_WGS84', 'Y_WGS84')]

# Load environmental variables extracted from BIOCLIM (bio_3, bio_4, bio_7, bio_11 & bio_12)
data(bioclim_current)
myExpl <- terra::rast(bioclim_current)
```

```

# ----- #
# Format Data with true absences
myBiomodData <- BIOMOD_FormatingData(resp.name = myRespName,
                                     resp.var = myResp,
                                     resp.xy = myRespXY,
                                     expl.var = myExpl)

# ----- #
# Create the different validation datasets

# random selection
cv.r <- bm_CrossValidation(bm.format = myBiomodData,
                           strategy = "random",
                           nb.rep = 3,
                           perc = 0.8)

# k-fold selection
cv.k <- bm_CrossValidation(bm.format = myBiomodData,
                           strategy = "kfold",
                           nb.rep = 2,
                           k = 3)

# block selection
cv.b <- bm_CrossValidation(bm.format = myBiomodData,
                           strategy = "block")

# stratified selection (geographic)
cv.s <- bm_CrossValidation(bm.format = myBiomodData,
                           strategy = "strat",
                           k = 2,
                           balance = "presences",
                           strat = "x")

# stratified selection (environmental)
cv.e <- bm_CrossValidation(bm.format = myBiomodData,
                           strategy = "env",
                           k = 2,
                           balance = "presences")

head(cv.r)
apply(cv.r, 2, table)
head(cv.k)
apply(cv.k, 2, table)
head(cv.b)
apply(cv.b, 2, table)
head(cv.s)
apply(cv.s, 2, table)
head(cv.e)
apply(cv.e, 2, table)

```

---

|                  |                                                                        |
|------------------|------------------------------------------------------------------------|
| bm_FindOptimStat | <i>Calculate the best score according to a given evaluation method</i> |
|------------------|------------------------------------------------------------------------|

---

## Description

This internal **biomod2** function allows the user to find the threshold to convert continuous values into binary ones leading to the best score for a given evaluation metric.

## Usage

```
bm_FindOptimStat(
  metric.eval = "TSS",
  obs,
  fit,
  nb.thresh = 100,
  threshold = NULL,
  boyce.bg.env = NULL,
  mpa.perc = 0.9,
  k = NULL
)

get_optim_value(metric.eval)

bm_CalculateStatBin(misc, metric.eval = "TSS")

bm_CalculateStatAbun(metric.eval, obs, fit, k)
```

## Arguments

|              |                                                                                                                                                                                                                                                                                                                                                                        |
|--------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| metric.eval  | a character corresponding to the evaluation metric to be used, must be either AUCroc, AUCprg, TSS, KAPPA, ACCURACY, BIAS, POD, FAR, POFD, SR, CSI, ETS, OR, ORSS, BOYCE, MPA ( <i>binary data</i> ), RMSE, MAE, MSE, Rsquared, Rsquared_aj, Max_error ( <i>abundance / count / relative data</i> ), Accuracy, Recall, Precision, F1 ( <i>multiclass/ordinal data</i> ) |
| obs          | a vector of observed values (binary, 0 or 1)                                                                                                                                                                                                                                                                                                                           |
| fit          | a vector of fitted values (continuous)                                                                                                                                                                                                                                                                                                                                 |
| nb.thresh    | an integer corresponding to the number of thresholds to be tested over the range of fitted values                                                                                                                                                                                                                                                                      |
| threshold    | ( <i>optional, default NULL</i> )<br>A numeric corresponding to the threshold used to convert the given data                                                                                                                                                                                                                                                           |
| boyce.bg.env | ( <i>optional, default NULL</i> )<br>A matrix, data.frame, <a href="#">SpatVector</a> or <a href="#">SpatRaster</a> object containing values of environmental variables (in columns or layers) extracted from the background ( <i>if presences are to be compared to background instead of absences or pseudo-absences selected for modeling</i> )                     |

*Note that old format from **raster** and **sp** are still supported such as RasterStack and SpatialPointsDataFrame objects.*

|          |                                                                                                                                                                            |
|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| mpa.perc | a numeric between 0 and 1 corresponding to the percentage of correctly classified presences for Minimal Predicted Area (see <code>ecospat.mpa()</code> in <b>ecospat</b> ) |
| k        | an integer corresponding to the number of environmental variables used in the model                                                                                        |
| misc     | a matrix corresponding to a contingency table                                                                                                                              |

## Details

Please refer to ***JWGFVR website ("Forecast verification - methods, issues and FAQ")*** to get detailed description (simple/complex metrics).

Optimal value of each method can be obtained with the `get_optim_value` function.

**simple** • POD : Probability of detection (hit rate)

- FAR : False alarm ratio
- POFD : Probability of false detection (fall-out)
- SR : Success ratio
- ACCURACY : Accuracy (fraction correct)
- BIAS : Bias score (frequency bias)

**complex** • AUCroc : Area Under Curve of Relative operating characteristic

- AUCprg : Area Under Curve of Precision-Recall-Gain curve
- TSS : True skill statistic (Hanssen and Kuipers discriminant, Peirce's skill score)
- KAPPA : Cohen's Kappa (Heidke skill score)
- OR : Odds Ratio
- ORSS : Odds ratio skill score (Yule's Q)
- CSI : Critical success index (threat score)
- ETS : Equitable threat score (Gilbert skill score)

**presence-only** • BOYCE : Boyce index

- MPA : Minimal predicted area (cutoff optimizing MPA to predict 90% of presences)

**abundance / count / relative data** • RMSE : Root Mean Square Error

- MSE : Mean Square Error
- MAE : Mean Absolute Error
- Rsquared : R squared
- Rsquared\_adj : R squared adjusted
- Max\_error : Maximum error

**multiclass/ordinal data** • Accuracy : Accuracy

- Recall : Macro average Recall
- Precision : Macro average Precision
- F1 : Macro F1 score

Note that if a value is given to threshold, no optimization will be done, and only the score for this threshold will be returned.

The Boyce index returns NA values for SRE models because it can not be calculated with binary predictions.

This is also the reason why some NA values might appear for GLM models if they did not converge.

**Value**

A 1 row x 5 columns data.frame containing :

- `metric.eval` : the chosen evaluation metric
- `cutoff` : the associated cut-off used to transform the continuous values into binary
- `sensitivity` : the sensibility obtained on fitted values with this threshold
- `specificity` : the specificity obtained on fitted values with this threshold
- `best.stat` : the best score obtained for the chosen evaluation metric

**Note**

In order to break dependency loop between packages **biomod2** and **ecospat**, code of `ecospat.boyce()` and `ecospat.mpa()` in **ecospat** functions have been copied within this file from version 3.2.2 (august 2022).

**Author(s)**

Damien Georges

**References**

- Engler R, Guisan A, Rechsteiner L (2004). *An improved approach for predicting the distribution of rare and endangered species from occurrence and pseudo-absence data*. Journal of Applied Ecology, 41(2), 263-274. doi:10.1111/j.00218901.2004.00881.x
- Hirzel AH, Le Lay G, Helfer V, Randin C, Guisan A (2006). *Evaluating the ability of habitat suitability models to predict species presences*. Ecological Modelling, 199(2), 142-152. doi:10.1016/j.ecolmodel.2006.05.017

**See Also**

`ecospat.boyce()` and `ecospat.mpa()` in **ecospat**, [BIOMOD\\_Modeling](#), [bm\\_RunModelsLoop](#), [BIOMOD\\_EnsembleModeling](#)

Other Secondary functions: [bm\\_BinaryTransformation\(\)](#), [bm\\_CrossValidation\(\)](#), [bm\\_MakeFormula\(\)](#), [bm\\_ModelAnalysis\(\)](#), [bm\\_ModelingOptions\(\)](#), [bm\\_PlotEvalBoxplot\(\)](#), [bm\\_PlotEvalMean\(\)](#), [bm\\_PlotRangeSize\(\)](#), [bm\\_PlotResponseCurves\(\)](#), [bm\\_PlotVarImpBoxplot\(\)](#), [bm\\_PseudoAbsences\(\)](#), [bm\\_RangeSize\(\)](#), [bm\\_RunModelsLoop\(\)](#), [bm\\_SRE\(\)](#), [bm\\_SampleBinaryVector\(\)](#), [bm\\_SampleFactorLevels\(\)](#), [bm\\_Tuning\(\)](#), [bm\\_VariablesImportance\(\)](#)

**Examples**

```
## Generate a binary vector
vec.a <- sample(c(0, 1), 100, replace = TRUE)

## Generate a 0-1000 vector (random drawing)
vec.b <- runif(100, min = 0, max = 1000)

## Generate a 0-1000 vector (biased drawing)
BiasedDrawing <- function(x, m1 = 300, sd1 = 200, m2 = 700, sd2 = 200) {
  return(ifelse(x < 0.5, rnorm(1, m1, sd1), rnorm(1, m2, sd2)))
}
```

```

}
vec.c <- sapply(vec.a, BiasedDrawing)
vec.c[which(vec.c < 0)] <- 0
vec.c[which(vec.c > 1000)] <- 1000

## Find optimal threshold for a specific evaluation metric
bm_FindOptimStat(metric.eval = 'TSS', fit = vec.b, obs = vec.a)
bm_FindOptimStat(metric.eval = 'TSS', fit = vec.c, obs = vec.a, nb.thresh = 100)
bm_FindOptimStat(metric.eval = 'TSS', fit = vec.c, obs = vec.a, threshold = 280)

```

---

|                |                                   |
|----------------|-----------------------------------|
| bm_MakeFormula | <i>Standardized formula maker</i> |
|----------------|-----------------------------------|

---

## Description

This internal **biomod2** function allows the user to create easily a standardized formula that can be used later by statistical models.

## Usage

```

bm_MakeFormula(
  resp.name,
  expl.var,
  type = "simple",
  interaction.level = 0,
  k = NULL
)

```

## Arguments

|                   |                                                                                                                                                                   |
|-------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| resp.name         | a character corresponding to the response variable name                                                                                                           |
| expl.var          | a matrix or data.frame containing the explanatory variables that will be used at the modeling step                                                                |
| type              | a character corresponding to the wanted type of formula, must be simple, quadratic, polynomial or s_smoother                                                      |
| interaction.level | an integer corresponding to the interaction level depth between explanatory variables                                                                             |
| k                 | (optional, default NULL)<br>If type = 's_smoother', an integer corresponding to the smoothing parameter value of <a href="#">s</a> or <a href="#">s</a> arguments |

## Details

It is advised to give only a subset of `expl.var` table to avoid useless memory consuming.  
If some explanatory variables are factorial, `expl.var` must be a `data.frame` whose corresponding columns are defined as factor.

**Value**

A `formula` class object that can be directly given to most of R statistical models.

**Author(s)**

Damien Georges

**See Also**

`formula`, `s`, `s`, `bm_ModelingOptions`, `bm_Tuning`, `bm_RunModelsLoop`

Other Secondary functions: `bm_BinaryTransformation()`, `bm_CrossValidation()`, `bm_FindOptimStat()`, `bm_ModelAnalysis()`, `bm_ModelingOptions()`, `bm_PlotEvalBoxplot()`, `bm_PlotEvalMean()`, `bm_PlotRangeSize()`, `bm_PlotResponseCurves()`, `bm_PlotVarImpBoxplot()`, `bm_PseudoAbsences()`, `bm_RangeSize()`, `bm_RunModelsLoop()`, `bm_SRE()`, `bm_SampleBinaryVector()`, `bm_SampleFactorLevels()`, `bm_Tuning()`, `bm_VariablesImportance()`

**Examples**

```
## Create simple simulated data
myResp.s <- sample(c(0, 1), 20, replace = TRUE)
myExpl.s <- data.frame(var1 = sample(c(0, 1), 100, replace = TRUE),
                      var2 = rnorm(100),
                      var3 = 1:100)

## Generate automatic formula
bm_MakeFormula(resp.name = 'myResp.s',
               expl.var = head(myExpl.s),
               type = 'quadratic',
               interaction.level = 0)
```

---

**bm\_ModelAnalysis**


---

*Analyze the residuals of the single models*


---

**Description**

This function return several graphs to help analyse the single models.

**Usage**

```
bm_ModelAnalysis(
  bm.mod,
  models.chosen = "all",
  color.by = "full.name",
  do.plot = TRUE
)
```

## Arguments

|               |                                                                                                                                                                                            |
|---------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| bm.mod        | a <a href="#">BIOMOD.models.out</a> object returned by the <a href="#">BIOMOD_Modeling</a> function                                                                                        |
| models.chosen | a vector containing model names to be kept, must be either all or a sub-selection of model names that can be obtained with the <a href="#">get_built_models</a> function applied to bm.mod |
| color.by      | a character corresponding to the way plots will be colored, must be among full.name, PA, run or algo                                                                                       |
| do.plot       | (optional, default TRUE)<br>A logical value defining whether the plot is to be rendered or not                                                                                             |

## Details

5 plots can be obtained with this function :

**residuals ~ observations number** to detect outliers. The x-axis only helps to find the outlier number.

**residuals Q-Q plot** to check if residuals follow a normal distribution. Points should follow the black line.

**residuals histogram** to check if residuals follow a normal distribution. Histogram should represent a gaussian distribution.

**residuals ~ fitted values** to detect an heteroscedasticity of the residuals. It corresponds to the Tukey-Anscombe plot.

**R scores** to detect overfitting. Representing Rsquared and Rsquared\_adj values, there should not be a big gap between calibration and validation values.

*Please note that all plots are made for all models, independently to the different models assumptions. It is up to the user to interpret the graphics.*

## Value

A list containing :

1. a data.frame with variables, predicted values and model residuals
2. a data.frame with the R score values
3. 5 ggplot objects (from A to E) representing the different analyses.

## Author(s)

Hélène Blancheteau

## See Also

Other Secondary functions: [bm\\_BinaryTransformation\(\)](#), [bm\\_CrossValidation\(\)](#), [bm\\_FindOptimStat\(\)](#), [bm\\_MakeFormula\(\)](#), [bm\\_ModelingOptions\(\)](#), [bm\\_PlotEvalBoxplot\(\)](#), [bm\\_PlotEvalMean\(\)](#), [bm\\_PlotRangeSize\(\)](#), [bm\\_PlotResponseCurves\(\)](#), [bm\\_PlotVarImpBoxplot\(\)](#), [bm\\_PseudoAbsences\(\)](#), [bm\\_RangeSize\(\)](#), [bm\\_RunModelsLoop\(\)](#), [bm\\_SRE\(\)](#), [bm\\_SampleBinaryVector\(\)](#), [bm\\_SampleFactorLevels\(\)](#), [bm\\_Tuning\(\)](#), [bm\\_VariablesImportance\(\)](#)

Other Plot functions: [bm\\_PlotEvalBoxplot\(\)](#), [bm\\_PlotEvalMean\(\)](#), [bm\\_PlotRangeSize\(\)](#), [bm\\_PlotResponseCurves\(\)](#), [bm\\_PlotVarImpBoxplot\(\)](#)

**Examples**

```

library(terra)

# Load species occurrences (6 species available)
data(DataSpecies)
head(DataSpecies)

# Select the name of the studied species
myRespName <- 'GuloGulo'

# Get corresponding presence/absence data
myResp <- as.numeric(DataSpecies[, myRespName])

# Get corresponding XY coordinates
myRespXY <- DataSpecies[, c('X_WGS84', 'Y_WGS84')]

# Load environmental variables extracted from BIOCLIM (bio_3, bio_4, bio_7, bio_11 & bio_12)
data(bioclim_current)
myExpl <- terra::rast(bioclim_current)

# -----#
file.out <- paste0(myRespName, "/", myRespName, ".AllModels.models.out")
if (file.exists(file.out)) {
  myBiomodModelOut <- get(load(file.out))
} else {

  # Format Data with true absences
  myBiomodData <- BIOMOD_FormatingData(resp.name = myRespName,
                                     resp.var = myResp,
                                     resp.xy = myRespXY,
                                     expl.var = myExpl)

  # Model single models
  myBiomodModelOut <- BIOMOD_Modeling(bm.format = myBiomodData,
                                     modeling.id = 'AllModels',
                                     models = c('RF', 'GLM'),
                                     CV.strategy = 'random',
                                     CV.nb.rep = 2,
                                     CV.perc = 0.8,
                                     OPT.strategy = 'bigboss',
                                     metric.eval = c('TSS', 'AUCroc'),
                                     var.import = 3,
                                     seed.val = 42)
}

# -----#
# Explore single models
myBiomodAnalysis <- bm_ModelAnalysis(bm.mod = myBiomodModelOut, color.by = "run")

```

```
plot(myBiomodAnalysis$plot.outliers)
```

---

|                    |                                                               |
|--------------------|---------------------------------------------------------------|
| bm_ModelingOptions | <i>Configure the modeling options for each selected model</i> |
|--------------------|---------------------------------------------------------------|

---

## Description

Parameterize and/or tune **biomod2**'s single models options.

## Usage

```
bm_ModelingOptions(
  data.type = "binary",
  models,
  strategy,
  user.val = NULL,
  user.base = NULL,
  bm.format = NULL,
  calib.lines = NULL
)
```

## Arguments

|             |                                                                                                                                                                                                        |
|-------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| data.type   | a character corresponding to the data type to be used, must be either binary, count, relative, abundance, multiclass, ordinal                                                                          |
| models      | a vector containing model names to be computed, must be among ANN, CTA, DNN, FDA, GAM, GBM, GLM, MARS, MAXENT, MAXNET, RF, RFd, SRE, XGBOOST                                                           |
| strategy    | a character corresponding to the method to select models' parameters values, must be either default, bigboss, user.defined, tuned (see Details)                                                        |
| user.val    | (optional, default NULL)<br>A list containing parameters values for some (all) models                                                                                                                  |
| user.base   | (optional, default NULL)<br>If strategy = 'user.defined', a character corresponding to the basic set of options to be modified by user defined values, must be either default or bigboss (see Details) |
| bm.format   | (optional, default NULL)<br>A <a href="#">BIOMOD.formated.data</a> or <a href="#">BIOMOD.formated.data.PA</a> object returned by the <a href="#">BIOMOD_FormatingData</a> function                     |
| calib.lines | (optional, default NULL)<br>A data.frame object returned by <a href="#">get_calib_lines</a> or <a href="#">bm_CrossValidation</a> functions                                                            |

## Details

This function creates a `BIOMOD.models.options` object containing parameter values for each single model that can be run within **biomod2** through `BIOMOD_Modeling` function.

11 different algorithms are currently available, with different versions for some (GAM, MAXENT, RF). These models are associated with *binary* or *nonbinary* datatypes, but all combinations are not available. They are all listed within the `ModelsTable` dataset.

Different strategies are available to set those parameters, through the `strategy` argument :

**default** all parameters names and values are directly retrieve from functions to be called through `formalArgs` and `formals` functions

**bigboss** default parameter values are updated with values predefined by **biomod2** team (see `OptionsBigboss`)

**user.defined** default parameter values are updated with values provided by the user

**tuned** default parameter values are updated by calling `bm_Tuning` function

To define the same options for all datasets of a model, options can be provided through the `user.val` parameter as a list whose name is `for_all_datasets`.

## Value

A `BIOMOD.models.options` of object that can be used to build species distribution model(s) with the `BIOMOD_Modeling` function.

## Note

MAXENT being the only external model (not called through a R package), default parameters, and their values, are the following :

| FLAG                             | default              | Description                                                                         |
|----------------------------------|----------------------|-------------------------------------------------------------------------------------|
| <code>path_to_maxent.jar</code>  | <code>getwd()</code> | a character corresponding to path to <code>maxent.jar</code> file                   |
| <code>memory_allocated</code>    | 512                  | an integer corresponding to the amount of memory (in Mo) reserved for java to       |
| <code>initial_heap_size</code>   | NULL                 | a character corresponding to initial heap space (shared memory space) allocated     |
| <code>max_heap_size</code>       | NULL                 | a character corresponding to maximum heap space (shared memory space) alloc         |
| <code>background_data_dir</code> | 'default'            | a character corresponding to path to folder where explanatory variables are store   |
| <code>visible</code>             | FALSE                | a logical value defining whether MAXENT user interface is to be used or not         |
| <code>linear</code>              | TRUE                 | a logical value defining whether linear features are to be used or not              |
| <code>quadratic</code>           | TRUE                 | a logical value defining whether quadratic features are to be used or not           |
| <code>product</code>             | TRUE                 | a logical value defining whether product features are to be used or not             |
| <code>threshold</code>           | TRUE                 | a logical value defining whether threshold features are to be used or not           |
| <code>hinge</code>               | TRUE                 | a logical value defining whether hinge features are to be used or not               |
| <code>l2lqthreshold</code>       | 10                   | an integer corresponding to the number of samples at which quadratic features st    |
| <code>lq2lqptthreshold</code>    | 80                   | an integer corresponding to the number of samples at which product and thresho      |
| <code>hingethreshold</code>      | 15                   | an integer corresponding to the number of samples at which hinge features start t   |
| <code>beta_lqp</code>            | -1.0                 | a numeric corresponding to the regularization parameter to be applied to all linear |
| <code>beta_threshold</code>      | -1.0                 | a numeric corresponding to the regularization parameter to be applied to all thresh |
| <code>beta_hinge</code>          | -1.0                 | a numeric corresponding to the regularization parameter to be applied to all hinge  |
| <code>beta_categorical</code>    | -1.0                 | a numeric corresponding to the regularization parameter to be applied to all catego |

|                     |              |                                                                                           |
|---------------------|--------------|-------------------------------------------------------------------------------------------|
| betamultiplier      | 1            | a numeric corresponding to the number by which multiply all automatic regularization      |
| defaultprevalence   | 0.5          | a numeric corresponding to the default prevalence of the modelled species ( <i>probab</i> |
| togglelayerselected | NULL         | a character defining the prefix to be used to REMOVE environmental layers who             |
| maximumbackground   | 10000        | an integer corresponding to the maximum number of pixels to be selected random            |
| maximumberations    | 500          | an integer corresponding to the maximum number of iterations for training                 |
| convergencehreshold | 0.00005      | a numeric corresponding to the drop in log loss per iteration below which the train       |
| autofeature         | TRUE         | a logical value defining whether feature classes to be used will automatically be         |
| jackknife           | FALSE        | a logical value defining whether variables' importance is to be measured or not.          |
| writelampgrid       | FALSE        | a logical value defining whether clamping mask is to be saved or not ( <i>absolute d</i>  |
| writemess           | FALSE        | a logical value defining whether multidimensional environmental similarity surfa          |
| logfile             | 'maxent.log' | a character corresponding to file name in which debugging information will be w           |
| verbose             | FALSE        | a logical value defining whether detailed diagnostics for debugging should be giv         |

### Author(s)

Damien Georges, Wilfried Thuiller, Maya Guéguen

### See Also

[ModelsTable](#), [OptionsBigboss](#), [BIOMOD.models.options](#), [bm\\_Tuning](#), [BIOMOD\\_Modeling](#)

Other Secondary functions: [bm\\_BinaryTransformation\(\)](#), [bm\\_CrossValidation\(\)](#), [bm\\_FindOptimStat\(\)](#), [bm\\_MakeFormula\(\)](#), [bm\\_ModelAnalysis\(\)](#), [bm\\_PlotEvalBoxplot\(\)](#), [bm\\_PlotEvalMean\(\)](#), [bm\\_PlotRangeSize\(\)](#), [bm\\_PlotResponseCurves\(\)](#), [bm\\_PlotVarImpBoxplot\(\)](#), [bm\\_PseudoAbsences\(\)](#), [bm\\_RangeSize\(\)](#), [bm\\_RunModelsLoop\(\)](#), [bm\\_SRE\(\)](#), [bm\\_SampleBinaryVector\(\)](#), [bm\\_SampleFactorLevels\(\)](#), [bm\\_Tuning\(\)](#), [bm\\_VariablesImportance\(\)](#)

### Examples

```
library(terra)

# Load species occurrences (6 species available)
data(DataSpecies)
head(DataSpecies)

# Select the name of the studied species
myRespName <- 'GuloGulo'

# Get corresponding presence/absence data
myResp <- as.numeric(DataSpecies[, myRespName])

# Get corresponding XY coordinates
myRespXY <- DataSpecies[, c('X_WGS84', 'Y_WGS84')]

# Load environmental variables extracted from BIOCLIM (bio_3, bio_4, bio_7, bio_11 & bio_12)
data(bioclim_current)
myExpl <- terra::rast(bioclim_current)
```



```

strategy = 'user.defined',
user.base = 'bigboss',
user.val = user.val)

opt.b
opt.u

## Not run:
# tuned parameters with formatted data
opt.t <- bm_ModelingOptions(data.type = 'binary',
                           models = c('SRE', 'XGBOOST'),
                           strategy = 'tuned',
                           bm.format = myBiomodData)

opt.t

## End(Not run)

```

---

|                    |                                          |
|--------------------|------------------------------------------|
| bm_PlotEvalBoxplot | <i>Plot boxplot of evaluation scores</i> |
|--------------------|------------------------------------------|

---

## Description

This function represents boxplot of evaluation scores of species distribution models, from [BIOMOD.models.out](#) or [BIOMOD.ensemble.models.out](#) objects that can be obtained from [BIOMOD\\_Modeling](#) or [BIOMOD\\_EnsembleModeling](#) functions. Scores are represented according to 2 grouping methods (see Details).

## Usage

```

bm_PlotEvalBoxplot(
  bm.out,
  dataset = "calibration",
  group.by = c("algo", "run"),
  do.plot = TRUE,
  ...
)

```

## Arguments

|         |                                                                                                                                                                                                             |
|---------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| bm.out  | a <a href="#">BIOMOD.models.out</a> or <a href="#">BIOMOD.ensemble.models.out</a> object that can be obtained with the <a href="#">BIOMOD_Modeling</a> or <a href="#">BIOMOD_EnsembleModeling</a> functions |
| dataset | a character corresponding to the dataset upon which evaluation metrics have been calculated and that is to be represented, must be among calibration, validation, evaluation                                |

|          |                                                                                                                                                                                                                                                                                                      |
|----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| group.by | a 2-length vector containing the way kept models will be represented, must be among full.name, PA, run, algo (if bm.out is a <a href="#">BIOMOD.models.out</a> object), or full.name, merged.by.PA, merged.by.run, merged.by.algo (if bm.out is a <a href="#">BIOMOD.ensemble.models.out</a> object) |
| do.plot  | ( <i>optional, default</i> TRUE)<br>A logical value defining whether the plot is to be rendered or not                                                                                                                                                                                               |
| ...      | some additional arguments (see Details)                                                                                                                                                                                                                                                              |

### Details

... can take the following values :

- main : a character corresponding to the graphic title
- scales : a character corresponding to the scales argument of the [facet\\_wrap](#) function, must be either fixed, free\_x, free\_y or free

### Value

A list containing a data.frame with evaluation scores and the corresponding ggplot object representing them in boxplot.

### Author(s)

Damien Georges, Maya Guéguen

### See Also

[BIOMOD.models.out](#), [BIOMOD.ensemble.models.out](#), [BIOMOD\\_Modeling](#), [BIOMOD\\_EnsembleModeling](#), [get\\_evaluations](#)

Other Secondary functions: [bm\\_BinaryTransformation\(\)](#), [bm\\_CrossValidation\(\)](#), [bm\\_FindOptimStat\(\)](#), [bm\\_MakeFormula\(\)](#), [bm\\_ModelAnalysis\(\)](#), [bm\\_ModelingOptions\(\)](#), [bm\\_PlotEvalMean\(\)](#), [bm\\_PlotRangeSize\(\)](#), [bm\\_PlotResponseCurves\(\)](#), [bm\\_PlotVarImpBoxplot\(\)](#), [bm\\_PseudoAbsences\(\)](#), [bm\\_RangeSize\(\)](#), [bm\\_RunModelsLoop\(\)](#), [bm\\_SRE\(\)](#), [bm\\_SampleBinaryVector\(\)](#), [bm\\_SampleFactorLevels\(\)](#), [bm\\_Tuning\(\)](#), [bm\\_VariablesImportance\(\)](#)

Other Plot functions: [bm\\_ModelAnalysis\(\)](#), [bm\\_PlotEvalMean\(\)](#), [bm\\_PlotRangeSize\(\)](#), [bm\\_PlotResponseCurves\(\)](#), [bm\\_PlotVarImpBoxplot\(\)](#)

### Examples

```
library(terra)

# Load species occurrences (6 species available)
data(DataSpecies)
head(DataSpecies)

# Select the name of the studied species
myRespName <- 'GuloGulo'

# Get corresponding presence/absence data
```

```

myResp <- as.numeric(DataSpecies[, myRespName])

# Get corresponding XY coordinates
myRespXY <- DataSpecies[, c('X_WGS84', 'Y_WGS84')]

# Load environmental variables extracted from BIOCLIM (bio_3, bio_4, bio_7, bio_11 & bio_12)
data(bioclim_current)
myExpl <- terra::rast(bioclim_current)

# -----
file.out <- paste0(myRespName, "/", myRespName, ".AllModels.models.out")
if (file.exists(file.out)) {
  myBiomodModelOut <- get(load(file.out))
} else {

  # Format Data with true absences
  myBiomodData <- BIOMOD_FormatingData(resp.name = myRespName,
                                       resp.var = myResp,
                                       resp.xy = myRespXY,
                                       expl.var = myExpl)

  # Model single models
  myBiomodModelOut <- BIOMOD_Modeling(bm.format = myBiomodData,
                                       modeling.id = 'AllModels',
                                       models = c('RF', 'GLM'),
                                       CV.strategy = 'random',
                                       CV.nb.rep = 2,
                                       CV.perc = 0.8,
                                       OPT.strategy = 'bigboss',
                                       metric.eval = c('TSS', 'ROC'),
                                       var.import = 3,
                                       seed.val = 42)

}

# -----
# Get evaluation scores
get_evaluations(myBiomodModelOut)

# Represent evaluation scores
bm_PlotEvalBoxplot(bm.out = myBiomodModelOut, group.by = c('algo', 'run'))

```

## Description

This function represents mean evaluation scores (and their standard deviation) of species distribution models, from `BIOMOD.models.out` or `BIOMOD.ensemble.models.out` objects that can be obtained from `BIOMOD_Modeling` or `BIOMOD_EnsembleModeling` functions. Scores are represented according to 2 different evaluation methods, and models can be grouped (see Details).

## Usage

```
bm_PlotEvalMean(
  bm.out,
  metric.eval = NULL,
  dataset = "calibration",
  group.by = "algo",
  do.plot = TRUE,
  ...
)
```

## Arguments

|                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|--------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>bm.out</code>      | a <code>BIOMOD.models.out</code> or <code>BIOMOD.ensemble.models.out</code> object that can be obtained with the <code>BIOMOD_Modeling</code> or <code>BIOMOD_EnsembleModeling</code> functions                                                                                                                                                                                                                                                                              |
| <code>metric.eval</code> | a 2-length vector containing evaluation metric names to be used, must be among the metrics used for <code>bm.out</code> and that can be obtained with the <code>get_evaluations</code> function applied to <code>bm.out</code>                                                                                                                                                                                                                                               |
| <code>dataset</code>     | a character corresponding to the dataset upon which evaluation metrics have been calculated and that is to be represented, must be among calibration, validation, evaluation                                                                                                                                                                                                                                                                                                 |
| <code>group.by</code>    | a character corresponding to the way kept models will be combined to compute mean and sd evaluation scores, must be among <code>full.name</code> , <code>PA</code> , <code>run</code> , <code>algo</code> (if <code>bm.out</code> is a <code>BIOMOD.models.out</code> object), or <code>full.name</code> , <code>merged.by.PA</code> , <code>merged.by.run</code> , <code>merged.by.algo</code> (if <code>bm.out</code> is a <code>BIOMOD.ensemble.models.out</code> object) |
| <code>do.plot</code>     | ( <i>optional, default TRUE</i> )<br>A logical value defining whether the plot is to be rendered or not                                                                                                                                                                                                                                                                                                                                                                      |
| <code>...</code>         | some additional arguments (see Details)                                                                                                                                                                                                                                                                                                                                                                                                                                      |

## Details

`...` can take the following values :

- `xlim` : an integer corresponding to the x maximum limit to represent
- `ylim` : an integer corresponding to the y maximum limit to represent
- `main` : a character corresponding to the graphic title
- `col` : a vector containing new color values

**Value**

A list containing a data.frame with mean and standard deviation of evaluation scores and the corresponding ggplot object representing them according to 2 different evaluation methods.

**Author(s)**

Damien Georges, Maya Guéguen

**See Also**

[BIOMOD.models.out](#), [BIOMOD.ensemble.models.out](#), [BIOMOD\\_Modeling](#), [BIOMOD\\_EnsembleModeling](#), [get\\_evaluations](#)

Other Secondary functions: [bm\\_BinaryTransformation\(\)](#), [bm\\_CrossValidation\(\)](#), [bm\\_FindOptimStat\(\)](#), [bm\\_MakeFormula\(\)](#), [bm\\_ModelAnalysis\(\)](#), [bm\\_ModelingOptions\(\)](#), [bm\\_PlotEvalBoxplot\(\)](#), [bm\\_PlotRangeSize\(\)](#), [bm\\_PlotResponseCurves\(\)](#), [bm\\_PlotVarImpBoxplot\(\)](#), [bm\\_PseudoAbsences\(\)](#), [bm\\_RangeSize\(\)](#), [bm\\_RunModelsLoop\(\)](#), [bm\\_SRE\(\)](#), [bm\\_SampleBinaryVector\(\)](#), [bm\\_SampleFactorLevels\(\)](#), [bm\\_Tuning\(\)](#), [bm\\_VariablesImportance\(\)](#)

Other Plot functions: [bm\\_ModelAnalysis\(\)](#), [bm\\_PlotEvalBoxplot\(\)](#), [bm\\_PlotRangeSize\(\)](#), [bm\\_PlotResponseCurves\(\)](#), [bm\\_PlotVarImpBoxplot\(\)](#)

**Examples**

```
library(terra)

# Load species occurrences (6 species available)
data(DataSpecies)
head(DataSpecies)

# Select the name of the studied species
myRespName <- 'GuloGulo'

# Get corresponding presence/absence data
myResp <- as.numeric(DataSpecies[, myRespName])

# Get corresponding XY coordinates
myRespXY <- DataSpecies[, c('X_WGS84', 'Y_WGS84')]

# Load environmental variables extracted from BIOCLIM (bio_3, bio_4, bio_7, bio_11 & bio_12)
data(bioclim_current)
myExpl <- terra::rast(bioclim_current)

# -----
file.out <- paste0(myRespName, "/", myRespName, ".AllModels.models.out")
if (file.exists(file.out)) {
  myBiomodModelOut <- get(load(file.out))
} else {

  # Format Data with true absences
```

```

myBiomodData <- BIOMOD_FormatingData(resp.name = myRespName,
                                     resp.var = myResp,
                                     resp.xy = myRespXY,
                                     expl.var = myExpl)

# Model single models
myBiomodModelOut <- BIOMOD_Modeling(bm.format = myBiomodData,
                                   modeling.id = 'AllModels',
                                   models = c('RF', 'GLM'),
                                   CV.strategy = 'random',
                                   CV.nb.rep = 2,
                                   CV.perc = 0.8,
                                   OPT.strategy = 'bigboss',
                                   metric.eval = c('TSS', 'ROC'),
                                   var.import = 3,
                                   seed.val = 42)
}

# -----
# Get evaluation scores
get_evaluations(myBiomodModelOut)

# Represent mean evaluation scores
bm_PlotEvalMean(bm.out = myBiomodModelOut)

```

---

|                  |                                  |
|------------------|----------------------------------|
| bm_PlotRangeSize | <i>Plot species range change</i> |
|------------------|----------------------------------|

---

## Description

This function represents species range change from object that can be obtained from [BIOMOD\\_RangeSize](#) function. Several graphics can be obtained, representing global counts or proportions of gains / losses, as well as spatial representations (see Details).

## Usage

```

bm_PlotRangeSize(
  bm.range,
  do.count = TRUE,
  do.perc = TRUE,
  do.maps = TRUE,
  do.mean = TRUE,
  do.plot = TRUE
)

```

**Arguments**

|          |                                                                                                           |
|----------|-----------------------------------------------------------------------------------------------------------|
| bm.range | an BIOMOD.rangesize.out object returned by the <a href="#">BIOMOD_RangeSize</a> function                  |
| do.count | (optional, default TRUE)<br>A logical value defining whether the count plot is to be computed or not      |
| do.perc  | (optional, default TRUE)<br>A logical value defining whether the percentage plot is to be computed or not |
| do.maps  | (optional, default TRUE)<br>A logical value defining whether the maps plot is to be computed or not       |
| do.mean  | (optional, default TRUE)<br>A logical value defining whether the mean maps plot is to be computed or not  |
| do.plot  | (optional, default TRUE)<br>A logical value defining whether the plots are to be rendered or not          |

**Details**

4 plots can be obtained with this function :

**Count barplot** representing absolute number of locations (pixels) lost, stable and gained

**Percentage barplot** representing percentage of locations (pixels) lost, stable, and the corresponding Species Range Change (PercGain - PercLoss)

**SRC models maps** representing spatially locations (pixels) lost, stable and gained for each single distribution model

**SRC community averaging maps** representing spatially locations (pixels) lost, stable and gained, taking the majoritary value across single distribution models (and representing the percentage of models' agreement)

*Please see [bm\\_RangeSize](#) function for more details about the values.*

**Value**

A list containing one or several data.frame and the corresponding ggplot object representing species range change.

**Author(s)**

Maya Guéguen, Hélène Blancheteau

**See Also**

[BIOMOD\\_RangeSize](#) [bm\\_RangeSize](#)

Other Secondary functions: [bm\\_BinaryTransformation\(\)](#), [bm\\_CrossValidation\(\)](#), [bm\\_FindOptimStat\(\)](#), [bm\\_MakeFormula\(\)](#), [bm\\_ModelAnalysis\(\)](#), [bm\\_ModelingOptions\(\)](#), [bm\\_PlotEvalBoxplot\(\)](#), [bm\\_PlotEvalMean\(\)](#), [bm\\_PlotResponseCurves\(\)](#), [bm\\_PlotVarImpBoxplot\(\)](#), [bm\\_PseudoAbsences\(\)](#), [bm\\_RangeSize\(\)](#), [bm\\_RunModelsLoop\(\)](#), [bm\\_SRE\(\)](#), [bm\\_SampleBinaryVector\(\)](#), [bm\\_SampleFactorLevels\(\)](#), [bm\\_Tuning\(\)](#), [bm\\_VariablesImportance\(\)](#)

Other Plot functions: [bm\\_ModelAnalysis\(\)](#), [bm\\_PlotEvalBoxplot\(\)](#), [bm\\_PlotEvalMean\(\)](#), [bm\\_PlotResponseCurves\(\)](#), [bm\\_PlotVarImpBoxplot\(\)](#)

**Examples**

```

library(terra)

# Load species occurrences (6 species available)
data(DataSpecies)
head(DataSpecies)

# Select the name of the studied species
myRespName <- 'GuloGulo'

# Get corresponding presence/absence data
myResp <- as.numeric(DataSpecies[, myRespName])

# Get corresponding XY coordinates
myRespXY <- DataSpecies[, c('X_WGS84', 'Y_WGS84')]

# Load environmental variables extracted from BIOCLIM (bio_3, bio_4, bio_7, bio_11 & bio_12)
data(bioclim_current)
myExpl <- terra::rast(bioclim_current)

# -----#
file.out <- paste0(myRespName, "/", myRespName, ".AllModels.models.out")
if (file.exists(file.out)) {
  myBiomodModelOut <- get(load(file.out))
} else {

  # Format Data with true absences
  myBiomodData <- BIOMOD_FormatingData(resp.name = myRespName,
                                     resp.var = myResp,
                                     resp.xy = myRespXY,
                                     expl.var = myExpl)

  # Model single models
  myBiomodModelOut <- BIOMOD_Modeling(bm.format = myBiomodData,
                                     modeling.id = 'AllModels',
                                     models = c('RF', 'GLM'),
                                     CV.strategy = 'random',
                                     CV.nb.rep = 2,
                                     CV.perc = 0.8,
                                     OPT.strategy = 'bigboss',
                                     metric.eval = c('TSS', 'ROC'),
                                     var.import = 3,
                                     seed.val = 42)
}

models.proj <- get_built_models(myBiomodModelOut, algo = "RF")
# Project single models
myBiomodProj <- BIOMOD_Projection(bm.mod = myBiomodModelOut,
                                 proj.name = 'CurrentRangeSize',
                                 new.env = myExpl,

```

```

models.chosen = models.proj,
metric.binary = 'all')

# -----#
# Load environmental variables extracted from BIOCLIM (bio_3, bio_4, bio_7, bio_11 & bio_12)
data(bioclim_future)
myExplFuture <- terra::rast(bioclim_future)

# Project onto future conditions
myBiomodProjectionFuture <- BIOMOD_Projection(bm.mod = myBiomodModelOut,
                                              proj.name = 'FutureRangeSize',
                                              new.env = myExplFuture,
                                              models.chosen = models.proj,
                                              metric.binary = 'TSS')

# Compute differences
myBiomodRangeSize <- BIOMOD_RangeSize(proj.current = myBiomodProj,
                                      proj.future = myBiomodProjectionFuture,
                                      metric.binary = "TSS")

# Represent main results
bm_PlotRangeSize(bm.range = myBiomodRangeSize)

```

---

bm\_PlotResponseCurves *Plot response curves*

---

## Description

This function represents response curves of species distribution models, from [BIOMOD.models.out](#) or [BIOMOD.ensemble.models.out](#) objects that can be obtained from [BIOMOD\\_Modeling](#) or [BIOMOD\\_EnsembleModeling](#) functions. Response curves can be represented in either 2 or 3 dimensions (meaning 1 or 2 explanatory variables at a time, see Details).

## Usage

```

bm_PlotResponseCurves(
  bm.out,
  models.chosen = "all",
  new.env = get_formal_data(bm.out, "expl.var"),
  show.variables = get_formal_data(bm.out, "expl.var.names"),
  fixed.var = "mean",
  do.bivariate = FALSE,

```

```

do.plot = TRUE,
do.progress = TRUE,
...
)

```

## Arguments

|                |                                                                                                                                                                                                                                                                                                                                                                                                                         |
|----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| bm.out         | a <code>BIOMOD.models.out</code> or <code>BIOMOD.ensemble.models.out</code> object that can be obtained with the <code>BIOMOD_Modeling</code> or <code>BIOMOD_EnsembleModeling</code> functions                                                                                                                                                                                                                         |
| models.chosen  | a vector containing model names to be kept, must be either all or a sub-selection of model names that can be obtained with the <code>get_built_models</code> function                                                                                                                                                                                                                                                   |
| new.env        | a matrix, data.frame or <code>SpatRaster</code> object containing the new explanatory variables (in columns or layers, with names matching the variables names given to the <code>BIOMOD_FormatingData</code> function to build <code>bm.out</code> ) that will be used to project the species distribution model(s)<br><i>Note that old format from <b>raster</b> are still supported such as RasterStack objects.</i> |
| show.variables | a vector containing the names of the explanatory variables present into <code>new.env</code> parameter and to be plotted                                                                                                                                                                                                                                                                                                |
| fixed.var      | a character corresponding to the statistic to be used to fix as constant the remaining variables other than the one used to predict response, must be either mean, median, min, max                                                                                                                                                                                                                                     |
| do.bivariate   | (optional, default FALSE)<br>A logical value defining whether the response curves are to be represented in 3 dimensions (meaning 2 explanatory variables at a time) or not (meaning only 1)                                                                                                                                                                                                                             |
| do.plot        | (optional, default TRUE)<br>A logical value defining whether the plot is to be rendered or not                                                                                                                                                                                                                                                                                                                          |
| do.progress    | (optional, default TRUE)<br>A logical value defining whether the progress bar is to be rendered or not                                                                                                                                                                                                                                                                                                                  |
| ...            | some additional arguments (see Details)                                                                                                                                                                                                                                                                                                                                                                                 |

## Details

This function is an adaptation of the Evaluation Strip method proposed by Elith et al. (2005). To build the predicted response curves :

- n-1 variables are set constant to a fixed value determined by the `fixed.var` parameter (in the case of categorical variable, the most represented class is taken)
- the remaining variable is made to vary throughout its range given by the `new.env` parameter
- predicted values are computed with these n-1 fixed variables, and this studied variable varying

If `do.bivariate = TRUE`, 2 variables are varying at the same time.

The response curves obtained show the sensibility of the model to the studied variable.  
Note that this method does not account for interactions between variables.

... can take the following values :

- `main` : a character corresponding to the graphic title

## Value

A list containing a data.frame with variables and predicted values and the corresponding ggplot object representing response curves.

## Author(s)

Damien Georges, Maya Guéguen

## References

- Elith J, Ferrier S, Huettmann F, Leathwick JR (2005). *The evaluation strip: A new and robust method for plotting predicted responses from species distribution models*. Ecological Modelling, 186, 280-289. doi:[10.1016/j.ecolmodel.2004.12.007](https://doi.org/10.1016/j.ecolmodel.2004.12.007)

## See Also

[BIOMOD.models.out](#), [BIOMOD.ensemble.models.out](#), [BIOMOD\\_Modeling](#), [BIOMOD\\_EnsembleModeling](#)

Other Secondary functions: [bm\\_BinaryTransformation\(\)](#), [bm\\_CrossValidation\(\)](#), [bm\\_FindOptimStat\(\)](#), [bm\\_MakeFormula\(\)](#), [bm\\_ModelAnalysis\(\)](#), [bm\\_ModelingOptions\(\)](#), [bm\\_PlotEvalBoxplot\(\)](#), [bm\\_PlotEvalMean\(\)](#), [bm\\_PlotRangeSize\(\)](#), [bm\\_PlotVarImpBoxplot\(\)](#), [bm\\_PseudoAbsences\(\)](#), [bm\\_RangeSize\(\)](#), [bm\\_RunModelsLoop\(\)](#), [bm\\_SRE\(\)](#), [bm\\_SampleBinaryVector\(\)](#), [bm\\_SampleFactorLevels\(\)](#), [bm\\_Tuning\(\)](#), [bm\\_VariablesImportance\(\)](#)

Other Plot functions: [bm\\_ModelAnalysis\(\)](#), [bm\\_PlotEvalBoxplot\(\)](#), [bm\\_PlotEvalMean\(\)](#), [bm\\_PlotRangeSize\(\)](#), [bm\\_PlotVarImpBoxplot\(\)](#)

## Examples

```
library(terra)

# Load species occurrences (6 species available)
data(DataSpecies)
head(DataSpecies)

# Select the name of the studied species
myRespName <- 'GuloGulo'

# Get corresponding presence/absence data
myResp <- as.numeric(DataSpecies[, myRespName])

# Get corresponding XY coordinates
myRespXY <- DataSpecies[, c('X_WGS84', 'Y_WGS84')]
```

```

# Load environmental variables extracted from BIOCLIM (bio_3, bio_4, bio_7, bio_11 & bio_12)
data(bioclim_current)
myExpl <- terra::rast(bioclim_current)

# -----#
file.out <- paste0(myRespName, "/", myRespName, ".AllModels.models.out")
if (file.exists(file.out)) {
  myBiomodModelOut <- get(load(file.out))
} else {

  # Format Data with true absences
  myBiomodData <- BIOMOD_FormatingData(resp.name = myRespName,
                                       resp.var = myResp,
                                       resp.xy = myRespXY,
                                       expl.var = myExpl)

  # Model single models
  myBiomodModelOut <- BIOMOD_Modeling(bm.format = myBiomodData,
                                     modeling.id = 'AllModels',
                                     models = c('RF', 'GLM'),
                                     CV.strategy = 'random',
                                     CV.nb.rep = 2,
                                     CV.perc = 0.8,
                                     OPT.strategy = 'bigboss',
                                     metric.eval = c('TSS', 'ROC'),
                                     var.import = 3,
                                     seed.val = 42)
}

# -----#
# Represent response curves
mods <- get_built_models(myBiomodModelOut, run = 'RUN1')
bm_PlotResponseCurves(bm.out = myBiomodModelOut,
                       models.chosen = mods,
                       fixed.var = 'median')
## fixed.var can also be set to 'min', 'max' or 'mean'
# bm_PlotResponseCurves(bm.out = myBiomodModelOut,
#                         models.chosen = mods,
#                         fixed.var = 'min')

# Bivariate case (one model)
# variables can be selected with argument 'show.variables'
# models can be selected with argument 'models.chosen'
mods <- get_built_models(myBiomodModelOut, full.name = 'GuloGulo_allData_RUN2_RF')
bm_PlotResponseCurves(bm.out = myBiomodModelOut,
                       show.variables = c("bio4", "bio12", "bio11"),
                       models.chosen = mods,
                       fixed.var = 'median',
                       do.bivariate = TRUE)

```

---

 bm\_PlotVarImpBoxplot *Plot boxplot of variables importance*


---

## Description

This function represents boxplot of variables importance of species distribution models, from `BIOMOD.models.out` or `BIOMOD.ensemble.models.out` objects that can be obtained from `BIOMOD_Modeling` or `BIOMOD_EnsembleModeling` functions. Scores are represented according to 3 grouping methods (see Details).

## Usage

```
bm_PlotVarImpBoxplot(
  bm.out,
  group.by = c("run", "expl.var", "algo"),
  do.plot = TRUE,
  ...
)
```

## Arguments

|          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| bm.out   | a <code>BIOMOD.models.out</code> or <code>BIOMOD.ensemble.models.out</code> object that can be obtained with the <code>BIOMOD_Modeling</code> or <code>BIOMOD_EnsembleModeling</code> functions                                                                                                                                                                                                                                                                                        |
| group.by | a 3-length vector containing the way kept models will be represented, must be among <code>full.name</code> , <code>PA</code> , <code>run</code> , <code>algo</code> , <code>expl.var</code> (if <code>bm.out</code> is a <code>BIOMOD.models.out</code> object), or <code>full.name</code> , <code>merged.by.PA</code> , <code>merged.by.run</code> , <code>merged.by.algo</code> , <code>expl.var</code> (if <code>bm.out</code> is a <code>BIOMOD.ensemble.models.out</code> object) |
| do.plot  | ( <i>optional, default TRUE</i> )<br>A logical value defining whether the plot is to be rendered or not                                                                                                                                                                                                                                                                                                                                                                                |
| ...      | some additional arguments (see Details)                                                                                                                                                                                                                                                                                                                                                                                                                                                |

## Details

... can take the following values :

- `main` : a character corresponding to the graphic title

## Value

A list containing a `data.frame` with variables importance and the corresponding `ggplot` object representing them in boxplot.

## Author(s)

Damien Georges, Maya Guéguen

**See Also**

BIOMOD.models.out, BIOMOD.ensemble.models.out, BIOMOD\_Modeling, BIOMOD\_EnsembleModeling, get\_variables\_importance

Other Secondary functions: `bm_BinaryTransformation()`, `bm_CrossValidation()`, `bm_FindOptimStat()`, `bm_MakeFormula()`, `bm_ModelAnalysis()`, `bm_ModelingOptions()`, `bm_PlotEvalBoxplot()`, `bm_PlotEvalMean()`, `bm_PlotRangeSize()`, `bm_PlotResponseCurves()`, `bm_PseudoAbsences()`, `bm_RangeSize()`, `bm_RunModelsLoop()`, `bm_SRE()`, `bm_SampleBinaryVector()`, `bm_SampleFactorLevels()`, `bm_Tuning()`, `bm_VariablesImportance()`

Other Plot functions: `bm_ModelAnalysis()`, `bm_PlotEvalBoxplot()`, `bm_PlotEvalMean()`, `bm_PlotRangeSize()`, `bm_PlotResponseCurves()`

**Examples**

```
library(terra)

# Load species occurrences (6 species available)
data(DataSpecies)
head(DataSpecies)

# Select the name of the studied species
myRespName <- 'GuloGulo'

# Get corresponding presence/absence data
myResp <- as.numeric(DataSpecies[, myRespName])

# Get corresponding XY coordinates
myRespXY <- DataSpecies[, c('X_WGS84', 'Y_WGS84')]

# Load environmental variables extracted from BIOCLIM (bio_3, bio_4, bio_7, bio_11 & bio_12)
data(bioclim_current)
myExpl <- terra::rast(bioclim_current)

# -----
file.out <- paste0(myRespName, "/", myRespName, ".AllModels.models.out")
if (file.exists(file.out)) {
  myBiomodModelOut <- get(load(file.out))
} else {

  # Format Data with true absences
  myBiomodData <- BIOMOD_FormatingData(resp.name = myRespName,
                                       resp.var = myResp,
                                       resp.xy = myRespXY,
                                       expl.var = myExpl)

  # Model single models
  myBiomodModelOut <- BIOMOD_Modeling(bm.format = myBiomodData,
                                       modeling.id = 'AllModels',
                                       models = c('RF', 'GLM'),
                                       CV.strategy = 'random',
                                       CV.nb.rep = 2,
```

```

CV.perc = 0.8,
OPT.strategy = 'bigboss',
metric.eval = c('TSS', 'ROC'),
var.import = 3,
seed.val = 42)
}

# -----
# Get variables importance
get_variables_importance(myBiomodModelOut)

# Represent variables importance
bm_PlotVarImpBoxplot(bm.out = myBiomodModelOut, group.by = c('expl.var', 'algo', 'algo'))
bm_PlotVarImpBoxplot(bm.out = myBiomodModelOut, group.by = c('expl.var', 'algo', 'PA'))
bm_PlotVarImpBoxplot(bm.out = myBiomodModelOut, group.by = c('algo', 'expl.var', 'PA'))

```

---

|                   |                               |
|-------------------|-------------------------------|
| bm_PseudoAbsences | <i>Select pseudo-absences</i> |
|-------------------|-------------------------------|

---

## Description

This internal **biomod2** function allows to select pseudo-absences according to 4 different methods : random, sre, disk or user-defined (see Details).

## Usage

```

bm_PseudoAbsences(
  resp.var,
  expl.var,
  strategy,
  nb.rep = NULL,
  nb.absences = NULL,
  sre.quant = NULL,
  dist.min = 0,
  dist.max = NULL,
  fact.aggr = NULL,
  user.table = NULL,
  seed.val = NULL
)

bm_PseudoAbsences_user.defined(resp.var, expl.var, ...)

## S4 method for signature 'ANY,SpatVector'
bm_PseudoAbsences_user.defined(resp.var, expl.var, user.table)

```

```

## S4 method for signature 'ANY,SpatRaster'
bm_PseudoAbsences_user.defined(resp.var, expl.var, user.table)

bm_PseudoAbsences_random(resp.var, expl.var, ...)

## S4 method for signature 'ANY,SpatVector'
bm_PseudoAbsences_random(resp.var, expl.var, nb.absences, nb.rep, fact.aggr)

## S4 method for signature 'ANY,SpatRaster'
bm_PseudoAbsences_random(resp.var, expl.var, nb.absences, nb.rep, fact.aggr)

bm_PseudoAbsences_sre(resp.var, expl.var, ...)

## S4 method for signature 'ANY,SpatVector'
bm_PseudoAbsences_sre(resp.var, expl.var, sre.quant, nb.absences, nb.rep)

## S4 method for signature 'ANY,SpatRaster'
bm_PseudoAbsences_sre(resp.var, expl.var, sre.quant, nb.absences, nb.rep)

bm_PseudoAbsences_disk(resp.var, expl.var, ...)

## S4 method for signature 'ANY,SpatVector'
bm_PseudoAbsences_disk(
  resp.var,
  expl.var,
  dist.min,
  dist.max,
  nb.absences,
  nb.rep,
  fact.aggr
)

## S4 method for signature 'ANY,SpatRaster'
bm_PseudoAbsences_disk(
  resp.var,
  expl.var,
  dist.min,
  dist.max,
  nb.absences,
  nb.rep,
  fact.aggr
)

```

### Arguments

**resp.var** a vector, [SpatialPoints](#) or [SpatialPointsDataFrame](#) object containing binary data (0 : absence, 1 : presence, NA : indeterminate) for a single species that will be used to find the pseudo-absences

|             |                                                                                                                                                                                                                                                                                                                                                                                                                          |
|-------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| expl.var    | a matrix, data.frame, <a href="#">SpatialPointsDataFrame</a> or <a href="#">SpatRaster</a> object containing the explanatory variables (in columns or layers) that will be used to find the pseudo-absences                                                                                                                                                                                                              |
| strategy    | a character corresponding to the pseudo-absence selection strategy, must be among random, sre, disk or user.defined                                                                                                                                                                                                                                                                                                      |
| nb.rep      | (optional, default NULL)<br>If strategy != 'user.defined', an integer corresponding to the number of sets (repetitions) of pseudo-absence points that will be drawn                                                                                                                                                                                                                                                      |
| nb.absences | (optional, default NULL)<br>If strategy = 'random' or strategy = 'sre' or strategy = 'disk', an integer corresponding to the number of pseudo-absence points that will be selected for each pseudo-absence repetition (true absences included).<br>It can also be a vector of the same length as nb.rep containing integer values corresponding to the different numbers of pseudo-absences to be selected (see Details) |
| sre.quant   | (optional, default NULL)<br>If strategy = 'sre', a numeric between 0 and 0.5 defining the half-quantile used to make the sre pseudo-absence selection (see <a href="#">bm_SRE</a> )                                                                                                                                                                                                                                      |
| dist.min    | (optional, default 0)<br>If strategy = 'disk', a numeric defining the minimal distance to presence points used to make the disk pseudo-absence selection (in the same projection system units as expl.var)                                                                                                                                                                                                               |
| dist.max    | (optional, default NULL)<br>If strategy = 'disk', a numeric defining the maximal distance to presence points used to make the disk pseudo-absence selection (in the same projection system units as expl.var)                                                                                                                                                                                                            |
| fact.aggr   | (optional, default NULL)<br>If strategy = 'random' or strategy = 'disk', an integer defining the factor of aggregation to reduce the spatial resolution of the environmental variables                                                                                                                                                                                                                                   |
| user.table  | (optional, default NULL)<br>If strategy = 'user.defined', a matrix or data.frame with as many rows as resp.var values, as many columns as nb.rep, and containing TRUE or FALSE values defining which points will be used to build the species distribution model(s) for each repetition                                                                                                                                  |
| seed.val    | (optional, default NULL)<br>An integer value corresponding to the new seed value to be set                                                                                                                                                                                                                                                                                                                               |
| ...         | (optional, one or several of the listed above arguments depending on the selected method)                                                                                                                                                                                                                                                                                                                                |

## Details

### Concerning random selection :

The idea is to select pseudo-absences randomly in spatial locations where the species has not been sampled. This method is the simplest one and the most appropriate if lacking information about the presence sampling (non-exhaustive, biased sampling, etc).

**Concerning SRE selection (see [bm\\_SRE](#)) :**

The idea is to select pseudo-absences in spatial locations whose environmental conditions are different from those of the presence points. This method is appropriate when most of the environmental space of the species has been sampled.

**Concerning disk selection :**

The idea is to select pseudo-absences, not too close from presence points, but not too far away either. This method is appropriate when most of the spatial range of the species has been sampled.

**Concerning user defined selection :**

The user can provide pseudo-absences locations through a table containing spatial locations in rows, pseudo-absences repetitions in columns, and TRUE/FALSE values indicating whether each point is to be considered as pseudo-absence or not for each dataset.

**Concerning multiple size selection :**

It is possible to select create several pseudo-absence repetitions with different number of points, BUT with the same sampling strategy. `nb.absences` must contain as many values as the number of sets of pseudo-absences (`nb.rep`).

**Value**

A list containing the following elements :

- `xy` : the coordinates of the species observations
- `sp` : the values of the species observations (0, 1 or NA)
- `env` : the explanatory variables
- `pa.tab` : the corresponding table of selected pseudo-absences (indicated by TRUE or FALSE)

**Author(s)**

Wilfried Thuiller, Damien Georges

**See Also**

[bm\\_SRE](#), [BIOMOD.formated.data.PA](#), [BIOMOD.FormatingData](#)

Other Secondary functions: [bm\\_BinaryTransformation\(\)](#), [bm\\_CrossValidation\(\)](#), [bm\\_FindOptimStat\(\)](#), [bm\\_MakeFormula\(\)](#), [bm\\_ModelAnalysis\(\)](#), [bm\\_ModelingOptions\(\)](#), [bm\\_PlotEvalBoxplot\(\)](#), [bm\\_PlotEvalMean\(\)](#), [bm\\_PlotRangeSize\(\)](#), [bm\\_PlotResponseCurves\(\)](#), [bm\\_PlotVarImpBoxplot\(\)](#), [bm\\_RangeSize\(\)](#), [bm\\_RunModelsLoop\(\)](#), [bm\\_SRE\(\)](#), [bm\\_SampleBinaryVector\(\)](#), [bm\\_SampleFactorLevels\(\)](#), [bm\\_Tuning\(\)](#), [bm\\_VariablesImportance\(\)](#)

**Examples**

```

library(terra)

# Load species occurrences (6 species available)
data(DataSpecies)
head(DataSpecies)

# Select the name of the studied species
myRespName <- 'GuloGulo'

# Get corresponding presence/absence data
myResp <- as.numeric(DataSpecies[, myRespName])

# Get corresponding XY coordinates
myRespXY <- DataSpecies[, c('X_WGS84', 'Y_WGS84')]

# Load environmental variables extracted from BIOCLIM (bio_3, bio_4, bio_7, bio_11 & bio_12)
data(bioclim_current)
myExpl <- terra::rast(bioclim_current)

# ----- #
# Create the different pseudo-absence datasets

# Transform true absences into potential pseudo-absences
myResp.PA <- ifelse(myResp == 1, 1, NA)
myResp.PA.vect <- vect(cbind(myRespXY, myResp.PA), geom = c("X_WGS84", "Y_WGS84"))

# random method
PA.r <- bm_PseudoAbsences(resp.var = myResp.PA.vect,
                          expl.var = myExpl,
                          nb.rep = 4,
                          nb.absences = 1000,
                          strategy = 'random')

# disk method
PA.d <- bm_PseudoAbsences(resp.var = myResp.PA.vect,
                          expl.var = myExpl,
                          nb.rep = 4,
                          nb.absences = 500,
                          strategy = 'disk',
                          dist.min = 5,
                          dist.max = 35)

# SRE method
PA.s <- bm_PseudoAbsences(resp.var = myResp.PA.vect,
                          expl.var = myExpl,
                          nb.rep = 4,
                          nb.absences = 1000,
                          strategy = 'sre',

```

```

sre.quant = 0.025)

# user.defined method
myPatable <- data.frame(PA1 = ifelse(myResp == 1, TRUE, FALSE),
                        PA2 = ifelse(myResp == 1, TRUE, FALSE))
for (i in 1:ncol(myPatable)) myPatable[sample(which(myPatable[, i] == FALSE), 500), i] = TRUE
PA.u <- bm_PseudoAbsences(resp.var = myResp.PA.vect,
                          expl.var = myExpl,
                          strategy = 'user.defined',
                          user.table = myPatable)

str(PA.r)
head(PA.r$pa.tab)
apply(PA.r$pa.tab, 2, table)

head(PA.d$pa.tab)
apply(PA.d$pa.tab, 2, table)

head(PA.s$pa.tab)
apply(PA.s$pa.tab, 2, table)

tail(PA.u$pa.tab)
apply(PA.u$pa.tab, 2, table)

# random method : different number of PA
PA.r_mult <- bm_PseudoAbsences(resp.var = myResp.PA.vect,
                              expl.var = myExpl,
                              nb.rep = 4,
                              nb.absences = c(1000, 500, 500, 200),
                              strategy = 'random')

str(PA.r_mult)
head(PA.r_mult$pa.tab)
apply(PA.r_mult$pa.tab, 2, table)

```

bm\_RangeSize

---

*Analyze the range size differences between projections of species distribution models*

---

## Description

This function allows to calculate the absolute number of locations (pixels) lost, stable and gained, as well as the corresponding relative proportions, between two (or more) binary projections of (ensemble) species distribution models (*which can represent new time scales or environmental scenarios for example*).

**Usage**

```
bm_RangeSize(proj.current, proj.future, ordinal = FALSE)

## S4 method for signature 'data.frame,data.frame'
bm_RangeSize(proj.current, proj.future, ordinal = FALSE)

## S4 method for signature 'SpatRaster,SpatRaster'
bm_RangeSize(proj.current, proj.future, ordinal = FALSE)
```

**Arguments**

|              |                                                                                                                                                                            |
|--------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| proj.current | a data.frame, <a href="#">RasterLayer</a> or <a href="#">SpatRaster</a> object containing the initial binary projection(s) of the (ensemble) species distribution model(s) |
| proj.future  | a data.frame, <a href="#">RasterLayer</a> or <a href="#">SpatRaster</a> object containing the final binary projection(s) of the (ensemble) species distribution model(s)   |
| ordinal      | a logical indicating whether or not the projections should be considered as ordinal data                                                                                   |

**Details**

Note that **this function is only relevant to compare binary projections, made on the same area with the same resolution.**

Comparison between proj.current and proj.future depends on the number of projection in both objects: | proj.current | proj.future | **Comparison** | | ————— | | ————— |  
 ——— | ————— | | **1 projection** (e.g. data.frame with 1 column, SpatRaster with 1 layer) | | **1 projection** (e.g. data.frame with 1 column, SpatRaster with 1 layer) | comparison of both projection (e.g. current vs future conditions for the same model ; current vs current condition for two different models) | | **n projections** (e.g. data.frame with n column, SpatRaster with n layer) | | **n projections** (e.g. data.frame with n column, SpatRaster with n layer) | comparing projection i in proj.current to projection i in proj.future (e.g. comparing current vs future condition for n models) | | **1 projection** (e.g. data.frame with 1 column, SpatRaster with 1 layer) | | **n projections** (e.g. data.frame with n column, SpatRaster with n layer) | comparing projection in proj.current to each projection in proj.future (e.g. comparing current vs n different future condition (e.g. climate change scenario) for 1 model) |

For binary data, Diff.By.Pixel object is obtained by applying the simple following formula :

$$proj.future - 2 * proj.current$$

For non binary data, Diff.By.Pixel object is obtained by rescaling the two projection to a 0 to 1 scale and applying the simple following formula :

$$proj.future - proj.current$$

**Value**

A list containing two objects :

**Compt.By.Species** a data.frame containing the summary of range change for each comparison

- Loss : number of pixels predicted to be lost
- Stable\_Abs : number of pixels not currently occupied and not predicted to be
- Stable\_Pres : number of pixels currently occupied and predicted to remain occupied
- Gain : number of pixels predicted to be gained
- PercLoss : percentage of pixels currently occupied and predicted to be lost ( $\text{Loss} / (\text{Loss} + \text{Stable\_Pres})$ )
- PercGain : percentage of pixels predicted to be gained compare to the number of pixels currently occupied ( $\text{Gain} / (\text{Loss} + \text{Stable\_Pres})$ )
- SpeciesRangeChange : percentage of pixels predicted to change (loss or gain) compare to the number of pixels currently occupied ( $\text{PercGain} - \text{PercLoss}$ )
- CurrentRangeSize : number of pixels currently occupied
- FutureRangeSize0Disp : number of pixels predicted to be occupied, assuming no migration
- FutureRangeSize1Disp : number of pixels predicted to be occupied, assuming migration

**loss.gain** an object in the same form than the input data (proj.current and proj.future) and containing a value for each point/pixel of each comparison among :

- -2 : predicted to be lost
- -1 : predicted to remain occupied
- 0 : predicted to remain unoccupied
- 1 : predicted to be gained

**Diff.By.Pixel** an object in the same form than the input data (proj.current and proj.future) and containing a value for each point/pixel of each comparison obtain with :

- Future - 2\* Current for binary data
- Future - Current for nonbinary

### Author(s)

Wilfried Thuiller, Damien Georges, Bruno Lafourcade

### See Also

[BIOMOD\\_Projection](#), [BIOMOD\\_EnsembleForecasting](#), [bm\\_PlotRangeSize](#)

Other Secondary functions: [bm\\_BinaryTransformation\(\)](#), [bm\\_CrossValidation\(\)](#), [bm\\_FindOptimStat\(\)](#), [bm\\_MakeFormula\(\)](#), [bm\\_ModelAnalysis\(\)](#), [bm\\_ModelingOptions\(\)](#), [bm\\_PlotEvalBoxplot\(\)](#), [bm\\_PlotEvalMean\(\)](#), [bm\\_PlotRangeSize\(\)](#), [bm\\_PlotResponseCurves\(\)](#), [bm\\_PlotVarImpBoxplot\(\)](#), [bm\\_PseudoAbsences\(\)](#), [bm\\_RunModelsLoop\(\)](#), [bm\\_SRE\(\)](#), [bm\\_SampleBinaryVector\(\)](#), [bm\\_SampleFactorLevels\(\)](#), [bm\\_Tuning\(\)](#), [bm\\_VariablesImportance\(\)](#)

### Examples

```
library(terra)

# Load species occurrences (6 species available)
data(DataSpecies)
```

```

head(DataSpecies)

# Select the name of the studied species
myRespName <- 'GuloGulo'

# Get corresponding presence/absence data
myResp <- as.numeric(DataSpecies[, myRespName])

# Get corresponding XY coordinates
myRespXY <- DataSpecies[, c('X_WGS84', 'Y_WGS84')]

# Load environmental variables extracted from BIOCLIM (bio_3, bio_4, bio_7, bio_11 & bio_12)
data(bioclim_current)
myExpl <- terra::rast(bioclim_current)

# ----- #
file.out <- paste0(myRespName, "/", myRespName, ".AllModels.models.out")
if (file.exists(file.out)) {
  myBiomodModelOut <- get(load(file.out))
} else {

  # Format Data with true absences
  myBiomodData <- BIOMOD_FormatingData(resp.name = myRespName,
                                     resp.var = myResp,
                                     resp.xy = myRespXY,
                                     expl.var = myExpl)

  # Model single models
  myBiomodModelOut <- BIOMOD_Modeling(bm.format = myBiomodData,
                                     modeling.id = 'AllModels',
                                     models = c('RF', 'GLM'),
                                     CV.strategy = 'random',
                                     CV.nb.rep = 2,
                                     CV.perc = 0.8,
                                     OPT.strategy = 'bigboss',
                                     metric.eval = c('TSS', 'ROC'),
                                     var.import = 3,
                                     seed.val = 42)
}

models.proj <- get_built_models(myBiomodModelOut, algo = "RF")
# Project single models
myBiomodProj <- BIOMOD_Projection(bm.mod = myBiomodModelOut,
                                proj.name = 'CurrentRangeSize',
                                new.env = myExpl,
                                models.chosen = models.proj,
                                metric.binary = 'all',
                                build.clamping.mask = TRUE)

# ----- #

```

```

# Load environmental variables extracted from BIOCLIM (bio_3, bio_4, bio_7, bio_11 & bio_12)
data(bioclim_future)
myExplFuture <- terra::rast(bioclim_future)

# Project onto future conditions
myBiomodProjectionFuture <- BIOMOD_Projection(bm.mod = myBiomodModelOut,
                                              proj.name = 'FutureRangeSize',
                                              new.env = myExplFuture,
                                              models.chosen = models.proj,
                                              metric.binary = 'TSS')

# Load current and future binary projections
CurrentProj <- get_predictions(myBiomodProj,
                              metric.binary = "TSS",
                              model.as.col = TRUE)
FutureProj <- get_predictions(myBiomodProjectionFuture,
                              metric.binary = "TSS",
                              model.as.col = TRUE)

# Compute differences
myBiomodRangeSize <- bm_RangeSize(proj.current = CurrentProj, proj.future = FutureProj)

myBiomodRangeSize$Compt.By.Models
plot(myBiomodRangeSize$Diff.By.Pixel)

```

---

bm\_RunModelsLoop

*Loop to compute all single species distribution models*


---

## Description

This internal **biomod2** function allows the user to compute all single species distribution models (asked by the [BIOMOD\\_Modeling](#) function).

## Usage

```

bm_RunModelsLoop(
  bm.format,
  modeling.id,
  models,
  models.pa,
  calib.lines,
  bm.options,
  metric.eval,
  var.import,
  weights,
  scale.models = FALSE,
  nb.cpu = 1,

```

```

    seed.val = NULL,
    do.progress = TRUE
  )

  bm_RunModel(
    model,
    run.name,
    dir.name = ".",
    modeling.id = "",
    Data,
    bm.options,
    calib.lines.vec,
    eval.data = NULL,
    metric.eval = c("AUCroc", "TSS", "KAPPA"),
    var.import = 0,
    weights.vec,
    scale.models = FALSE,
    nb.cpu = 1,
    seed.val = NULL,
    do.progress = TRUE
  )

```

### Arguments

|             |                                                                                                                                                                                                                                                                                                                                                                 |
|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| bm.format   | a <a href="#">BIOMOD.formated.data</a> or <a href="#">BIOMOD.formated.data.PA</a> object returned by the <a href="#">BIOMOD_FormatingData</a> function                                                                                                                                                                                                          |
| modeling.id | a character corresponding to the name (ID) of the simulation set ( <i>a random number by default</i> )                                                                                                                                                                                                                                                          |
| models      | a vector containing model names to be computed, must be among ANN, CTA, DNN, FDA, GAM, GBM, GLM, MARS, MAXENT, MAXNET, RF, RFd, SRE, XGBOOST                                                                                                                                                                                                                    |
| models.pa   | ( <i>optional, default NULL</i> )<br>A list containing for each model a vector defining which pseudo-absence datasets are to be used, must be among <code>colnames(bm.format@PA.table)</code>                                                                                                                                                                   |
| calib.lines | a matrix containing calibration / validation lines for each pseudo-absence (or allData) x repetition (or allRun) combination that can be obtained with the <a href="#">bm_CrossValidation</a> function                                                                                                                                                          |
| bm.options  | a <a href="#">BIOMOD.models.options</a> object returned by the <a href="#">bm_ModelingOptions</a> function                                                                                                                                                                                                                                                      |
| metric.eval | a vector containing evaluation metric names to be used, must be among AUCroc, AUCprg, TSS, KAPPA, ACCURACY, BIAS, POD, FAR, POFD, SR, CSI, ETS, OR, ORSS, BOYCE, MPA ( <i>binary data</i> ), RMSE, MAE, MSE, Rsquared, Rsquared_aj, Max_error ( <i>abundance / count / relative data</i> ), Accuracy, Recall, Precision, F1 ( <i>multi-class/ordinal data</i> ) |
| var.import  | ( <i>optional, default NULL</i> )<br>An integer corresponding to the number of permutations to be done for each variable to estimate variable importance                                                                                                                                                                                                        |

|                 |                                                                                                                                                                           |
|-----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| weights         | a matrix containing observation weights for each pseudo-absence (or allData) dataset                                                                                      |
| scale.models    | (optional, default FALSE)<br>A logical value defining whether all models predictions should be scaled with a binomial GLM or not                                          |
| nb.cpu          | (optional, default 1)<br>An integer value corresponding to the number of computing resources to be used to parallelize the single models computation                      |
| seed.val        | (optional, default NULL)<br>An integer value corresponding to the new seed value to be set                                                                                |
| do.progress     | (optional, default TRUE)<br>A logical value defining whether the progress bar is to be rendered or not                                                                    |
| model           | a character corresponding to the model name to be computed, must be either ANN, CTA, DNN, FDA, GAM, GBM, GLM, MARS, MAXENT, MAXNET, RF, SRE, XGBOOST                      |
| run.name        | a character corresponding to the model to be run (sp.name + pa.id + run.id)                                                                                               |
| dir.name        | (optional, default .)<br>A character corresponding to the modeling folder                                                                                                 |
| Data            | a data.frame containing observations, coordinates and environmental variables that can be obtained with the get_species_data function                                     |
| calib.lines.vec | a vector containing calibration / validation lines for the concerned pseudo-absence (or allData) x repetition (or allRun) combination                                     |
| eval.data       | (optional, default NULL)<br>A data.frame containing validation observations, coordinates and environmental variables that can be obtained with the get_eval_data function |
| weights.vec     | a vector containing observation weights the concerned pseudo-absence (or allData) dataset                                                                                 |

### Value

A list containing for each model a list containing the following elements :

- model : the name of correctly computed model
- calib.failure : the name of incorrectly computed model
- pred : the prediction outputs for calibration data
- pred.eval : the prediction outputs for evaluation data
- evaluation : the evaluation outputs returned by the [bm\\_FindOptimStat](#) function
- var.import : the mean of variables importance returned by the [bm\\_VariablesImportance](#) function

### Author(s)

Damien Georges

**See Also**

[rpart](#), [prune](#), [gbm](#), [nnet](#), [earth](#), [fda](#), [mars](#), [maxnet](#), [randomForest](#), [xgboost](#), [bm\\_ModelingOptions](#), [BIOMOD\\_Modeling](#), [bm\\_MakeFormula](#), [bm\\_SampleFactorLevels](#), [bm\\_FindOptimStat](#), [bm\\_VariablesImportance](#)

Other Secondary functions: [bm\\_BinaryTransformation\(\)](#), [bm\\_CrossValidation\(\)](#), [bm\\_FindOptimStat\(\)](#), [bm\\_MakeFormula\(\)](#), [bm\\_ModelAnalysis\(\)](#), [bm\\_ModelingOptions\(\)](#), [bm\\_PlotEvalBoxplot\(\)](#), [bm\\_PlotEvalMean\(\)](#), [bm\\_PlotRangeSize\(\)](#), [bm\\_PlotResponseCurves\(\)](#), [bm\\_PlotVarImpBoxplot\(\)](#), [bm\\_PseudoAbsences\(\)](#), [bm\\_RangeSize\(\)](#), [bm\\_SRE\(\)](#), [bm\\_SampleBinaryVector\(\)](#), [bm\\_SampleFactorLevels\(\)](#), [bm\\_Tuning\(\)](#), [bm\\_VariablesImportance\(\)](#)

---

bm\_SampleBinaryVector    *Sample binary vector*

---

**Description**

This internal **biomod2** function allows the user to sample a binary vector keeping the same proportion of 0 and 1 as the initial vector.

**Usage**

```
bm_SampleBinaryVector(obs, ratio, as.logical = FALSE, seedval = NULL)
```

**Arguments**

|            |                                                                                                                                                                                                            |
|------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| obs        | a vector containing binary values (either 0 or 1)                                                                                                                                                          |
| ratio      | a numeric between 0 and 1 corresponding to the proportion of obs values to sample                                                                                                                          |
| as.logical | ( <i>optional, default</i> FALSE)<br>A logical value defining whether output should be returned as a vector of TRUE/FALSE values or integer values corresponding to the indices of obs elements to be kept |
| seedval    | ( <i>optional, default</i> NULL)<br>An integer value corresponding to the new seed value to be set                                                                                                         |

**Value**

A list containing the following elements :

- calibration : elements selected for calibration
- validation : elements selected for validation (complementary to the calibration set)

**Author(s)**

Damien Georges

**See Also**

Other Secondary functions: [bm\\_BinaryTransformation\(\)](#), [bm\\_CrossValidation\(\)](#), [bm\\_FindOptimStat\(\)](#), [bm\\_MakeFormula\(\)](#), [bm\\_ModelAnalysis\(\)](#), [bm\\_ModelingOptions\(\)](#), [bm\\_PlotEvalBoxplot\(\)](#), [bm\\_PlotEvalMean\(\)](#), [bm\\_PlotRangeSize\(\)](#), [bm\\_PlotResponseCurves\(\)](#), [bm\\_PlotVarImpBoxplot\(\)](#), [bm\\_PseudoAbsences\(\)](#), [bm\\_RangeSize\(\)](#), [bm\\_RunModelsLoop\(\)](#), [bm\\_SRE\(\)](#), [bm\\_SampleFactorLevels\(\)](#), [bm\\_Tuning\(\)](#), [bm\\_VariablesImportance\(\)](#)

**Examples**

```
## Generate a binary vector
vec.a <- sample(c(0, 1), 100, replace = TRUE)

## Generate calibration / validation datasets
bm_SampleBinaryVector(obs = vec.a, ratio = 0.7)
```

---

bm\_SampleFactorLevels *Sample all levels of a factorial variable*

---

**Description**

This internal **biomod2** function allows the user to sample all levels of all the factorial variables contained in a `data.frame` or [SpatRaster](#) object.

**Usage**

```
bm_SampleFactorLevels(expl.var, mask.out = NULL, mask.in = NULL)
```

**Arguments**

|                       |                                                                                                                                                                                                                                                                                                          |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>expl.var</code> | a <code>data.frame</code> or <a href="#">SpatRaster</a> object containing the explanatory variables (in columns or layers)                                                                                                                                                                               |
| <code>mask.out</code> | a <code>data.frame</code> or <a href="#">SpatRaster</a> object containing the area that has already been sampled ( <i>factor levels within this mask will not be sampled</i> )                                                                                                                           |
| <code>mask.in</code>  | a <code>data.frame</code> or <a href="#">SpatRaster</a> object containing areas where factor levels are to be sampled in priority. <i>Note that if after having explored these masks, some factor levels remain unsampled, they will be sampled in the reference input object <code>expl.var</code>.</i> |

**Details**

The `expl.var`, `mask.out` and `mask.in` parameters must be coherent in terms of dimensions :

- same number of rows for `data.frame` objects
- same resolution, projection system and number of cells for [SpatRaster](#) objects

If `mask.in` contains several columns (`data.frame`) or layers ([SpatRaster](#)), then their order matters : they will be considered successively to sample missing factor levels.

- Values in `data.frame` will be understood as :
  - FALSE : out of mask
  - TRUE : in mask
- Values in [SpatRaster](#) will be understood as :
  - NA : out of mask
  - not NA : in mask

### Value

A vector of numeric values corresponding to either row (`data.frame`) or cell ([SpatRaster](#)) numbers, each referring to a single level of a single factorial variable.

In case no factorial variable is found in the input object, NULL is returned.

### Author(s)

Damien Georges

### See Also

[bm\\_PseudoAbsences](#), [bm\\_CrossValidation](#)

Other Secondary functions: [bm\\_BinaryTransformation\(\)](#), [bm\\_CrossValidation\(\)](#), [bm\\_FindOptimStat\(\)](#), [bm\\_MakeFormula\(\)](#), [bm\\_ModelAnalysis\(\)](#), [bm\\_ModelingOptions\(\)](#), [bm\\_PlotEvalBoxplot\(\)](#), [bm\\_PlotEvalMean\(\)](#), [bm\\_PlotRangeSize\(\)](#), [bm\\_PlotResponseCurves\(\)](#), [bm\\_PlotVarImpBoxplot\(\)](#), [bm\\_PseudoAbsences\(\)](#), [bm\\_RangeSize\(\)](#), [bm\\_RunModelsLoop\(\)](#), [bm\\_SRE\(\)](#), [bm\\_SampleBinaryVector\(\)](#), [bm\\_Tuning\(\)](#), [bm\\_VariablesImportance\(\)](#)

### Examples

```
library(terra)

## Create raster data
ras.1 <- ras.2 <- mask.out <- rast(nrows = 10, ncols = 10)
ras.1[] <- as.factor(rep(c(1, 2, 3, 4, 5), each = 20))
ras.1 <- as.factor(ras.1)
ras.2[] <- rnorm(100)
stk <- c(ras.1, ras.2)
names(stk) <- c("varFact", "varNorm")

## define a mask for already sampled points
mask.out[1:40] <- 1

## define a list of masks where we want to sample in priority
mask.in <- list(ras.1, ras.1)
mask.in[[1]][1:80] <- NA ## only level 5 should be sampled in this mask
```

```
mask.in[[1]][21:80] <- NA ## only levels 1 and 5 should be sampled in this mask

## Sample all factor levels
samp1 <- bm_SampleFactorLevels(expl.var = stk, mask.out = mask.out)
samp2 <- bm_SampleFactorLevels(expl.var = stk, mask.in = mask.in)
samp3 <- bm_SampleFactorLevels(expl.var = stk, mask.out = mask.out, mask.in = mask.in)
```

bm\_SRE

*Surface Range Envelope*

## Description

This internal **biomod2** function allows the user to run a rectilinear surface range envelop (SRE) (equivalent to **BIOCLIM**) using the extreme percentiles (as recommended by Nix or Busby, see References and Details).

## Usage

```
bm_SRE(
  resp.var = NULL,
  expl.var = NULL,
  new.env = NULL,
  quant = 0.025,
  do.extrem = FALSE
)
```

## Arguments

|          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| resp.var | a vector, a <a href="#">SpatVector</a> without associated data ( <i>if presence-only</i> ), or a <a href="#">SpatVector</a> object containing binary data (0 : absence, 1 : presence, NA : indeterminate) for a single species that will be used to build the species distribution model(s)<br><i>Note that old format from <b>sp</b> are still supported such as SpatialPoints (if presence-only) or SpatialPointsDataFrame object containing binary data.</i> |
| expl.var | a matrix, data.frame, <a href="#">SpatVector</a> or <a href="#">SpatRaster</a> object containing the explanatory variables (in columns or layers) that will be used to build the SRE model<br><i>Note that old format from <b>raster</b> and <b>sp</b> are still supported such as RasterStack and SpatialPointsDataFrame objects.</i>                                                                                                                          |
| new.env  | a matrix, data.frame, <a href="#">SpatVector</a> or <a href="#">SpatRaster</a> object containing the explanatory variables (in columns or layers) that will be used to predict the SRE model<br><i>Note that old format from <b>raster</b> and <b>sp</b> are still supported such as RasterStack and SpatialPointsDataFrame objects.</i>                                                                                                                        |
| quant    | a numeric between 0 and 0.5 defining the half-quantile corresponding to the most extreme value for each variable not to be taken into account for determining the tolerance boundaries of the considered species (see Details)                                                                                                                                                                                                                                  |

do.extrem      (optional, default FALSE)  
 A logical value defining whether a matrix containing extreme conditions supported should be returned or not

## Details

*Please refer to References to get more information about surface range envelop models.*

This method is highly influenced by the extremes of the data input. Whereas a linear model can discriminate the extreme values from the main tendency, the SRE considers them as important as any other data point leading to changes in predictions.

*The more (non-collinear) variables, the more restrictive the model will be.*

Predictions are returned as binary (0 or 1) values, a site being either potentially suitable for all the variables, or out of bounds for at least one variable and therefore considered unsuitable.

quant determines the threshold from which the data will be taken into account for calibration. The default value of 0.05 induces that the 5% most extreme values will be avoided for each variable on each side of its distribution along the gradient, meaning that a total of 10% of the data will not be considered.

## Value

A vector or a [SpatRaster](#) object, containing binary (0 or 1) values.

## Author(s)

Wilfried Thuiller, Bruno Lafourcade, Damien Georges

## References

- Nix HA (1986). *A biogeographic analysis of Australian elapid snakes*. In: Atlas of Elapid Snakes of Australia. (Ed.) R. Longmore, pp. 4-15. Australian Flora and Fauna Series Number 7. Australian Government Publishing Service: Canberra.
- Busby J (1991). *BIOCLIM - a bioclimate analysis and prediction system*. Plant protection quarterly, 6, 8-9.

## See Also

[bm\\_PseudoAbsences](#), [BIOMOD\\_FormatingData](#), [bm\\_ModelingOptions](#), [bm\\_Tuning](#), [bm\\_RunModelsLoop](#), [BIOMOD\\_Modeling](#),

Other Secondary functions: [bm\\_BinaryTransformation\(\)](#), [bm\\_CrossValidation\(\)](#), [bm\\_FindOptimStat\(\)](#), [bm\\_MakeFormula\(\)](#), [bm\\_ModelAnalysis\(\)](#), [bm\\_ModelingOptions\(\)](#), [bm\\_PlotEvalBoxplot\(\)](#), [bm\\_PlotEvalMean\(\)](#), [bm\\_PlotRangeSize\(\)](#), [bm\\_PlotResponseCurves\(\)](#), [bm\\_PlotVarImpBoxplot\(\)](#), [bm\\_PseudoAbsences\(\)](#),

```
bm_RangeSize(),bm_RunModelsLoop(),bm_SampleBinaryVector(),bm_SampleFactorLevels(),
bm_Tuning(),bm_VariablesImportance()
```

## Examples

```
library(terra)

## Load real data
data(DataSpecies)
myResp.r <- as.numeric(DataSpecies[, 'GuloGulo'])

data(bioclim_current)
myExpl.r <- rast(bioclim_current)

myRespXY <- DataSpecies[which(myResp.r == 1), c('X_WGS84', 'Y_WGS84')]
myResp.v <- classify(subset(myExpl.r, 1),
                    matrix(c(-Inf, Inf, 0), ncol = 3, byrow = TRUE))
myResp.v[cellFromXY(myResp.v, myRespXY)] <- 1

## Compute SRE for several quantile values
sre.100 <- bm_SRE(resp.var = myResp.v,
                  expl.var = myExpl.r,
                  new.env = myExpl.r,
                  quant = 0)
sre.095 <- bm_SRE(resp.var = myResp.v,
                  expl.var = myExpl.r,
                  new.env = myExpl.r,
                  quant = 0.025)
sre.090 <- bm_SRE(resp.var = myResp.v,
                  expl.var = myExpl.r,
                  new.env = myExpl.r,
                  quant = 0.05)

## Visualize results
res <- c(myResp.v, sre.100, sre.095, sre.090)
names(res) <- c("Original distribution", "Full data calibration"
               , "Over 95 percent", "Over 90 percent")
plot(res)
```

---

bm\_Tuning

*Tune models parameters*


---

## Description

This internal **biomod2** function allows to tune single model parameters and select more efficient ones based on an evaluation metric.

**Usage**

```
bm_Tuning(
  model,
  tuning.fun,
  do.formula = FALSE,
  do.stepAIC = FALSE,
  bm.options,
  bm.format,
  calib.lines = NULL,
  metric.eval = "TSS",
  metric.AIC = "AIC",
  weights = NULL,
  ctrl.train = NULL,
  params.train = list(ANN.size = c(2, 4, 6, 8), ANN.decay = c(0.01, 0.05, 0.1), ANN.bag =
    FALSE, DNN.hidden = list(depth = 3, width = 100), DNN.bias = TRUE, DNN.lambda =
    0.001, DNN.alpha = 1, DNN.lr = c(1e-04, 0.1), DNN.batchsize = 100, DNN.epochs = 150,
    FDA.degree = 1:2, FDA.nprune = 2:25, GAM.select = c(TRUE, FALSE), GAM.method =
    c("GCV.Cp", "GACV.Cp", "REML", "P-REML", "ML", "P-ML"), GAM.span = c(0.3, 0.5, 0.7),
    GAM.degree = 1, GBM.n.trees = c(500, 1000, 2500), GBM.interaction.depth = seq(2, 8,
    by = 3), GBM.shrinkage = c(0.001,
    0.01, 0.1), GBM.n.minobsinnode = 10,
    MARS.degree = 1:2, MARS.nprune = 2:max(21, 2 * ncol(bm.format@data.env.var) + 1),
    MAXENT.algorithm = "maxnet", MAXENT.parallel = TRUE, MAXENT.tune.args = list(rm =
    seq(0.5, 1, 0.5), fc = c("L")), MAXENT.partitions = "randomkfold",
    MAXENT.partition.settings = list(orientation = "lat_lon", aggregation.factor = 2,
    kfolds = 10), MAXENT.user.grp = NULL, RF.mtry = 1:min(10,
    ncol(bm.format@data.env.var)), RFd.mtry = 1:min(10, ncol(bm.format@data.env.var)),
    SRE.quant = c(0,
    0.0125, 0.025, 0.05, 0.1), XGBOOST.nrounds = 50,
    XGBOOST.max_depth = 1, XGBOOST.eta = c(0.3, 0.4), XGBOOST.gamma = 0,
    XGBOOST.colsample_bytree = c(0.6, 0.8), XGBOOST.min_child_weight = 1,
    XGBOOST.subsample = 0.5)
)
```

**Arguments**

|            |                                                                                                                                                                          |
|------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| model      | a character corresponding to the algorithm to be tuned, must be either ANN, CTA, DNN, FDA, GAM, GBM, GLM, MARS, MAXENT, MAXNET, RF, RFd, SRE, XGBOOST                    |
| tuning.fun | a character corresponding to the model function name to be called through <a href="#">train</a> function for tuning parameters (see <a href="#">ModelsTable</a> dataset) |
| do.formula | ( <i>optional, default</i> FALSE)<br>A logical value defining whether formula is to be optimized or not                                                                  |
| do.stepAIC | ( <i>optional, default</i> FALSE)<br>A logical value defining whether variables selection is to be performed for GLM and GAM models or not                               |
| bm.options | a <a href="#">BIOMOD.options.default</a> or <a href="#">BIOMOD.options.dataset</a> object returned by the <a href="#">bm_ModelingOptions</a> function                    |

|              |                                                                                                                                                                                                                          |
|--------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| bm.format    | a <a href="#">BIOMOD.formated.data</a> or <a href="#">BIOMOD.formated.data.PA</a> object returned by the <a href="#">BIOMOD_FormatingData</a> function                                                                   |
| calib.lines  | (optional, default NULL)<br>A data.frame object returned by <a href="#">get_calib_lines</a> or <a href="#">bm_CrossValidation</a> functions                                                                              |
| metric.eval  | a character corresponding to the evaluation metric to be used, must be either AUC, Kappa or TSS for SRE only ; auc.val.avg, auc.diff.avg, or.mtp.avg, or.10p.avg, AICc for MAXENT only ; ROC or TSS for all other models |
| metric.AIC   | a character corresponding to the AIC metric to be used, must be either AIC or BIC                                                                                                                                        |
| weights      | (optional, default NULL)<br>A vector of numeric values corresponding to observation weights (one per observation, see Details)                                                                                           |
| ctrl.train   | (optional, default NULL)<br>A <a href="#">trainControl</a> object                                                                                                                                                        |
| params.train | a list containing values of model parameters to be tested (see Details)                                                                                                                                                  |

## Details

### Concerning ctrl.train parameter :

Set by default to :

```
ctrl.train <- caret::trainControl(method = "repeatedcv", repeats = 3, number = 10,
summaryFunction = caret::twoClassSummary,
classProbs = TRUE, returnData = FALSE)
```

### Concerning params.train parameter :

All elements of the list must have names matching model.parameter\_name format, parameter\_name being one of the parameter of the tuning.fun function called by caret package and that can be found through the [getModelInfo](#) function.

Currently, the available parameters to be tuned are the following :

**ANN** size, decay, bag

**CTA** maxdepth

**DNN** hidden , bias, lambda, alpha, lr, batchsize, 150

**FDA** degree, nprune

**GAM.gam** span, degree

**GAM.mgcv** select, method

**GBM** n.trees, interaction.depth, shrinkage, n.minobsinnode

**MARS** degree, nprune

**MAXENT** algorithm,tune.args, parallel, partitions, partition.settings, user.grp

**RF** mtry

**RFd** mtry

**SRE** quant

**XGBOOST** nrounds, max\_depth, eta, gamma, colsampl\_bytree, min\_child\_weight, subsample

The `expand.grid` function is used to build a matrix containing all combinations of parameters to be tested.

## Value

A `BIOMOD.models.options` object (see `bm_ModelingOptions`) with optimized parameters

### Note

- No tuning for GLM and MAXNET
- MAXENT is tuned through `ENMevaluate` function which is calling either :
  - maxnet (by defining `MAXENT.algorithm = 'maxnet'`) (*default*)
  - Java version of Maxent defined in **dismo** package (by defining `MAXENT.algorithm = 'maxent.jar'`)
- DNN is tuned through `tune` function. The values include in `params.train` are the lower or upper range which hyperparameters are sampled. If there is only one value, the hyperparameter is fixed by biomod2 (including the width and depth of hidden parameters.)
- SRE is tuned through `bm_SRE` function
- All other models are tuned through `train` function
- No optimization of formula for DNN, MAXENT, MAXNET, SRE and XGBOOST
- No interaction included in formula for CTA
- Variables selection only for GAM, gam and GLM

**Author(s)**

Frank Breiner, Maya Guéguen, Hélène Blancheteau

## See Also

```
trainControl, train, ENMevaluate, ModelsTable, BIOMOD.models.options, bm_ModelingOptions,
BIOMOD_Modeling
```

Other Secondary functions: `bm_BinaryTransformation()`, `bm_CrossValidation()`, `bm_FindOptimStat()`, `bm_MakeFormula()`, `bm_ModelAnalysis()`, `bm_ModelingOptions()`, `bm_PlotEvalBoxplot()`, `bm_PlotEvalMean()`, `bm_PlotRangeSize()`, `bm_PlotResponseCurves()`, `bm_PlotVarImpBoxplot()`, `bm_PseudoAbsences()`, `bm_RangeSize()`, `bm_RunModelsLoop()`, `bm_SRE()`, `bm_SampleBinaryVector()`, `bm_SampleFactorLevels()`, `bm_VariablesImportance()`



```
## Not run:
# tune parameters for GAM (from mgcv package) model
tuned.gam <- bm_Tuning(model = 'GAM',
                      tuning.fun = 'gam', ## see in ModelsTable
                      do.formula = TRUE,
                      do.stepAIC = TRUE,
                      bm.options = opt.d@options$GAM.binary.mgcv.gam,
                      bm.format = myBiomodData)

tuned.gam

## End(Not run)
```

---

bm\_VariablesImportance

*Variables' importance calculation*

---

## Description

This internal **biomod2** function allows the user to compute a variable importance value for each variable involved in the given model.

## Usage

```
bm_VariablesImportance(
  bm.model,
  expl.var,
  variables = NULL,
  method = "full_rand",
  nb.rep = 1,
  seed.val = NULL,
  do.progress = TRUE,
  temp.workdir = NULL
)
```

## Arguments

|           |                                                                                                                                                                          |
|-----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| bm.model  | a biomod2_model object (or nnet, rpart, fda, gam, glm, lm, gbm, mars, randomForest, xgb.Booster) that can be obtained with the <a href="#">get_formal_model</a> function |
| expl.var  | a data.frame containing the explanatory variables that will be used to compute the variables importance                                                                  |
| variables | (optional, default NULL)<br>A vector containing the names of the explanatory variables that will be considered                                                           |

|              |                                                                                                                                                |
|--------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| method       | a character corresponding to the randomization method to be used, must be <code>full_rand</code> ( <i>only method available so far</i> )       |
| nb.rep       | an integer corresponding to the number of permutations to be done for each variable                                                            |
| seed.val     | ( <i>optional, default NULL</i> )<br>An integer value corresponding to the new seed value to be set                                            |
| do.progress  | ( <i>optional, default TRUE</i> )<br>A logical value defining whether the progress bar is to be rendered or not                                |
| temp.workdir | ( <i>optional, default NULL</i> )<br>A character value corresponding to the folder name containing temporal prediction files when using MAXENT |

### Details

For each variable to be evaluated :

1. shuffle the original variable
2. compute model prediction with shuffled variable
3. calculate Pearson's correlation between reference and shuffled predictions
4. return score as  $1 - \text{cor}$

The highest the value, the less reference and shuffled predictions are correlated, and the more influence the variable has on the model. A value of 0 assumes no influence of the variable on the model.

*Note that this calculation does not account for variables' interactions.*

The same principle is used in [randomForest](#).

### Value

A 3 columns data.frame containing variable's importance scores for each permutation run :

- `expl.var` : the considered explanatory variable (the one permuted)
- `rand` : the ID of the permutation run
- `var.imp` : the variable's importance score

### Author(s)

Damien Georges

### See Also

[randomForest](#), [bm\\_RunModelsLoop](#), [BIOMOD\\_Modeling](#), [BIOMOD\\_EnsembleModeling](#), [bm\\_PlotVarImpBoxplot](#), [get\\_variables\\_importance](#)

Other Secondary functions: [bm\\_BinaryTransformation\(\)](#), [bm\\_CrossValidation\(\)](#), [bm\\_FindOptimStat\(\)](#), [bm\\_MakeFormula\(\)](#), [bm\\_ModelAnalysis\(\)](#), [bm\\_ModelingOptions\(\)](#), [bm\\_PlotEvalBoxplot\(\)](#), [bm\\_PlotEvalMean\(\)](#), [bm\\_PlotRangeSize\(\)](#), [bm\\_PlotResponseCurves\(\)](#), [bm\\_PlotVarImpBoxplot\(\)](#), [bm\\_PseudoAbsences\(\)](#), [bm\\_RangeSize\(\)](#), [bm\\_RunModelsLoop\(\)](#), [bm\\_SRE\(\)](#), [bm\\_SampleBinaryVector\(\)](#), [bm\\_SampleFactorLevels\(\)](#), [bm\\_Tuning\(\)](#)

## Examples

```
## Create simple simulated data
myResp.s <- sample(c(0, 1), 20, replace = TRUE)
myExpl.s <- data.frame(var1 = sample(c(0, 1), 100, replace = TRUE),
                      var2 = rnorm(100),
                      var3 = 1:100)

## Compute variables importance
mod <- glm(var1 ~ var2 + var3, data = myExpl.s)
bm_VariablesImportance(bm.model = mod,
                      expl.var = myExpl.s[, c('var2', 'var3')],
                      method = "full_rand",
                      nb.rep = 3)
```

---

DataSpecies

*Presence-Absence data to build test SDM*


---

## Description

A dataset covering all the continent with presence/absence data for 6 mammal species. Presence/absence were derived from range maps downloaded at [IUCN](#).

## Usage

```
DataSpecies
```

## Format

A data.frame object with 2488 rows and 10 variables:

**X\_WGS84** Longitude

**Y\_WGS84** Latitude

**ConnochaetesGnou** Presence (1) or Absence (0) for black wildebeest

**GuloGulo** Presence (1) or Absence (0) for wolverine

**PantheraOnca** Presence (1) or Absence (0) for jaguar

**PteropusGiganteus** Presence (1) or Absence (0) for Indian flying fox

**TenrecEcaudatus** Presence (1) or Absence (0) for tailless tenrec

**VulpesVulpes** Presence (1) or Absence (0) for red fox

DataSTOC

*Abundance to build test SDM***Description**

A dataset covering France with abundance data for 20 bird species. Data comes from the French Breeding Bird Survey (STOC program) of Vigie-Nature (Fontaine et al. 2020). The original dataset contains 2,948 sites in which bird species have been observed from 2001 to 2024. Original raw data is not provided here, but might be made available on request by contacting Benoît Fontaine (benoit.fontaine [at] mnhn.fr).

**Usage**

DataSTOC

**Format**

A data.frame object with 2006 rows and 30 columns (10 variables and 20 species):

**site** Observation site ID

**period** yearly average headcounts have been computed over 2 times periods: 2006-2011 and 2012-2017

**X\_WGS84** Longitude

**Y\_WGS84** Latitude

**temp** annual mean temperature (CHELSA)

**precip** annual mean precipitation (CHELSA)

**cover\_agri** percentage of agricultural habitat cover around each point (European Union's Copernicus Land Monitoring Service information)

**cover\_water** percentage of water habitat cover around each point (European Union's Copernicus Land Monitoring Service information)

**cover\_wet** percentage of wetland habitat cover around each point (European Union's Copernicus Land Monitoring Service information)

**sdiv\_hab** Shannon habitat diversity (CORINE)

**Alauda.arvensis** abundance data for Eurasian skylark

**Cettia.cetti** abundance data for Cetti's warbler

**Coccothraustes.coccothraustes** abundance data for hawfinch

**Cuculus.canorus** abundance data for common cuckoo

**Emberiza.calandra** abundance data for corn bunting

**Emberiza.citrinella** abundance data for yellowhammer

**Erithacus.rubecula** abundance data for European robin

**Fulica.atra** abundance data for Eurasian coot

**Luscinia.megarhynchos** abundance data for common nightingale

**Passer.domesticus** abundance data for house sparrow  
**Perdix.perdix** abundance data for grey partridge  
**Periparus.ater** abundance data for coal tit  
**Phylloscopus.bonelli** abundance data for western Bonelli's warbler  
**Phylloscopus.trochilus** abundance data for willow warbler  
**Regulus.regulus** abundance data for goldcrest  
**Serinus.serinus** abundance data for European serin  
**Sitta.europaea** abundance data for Eurasian nuthatch  
**Streptopelia.decaocto** abundance data for Eurasian collared dove  
**Sylvia.melanocephala** abundance data for Sardinian warbler  
**Turdus.philomelos** abundance data for song thrush

## References

- **STOC EPS** - Vigie-Nature (2025). *French Breeding Bird Monitoring Scheme*. Muséum National d'Histoire Naturelle (MNHN) - Office Français pour la Biodiversité (OFB) - Ligue pour la Protection des Oiseaux (LPO).
- Fontaine B, Moussy C, Chiffard Carricaburu J, Dupuis J, Corolleur E, Schmaltz L, Lorrillière R, Loïs G, Gaudard C (2020). *Suivi des oiseaux communs en France 1989-2019 : 30 ans de suivis participatifs*. MNHN - Centre d'Ecologie et des Sciences de la Conservation, LPO BirdLife France - Service Connaissance, Ministère de la Transition écologique et solidaire. 46 pp.
- Brun P, Zimmermann NE, Hari C, Pellissier L, Karger DN (2022). *CHELSEA-BIOCLIM+ A novel set of global climate-related predictors at kilometre-resolution*. EnviDat. doi:10.16904/envi.dat.332
- CORINE Land Cover 2018 (raster 100 m), Europe, 6-yearly - **version 2020\_20u1**, May 2020. European Environment Agency. doi:10.2909/960998c118704e8280516485205ebbac

---

getters.bm

---

*Functions to extract informations from `biomod2_model` objects*


---

## Description

These functions allow the user to easily retrieve single models (formal or scaled) from `biomod2_model` objects from the modeling step.

## Usage

```
## S4 method for signature 'biomod2_model'
get_formal_model(object)

## S4 method for signature 'biomod2_model'
get_scaling_model(object)
```

**Arguments**

object                    a `biomod2_model` object

**Value**

`get_formal_model` an object from the `model` slot of a `biomod2_model` object

`get_scaling_model` an object from the `scaling_model` slot of a `biomod2_model` object

**Author(s)**

Damien Georges

**See Also**

`biomod2_model`

Other Toolbox functions: `getters.out`, `load_stored_object()`, `predict2.bm`, `predict2.em`, `setters`

---

|                          |                                                                                                                                                                     |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>getters.out</code> | <i>Functions to extract informations from <code>BIOMOD.models.out</code>, <code>BIOMOD.projection.out</code> or <code>BIOMOD.ensemble.models.out</code> objects</i> |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|

---

**Description**

These functions allow the user to easily retrieve informations stored in the different **biomod2** objects from the different modeling steps, such as modeling options and formatted data, models used or not, predictions, evaluations, variables importance.

**Usage**

```
## S4 method for signature 'BIOMOD.formated.data'
get_species_data(obj)

## S4 method for signature 'BIOMOD.formated.data.PA'
get_species_data(obj)

## S4 method for signature 'BIOMOD.formated.data'
get_eval_data(obj)

## S4 method for signature 'BIOMOD.models.out'
get_options(obj)

## S4 method for signature 'BIOMOD.models.out'
get_calib_lines(obj, as.data.frame = FALSE, PA = NULL, run = NULL)

## S4 method for signature 'BIOMOD.models.out'
```

```
get_formal_data(obj, subinfo = NULL)

## S4 method for signature 'BIOMOD.models.out'
get_predictions(
  obj,
  evaluation = FALSE,
  full.name = NULL,
  PA = NULL,
  run = NULL,
  algo = NULL,
  model.as.col = FALSE
)

## S4 method for signature 'BIOMOD.models.out'
get_built_models(obj, full.name = NULL, PA = NULL, run = NULL, algo = NULL)

## S4 method for signature 'BIOMOD.models.out'
get_evaluations(
  obj,
  full.name = NULL,
  PA = NULL,
  run = NULL,
  algo = NULL,
  metric.eval = NULL
)

## S4 method for signature 'BIOMOD.models.out'
get_variables_importance(
  obj,
  full.name = NULL,
  PA = NULL,
  run = NULL,
  algo = NULL,
  expl.var = NULL
)

## S4 method for signature 'BIOMOD.projection.out'
get_projected_models(
  obj,
  full.name = NULL,
  PA = NULL,
  run = NULL,
  algo = NULL,
  merged.by.algo = NULL,
  merged.by.run = NULL,
  merged.by.PA = NULL,
  filtered.by = NULL
)
```

```
## S4 method for signature 'BIOMOD.projection.out'
free(obj)

## S4 method for signature 'BIOMOD.projection.out'
get_predictions(
  obj,
  metric.binary = NULL,
  metric.filter = NULL,
  full.name = NULL,
  PA = NULL,
  run = NULL,
  algo = NULL,
  merged.by.algo = NULL,
  merged.by.run = NULL,
  merged.by.PA = NULL,
  filtered.by = NULL,
  model.as.col = FALSE,
  ...
)

## S4 method for signature 'BIOMOD.ensemble.models.out'
get_formal_data(obj, subinfo = NULL)

## S4 method for signature 'BIOMOD.ensemble.models.out'
get_built_models(
  obj,
  full.name = NULL,
  merged.by.algo = NULL,
  merged.by.run = NULL,
  merged.by.PA = NULL,
  filtered.by = NULL,
  algo = NULL
)

## S4 method for signature 'BIOMOD.ensemble.models.out'
get_kept_models(obj)

## S4 method for signature 'BIOMOD.ensemble.models.out'
get_predictions(
  obj,
  evaluation = FALSE,
  full.name = NULL,
  merged.by.algo = NULL,
  merged.by.run = NULL,
  merged.by.PA = NULL,
  filtered.by = NULL,
  algo = NULL,
```

```

    model.as.col = FALSE
  )

  ## S4 method for signature 'BIOMOD.ensemble.models.out'
  get_evaluations(
    obj,
    full.name = NULL,
    merged.by.algo = NULL,
    merged.by.run = NULL,
    merged.by.PA = NULL,
    filtered.by = NULL,
    algo = NULL,
    metric.eval = NULL
  )

  ## S4 method for signature 'BIOMOD.ensemble.models.out'
  get_variables_importance(
    obj,
    full.name = NULL,
    merged.by.algo = NULL,
    merged.by.run = NULL,
    merged.by.PA = NULL,
    filtered.by = NULL,
    algo = NULL,
    expl.var = NULL
  )

```

## Arguments

|               |                                                                                                                                                                                                                   |
|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| obj           | a <a href="#">BIOMOD.formated.data</a> , <a href="#">BIOMOD.formated.data.PA</a> , <a href="#">BIOMOD.models.out</a> , <a href="#">BIOMOD.projection.out</a> or <a href="#">BIOMOD.ensemble.models.out</a> object |
| as.data.frame | a logical defining whether output should be returned as data.frame or array object                                                                                                                                |
| PA            | (optional, default NULL)<br>A vector containing pseudo-absence set to be loaded, must be among PA1, PA2, ..., allData                                                                                             |
| run           | (optional, default NULL)<br>A vector containing repetition set to be loaded, must be among RUN1, RUN2, ..., allRun                                                                                                |
| subinfo       | a character corresponding to the information to be extracted, must be among NULL, expl.var.names, resp.var, expl.var, MinMax, eval.resp.var, eval.expl.var (see Details)                                          |
| evaluation    | a logical defining whether evaluation data should be used or not                                                                                                                                                  |
| full.name     | (optional, default NULL)<br>A vector containing model names to be kept, must be either all or a sub-selection of model names that can be obtained with the <a href="#">get_built_models</a> function              |

|                             |                                                                                                                                                                                                                                                                                                                                                                                                      |
|-----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>algo</code>           | <i>(optional, default NULL)</i><br>A character containing algorithm to be loaded, must be either ANN, CTA, DNN, FDA, GAM, GBM, GLM, MARS, MAXENT, MAXNET, RF, SRE, XGBOOST                                                                                                                                                                                                                           |
| <code>model.as.col</code>   | <i>(optional, default FALSE)</i><br>A boolean given to <a href="#">get_predictions</a> . If TRUE prediction are returned as a wide data.frame with each column containing predictions for a single model and corresponding to the old output given by <b>biomod2</b> in version < 4.2-2. If FALSE predictions are returned as a long data.frame with many additional informations readily available. |
| <code>metric.eval</code>    | <i>(optional, default NULL)</i><br>A vector containing evaluation metric to be kept, must be among POD, FAR, POFD, SR, ACCURACY, BIAS, AUCroc, AUCprg, TSS, KAPPA, OR, ORSS, CSI, ETS, BOYCE, MPA                                                                                                                                                                                                    |
| <code>expl.var</code>       | <i>(optional, default NULL)</i><br>A vector containing explanatory variables to be kept, that can be obtained with the <a href="#">get_formal_data</a> (obj, subinfo = 'expl.var.names') function                                                                                                                                                                                                    |
| <code>merged.by.algo</code> | <i>(optional, default NULL)</i><br>A character containing merged algorithm to be loaded, must be among ANN, CTA, DNN, FDA, GAM, GBM, GLM, MARS, MAXENT, MAXNET, RF, SRE, XGBOOST, mergedAlgo                                                                                                                                                                                                         |
| <code>merged.by.run</code>  | <i>(optional, default NULL)</i><br>A vector containing merged repetition set to be loaded, must be among RUN1, RUN2, ..., mergedRun                                                                                                                                                                                                                                                                  |
| <code>merged.by.PA</code>   | <i>(optional, default NULL)</i><br>A vector containing merged pseudo-absence set to be loaded, must be among PA1, PA2, ..., mergedData                                                                                                                                                                                                                                                               |
| <code>filtered.by</code>    | <i>(optional, default NULL)</i><br>A vector containing evaluation metric selected to filter single models to build the ensemble models, must be among POD, FAR, POFD, SR, ACCURACY, BIAS, AUCroc, AUCprg, TSS, KAPPA, OR, ORSS, CSI, ETS, BOYCE, MPA                                                                                                                                                 |
| <code>metric.binary</code>  | <i>(optional, default NULL)</i><br>A vector containing evaluation metric selected to transform predictions into binary values, must be among POD, FAR, POFD, SR, ACCURACY, BIAS, AUCroc, AUCprg, TSS, KAPPA, OR, ORSS, CSI, ETS, BOYCE, MPA                                                                                                                                                          |
| <code>metric.filter</code>  | <i>(optional, default NULL)</i><br>A vector containing evaluation metric to filter predictions, must be among POD, FAR, POFD, SR, ACCURACY, BIAS, AUCroc, AUCprg, TSS, KAPPA, OR, ORSS, CSI, ETS, BOYCE, MPA                                                                                                                                                                                         |
| <code>...</code>            | <i>(optional, one or several of the following arguments depending on the selected function)</i>                                                                                                                                                                                                                                                                                                      |

## Value

`get_species_data` a data.frame combining data.species, coord, data.env.var (and PA.table) slots of [BIOMOD.formated.data](#) (or [BIOMOD.formated.data.PA](#)) object

`get_eval_data` a data.frame combining eval.data.species, eval.coord, eval.data.env.var slots of [BIOMOD.formated.data](#) or [BIOMOD.formated.data.PA](#) object

`get_options` a `BIOMOD.stored.options-class` object from the `models.options` slot of a `BIOMOD.models.out-class` object

`get_calib_lines` a `BIOMOD.stored.data.frame-class` object from the `calib.lines` slot of a `BIOMOD.models.out` object

`get_projected_models` a vector from the `models.projected` slot of a `BIOMOD.projection.out` object

`get_predictions` a `BIOMOD.stored.data` object from the `proj.out` slot of a `BIOMOD.models.out`, `BIOMOD.projection.out` or `BIOMOD.ensemble.models.out` object

`get_kept_models` a vector containing names of the kept models of a `BIOMOD.ensemble.models.out` object

`get_formal_data` depending on the `subinfo` parameter :

- `NULL` a `BIOMOD.stored.formated.data-class` (or `BIOMOD.stored.models.out-class`) object from the `formated.input.data` (or `models.out`) slot of a `BIOMOD.models.out` (or `BIOMOD.ensemble.models.out`) object
- `expl.var.names` a vector from the `expl.var.names` slot of a `BIOMOD.models.out` or `BIOMOD.ensemble.models.out` object
- `resp.var` a vector from the `data.species` slot of the `formated.input.data` slot of a `BIOMOD.models.out` or `BIOMOD.ensemble.models.out` object
- `expl.var` a `data.frame` from the `data.env.var` slot of the `formated.input.data` slot of a `BIOMOD.models.out` or `BIOMOD.ensemble.models.out` object
- `MinMax` a list of minimum and maximum values (or levels if factorial) of variable contained in the `data.env.var` slot of the `formated.input.data` slot of a `BIOMOD.models.out` or `BIOMOD.ensemble.models.out` object
- `eval.resp.var` a vector from the `eval.data.species` slot of the `formated.input.data` slot of a `BIOMOD.models.out` or `BIOMOD.ensemble.models.out` object
- `eval.expl.var` a `data.frame` from the `eval.data.env.var` slot of the `formated.input.data` slot of a `BIOMOD.models.out` or `BIOMOD.ensemble.models.out` object

`get_built_models` a vector from the `models.computed` slot (or `em.computed`) of a `BIOMOD.models.out` (or `BIOMOD.ensemble.models.out`) object

`get_evaluations` a `data.frame` from the `models.evaluation` slot (or `model_evaluation` of each model in `em.computed`) of a `BIOMOD.models.out` (or `BIOMOD.ensemble.models.out`) object. Contains evaluation metric for different models and dataset. Evaluation metric are calculated on the calibrating data (column calibration), on the cross-validation data (column validation) or on the evaluation data (column evaluation).  
*For cross-validation data, see `CV[...] parameters` in `BIOMOD_Modeling` function ; for evaluation data, see `eval[...] parameters` in `BIOMOD_FormatingData`.*

`get_variables_importance` a `BIOMOD.stored.data.frame-class` from the `variables.importance` slot (or `model_variables_importance` of each model in `em.models`) of a `BIOMOD.models.out` (or `BIOMOD.ensemble.models.out`) object

**Author(s)**

Damien Georges

**See Also**

[BIOMOD.models.out](#), [BIOMOD.projection.out](#), [BIOMOD.ensemble.models.out](#)

Other Toolbox functions: [getters.bm](#), [load\\_stored\\_object\(\)](#), [predict2.bm](#), [predict2.em](#), [setters](#)

---

|                    |                                                                     |
|--------------------|---------------------------------------------------------------------|
| load_stored_object | <i>Functions to load <a href="#">BIOMOD.stored.data</a> objects</i> |
|--------------------|---------------------------------------------------------------------|

---

**Description**

This functions allow the user to load [BIOMOD.stored.data](#) objects into memory.

**Usage**

```
load_stored_object(obj, ...)  
  
## S4 method for signature 'BIOMOD.stored.data'  
load_stored_object(obj, layer = 1)  
  
## S4 method for signature 'BIOMOD.stored.SpatRaster'  
load_stored_object(obj, layer = 1)
```

**Arguments**

|       |                                                                                            |
|-------|--------------------------------------------------------------------------------------------|
| obj   | a <a href="#">BIOMOD.stored.data</a> object                                                |
| ...   | additional arguments                                                                       |
| layer | an integer corresponding to the layer ID to be extracted when multilayer object considered |

**Author(s)**

Damien Georges

**See Also**

[BIOMOD.stored.data](#)

Other Toolbox functions: [getters.bm](#), [getters.out](#), [predict2.bm](#), [predict2.em](#), [setters](#)

---

ModelsTable*Single models package and functions*

---

**Description**

A data.frame containing for each single model available in **biomod2** the package and functions to be called.

**Usage**

ModelsTable

**Format**

A data.frame object with 12 rows and 5 variables:

**model** all single models that can be computed in **biomod2**

**type** data type associated to the models

**package** R package used

**func** function used in the R package

**train** function called by **caret** for the tuning

All single models available are the following :

- ANN ([nnet](#))
- CTA ([rpart](#))
- DNN ([cito](#))
- FDA ([fda](#))
- GAM ([gam](#), [gam](#) or [bam](#))
- GBM ([gbm](#))
- GLM ([glm](#))
- MARS ([earth](#))
- MAXENT ([see Maxent website](#))
- MAXNET ([maxnet](#))
- RF ([randomForest](#))
- RFd ([randomForest](#) downsampled)
- SRE ([bm\\_SRE](#))
- XGBOOST ([xgboost](#))

---

|       |                          |
|-------|--------------------------|
| ODMAP | <i>ODMAP empty table</i> |
|-------|--------------------------|

---

### Description

A data.frame containing ODMAP (Overview, Data, Model, Assessment, Prediction) protocol components.

### Usage

ODMAP

### Format

A data.frame object with 84 rows and 4 variables:

**section** Overview, Data, Model, Assessment or Prediction step

**subsection** corresponding field

**element** corresponding field

**value** to be filled with [BIOMOD\\_Report](#) function

---

|                |                                                               |
|----------------|---------------------------------------------------------------|
| OptionsBigboss | <i>Bigboss pre-defined parameter values for single models</i> |
|----------------|---------------------------------------------------------------|

---

### Description

A [BIOMOD.models.options](#) object containing for each single model available in **biomod2** the parameter values pre-defined by **biomod2** team.

### Usage

OptionsBigboss

### Format

A [BIOMOD.models.options](#) object with some changed values :

ANN.nnet.nnet • size = 5

- decay = 0.1
- trace = FALSE
- rang = 0.1
- maxit = 200

CTA.rpart.rpart • control = list(xval = 5, minbucket = 5, minsplit = 5, cp = 0.001, maxdepth = 10)

```

      • cost = NULL
DNN.cito.dnn    • batchsize = 100L
      • epochs = 150L
      • hidden = c(100L, 100L)
      • lr = 0.05
      • optimizer = "adam"
      • lambda = 0.001
      • alpha = 1.0
      • validation = 0.2
      • lr_scheduler = config_lr_scheduler("reduce_on_plateau", patience = 7)
      • early_stopping = 14
FDA.mda.fda
GAM.gam.gam
GAM.mgcv.bam
GAM.mgcv.gam    • method = 'GCV.Cp'
      • control = list(epsilon = 1e-06, trace = FALSE, maxit = 100)
GBM.gbm.gbm    • n.trees = 2500
      • interaction.depth = 7
      • n.minobsinnode = 5
      • shrinkage = 0.001
      • cv.folds = 3
      • keep.data = FALSE
      • n.cores = 1
GLM.stats.glm  • mustart = 0.5
      • control = glm.control(maxit = 50)
MARS.earth.earth • ncross = 0
      • nk = NULL
      • penalty = 2
      • thresh = 0.001
      • nprune = NULL
      • pmethod = 'backward'
MAXENT.MAXENT.MAXENT • path_to_maxent.jar = '.'
RF.randomForest.randomForest • ntree = 500
      • mtry = 2
      • sampsize = NULL
      • nodesize = 5
      • maxnodes = NULL
RFd.randomForest.randomForest • type = 'classification'
      • ntree = 500
      • mtry = 2
      • strata = factor(c(0, 1))

```

- `sampsize = NULL`
- `nodesize = 5`
- `maxnodes = NULL`

`SRE.biomod2.bm_SRE`    • `do.extrem = TRUE`

`XGB00ST.xgboost.xgb_train`    • `params = list(max_depth = 2, eta = 1, nthread = 2)`

- `nrounds = 4`

---

`plot, BIOMOD.formated.data, missing-method`

*plot      method      for      BIOMOD.formated.data      and*  
*BIOMOD.formated.data.PA object class*

---

## Description

Plot the spatial distribution of presences, absences and pseudo-absences among the different potential dataset (calibration, validation and evaluation). Available only if coordinates were given to [BIOMOD\\_FormatingData](#).

## Usage

```
## S4 method for signature 'BIOMOD.formated.data,missing'
plot(
  x,
  calib.lines = NULL,
  PA,
  run,
  plot.type,
  point.size = 1.5,
  plot.output,
  plot.valid = TRUE,
  plot.eval = TRUE,
  do.plot = TRUE,
  has.mask = FALSE,
  has.mask.eval = FALSE
)
```

## Arguments

|                          |                                                                                                                                                                                                                               |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>x</code>           | a <a href="#">BIOMOD.formated.data</a> or <a href="#">BIOMOD.formated.data.PA</a> object. Coordinates must be available to be able to use plot                                                                                |
| <code>calib.lines</code> | (optional, default <code>NULL</code> )<br>A data.frame object returned by <a href="#">get_calib_lines</a> or <a href="#">bm_CrossValidation</a> functions, to explore the distribution of calibration and validation datasets |
| <code>PA</code>          | (optional, default <code>'all'</code> )<br>If <code>x</code> is a <a href="#">BIOMOD.formated.data.PA</a> object, a vector containing pseudo-absence set to be represented                                                    |

|               |                                                                                                                                                                                                                                  |
|---------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| run           | (optional, default 'all')<br>If calib.lines is provided, a vector containing repetition set to be represented                                                                                                                    |
| plot.type     | a character defining how occurrences will be represented. Must be 'points' (default, better when using fine-grained data) or 'raster' (if environmental variables were given as a raster, better when using coarse-grained data) |
| point.size    | (optional, default 1.5)<br>If plot.type = 'points', a numeric to adjust the size of points                                                                                                                                       |
| plot.output   | a character defining whether to return a single facet with all plots or a list of individual plots, must be 'facet' (default) or list                                                                                            |
| plot.valid    | (optional, default TRUE)<br>A logical defining whether validation data should be separated on plot or not                                                                                                                        |
| plot.eval     | (optional, default TRUE)<br>A logical defining whether evaluation data should be added to the plot or not                                                                                                                        |
| do.plot       | (optional, default TRUE)<br>A logical defining whether the plot is to be rendered or not                                                                                                                                         |
| has.mask      | (optional, default FALSE)<br>A logical defining whether a mask for calibration data is available or not                                                                                                                          |
| has.mask.eval | (optional, default FALSE)<br>A logical defining whether a mask for evaluation data is available or not                                                                                                                           |

**Value**

a list with the data used to generate the plot and a ggplot2 object

**Author(s)**

Rémi Lemaire-Patin, Hélène Blancheteau

**Examples**

```
library(terra)

# Load species occurrences (6 species available)
data(DataSpecies)
head(DataSpecies)

# Select the name of the studied species
myRespName <- 'GuloGulo'

# Get corresponding presence/absence data
myResp <- as.numeric(DataSpecies[, myRespName])

# Get corresponding XY coordinates
myRespXY <- DataSpecies[, c('X_WGS84', 'Y_WGS84')]

# Load environmental variables extracted from BIOCLIM (bio_3, bio_4, bio_7, bio_11 & bio_12)
data(bioclim_current)
myExpl <- terra::rast(bioclim_current)
```

```
## ----- #
# Format Data with true absences
myBiomodData <- BIOMOD_FormatingData(resp.name = myRespName,
                                   resp.var = myResp,
                                   resp.xy = myRespXY,
                                   expl.var = myExpl)

myBiomodData
plot(myBiomodData)
```

---

**setters**

*Functions to change the place of the different biomod2 objects*

---

**Description**

This function allow the user to change the folder where the modelling of biomod2 have been done.

**Usage**

```
set_new_dirname(obj, new.dir.name)

## S4 method for signature 'BIOMOD.models.out'
set_new_dirname(obj, new.dir.name)

## S4 method for signature 'BIOMOD.ensemble.models.out'
set_new_dirname(obj, new.dir.name)

## S4 method for signature 'BIOMOD.projection.out'
set_new_dirname(obj, new.dir.name)
```

**Arguments**

|              |                                                                                                                                                                                                                   |
|--------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| obj          | a <a href="#">BIOMOD.formated.data</a> , <a href="#">BIOMOD.formated.data.PA</a> , <a href="#">BIOMOD.models.out</a> , <a href="#">BIOMOD.projection.out</a> or <a href="#">BIOMOD.ensemble.models.out</a> object |
| new.dir.name | a character corresponding to the new folder path                                                                                                                                                                  |

**Author(s)**

Hélène Blancheteau

**See Also**

[BIOMOD.models.out](#), [BIOMOD.projection.out](#), [BIOMOD.ensemble.models.out](#)

Other Toolbox functions: [getters.bm](#), [getters.out](#), [load\\_stored\\_object\(\)](#), [predict2.bm](#), [predict2.em](#)

---

summary,BIOMOD.formated.data-method

summary method for [BIOMOD.formated.data](#) object class

---

## Description

Summarize the number of presences, absences and pseudo-absences among the different potential dataset (calibration, validation and evaluation).

## Usage

```
## S4 method for signature 'BIOMOD.formated.data'
summary(object, calib.lines = NULL)
```

## Arguments

|             |                                                                                                                                                                                                             |
|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| object      | a <a href="#">BIOMOD.formated.data</a> or <a href="#">BIOMOD.formated.data.PA</a> object returned by the <a href="#">BIOMOD_FormatingData</a> function                                                      |
| calib.lines | (optional, default NULL)<br>an array object returned by <a href="#">get_calib_lines</a> or <a href="#">bm_CrossValidation</a> functions, to explore the distribution of calibration and validation datasets |

## Value

a data.frame

## Author(s)

Rémi Lemaire-Patin

## Examples

```
library(terra)

# Load species occurrences (6 species available)
data(DataSpecies)
head(DataSpecies)

# Select the name of the studied species
myRespName <- 'GuloGulo'

# Get corresponding presence/absence data
myResp <- as.numeric(DataSpecies[, myRespName])

# Get corresponding XY coordinates
myRespXY <- DataSpecies[, c('X_WGS84', 'Y_WGS84')]

# Load environmental variables extracted from BIOCLIM (bio_3, bio_4, bio_7, bio_11 & bio_12)
```

```
data(bioclim_current)
myExpl <- terra::rast(bioclim_current)

## ----- #
# Format Data with true absences
myBiomodData <- BIOMOD_FormatingData(resp.name = myRespName,
                                     resp.var = myResp,
                                     resp.xy = myRespXY,
                                     expl.var = myExpl)

myBiomodData
summary(myBiomodData)
```

# Index

- \* **ANN**
  - bm\_RunModelsLoop, 110
- \* **CTA**
  - bm\_RunModelsLoop, 110
- \* **DNN**
  - bm\_RunModelsLoop, 110
- \* **FDA**
  - bm\_RunModelsLoop, 110
- \* **GAM**
  - bm\_RunModelsLoop, 110
- \* **GBM**
  - bm\_RunModelsLoop, 110
- \* **GLM**
  - bm\_RunModelsLoop, 110
- \* **MARS**
  - bm\_RunModelsLoop, 110
- \* **MAXENT**
  - bm\_RunModelsLoop, 110
- \* **Main functions**
  - BIOMOD\_EnsembleForecasting, 27
  - BIOMOD\_EnsembleModeling, 31
  - BIOMOD\_FormatingData, 38
  - BIOMOD\_LoadModels, 45
  - BIOMOD\_Modeling, 48
  - BIOMOD\_Projection, 54
  - BIOMOD\_RangeSize, 58
- \* **ODMAP**
  - BIOMOD\_Report, 62
- \* **Pearson**
  - bm\_VariablesImportance, 123
- \* **Plot functions**
  - bm\_ModelAnalysis, 80
  - bm\_PlotEvalBoxplot, 87
  - bm\_PlotEvalMean, 89
  - bm\_PlotRangeSize, 92
  - bm\_PlotResponseCurves, 95
  - bm\_PlotVarImpBoxplot, 99
- \* **Primary functions**
  - BIOMOD\_Report, 62
- \* **RF**
  - bm\_RunModelsLoop, 110
- \* **SRE**
  - bm\_PseudoAbsences, 101
  - bm\_RunModelsLoop, 110
- \* **Secondary functions**
  - bm\_BinaryTransformation, 68
  - bm\_CrossValidation, 70
  - bm\_FindOptimStat, 76
  - bm\_MakeFormula, 79
  - bm\_ModelAnalysis, 80
  - bm\_ModelingOptions, 83
  - bm\_PlotEvalBoxplot, 87
  - bm\_PlotEvalMean, 89
  - bm\_PlotRangeSize, 92
  - bm\_PlotResponseCurves, 95
  - bm\_PlotVarImpBoxplot, 99
  - bm\_PseudoAbsences, 101
  - bm\_RangeSize, 106
  - bm\_RunModelsLoop, 110
  - bm\_SampleBinaryVector, 113
  - bm\_SampleFactorLevels, 114
  - bm\_SRE, 116
  - bm\_Tuning, 118
  - bm\_VariablesImportance, 123
- \* **Toolbox functions**
  - getters.bm, 127
  - getters.out, 128
  - load\_stored\_object, 134
  - setters, 140
- \* **Toolbox objects**
  - BIOMOD.ensemble.models.out, 4
  - BIOMOD.formated.data, 7
  - BIOMOD.formated.data.PA, 11
  - BIOMOD.models.options, 16
  - BIOMOD.models.out, 17
  - BIOMOD.options.dataset, 19
  - BIOMOD.options.default, 21
  - BIOMOD.projection.out, 22

- BIOMOD.rangesize.out, 25
- BIOMOD.stored.data, 26
- biomod2\_ensemble\_model, 65
- biomod2\_model, 67
- \* **XGBOOST**
  - bm\_RunModelsLoop, 110
- \* **analyze**
  - bm\_ModelAnalysis, 80
- \* **auc**
  - bm\_FindOptimStat, 76
- \* **binary**
  - bm\_BinaryTransformation, 68
  - bm\_SampleBinaryVector, 113
- \* **boxplot**
  - bm\_PlotEvalBoxplot, 87
  - bm\_PlotVarImpBoxplot, 99
- \* **boyce**
  - bm\_FindOptimStat, 76
- \* **convert**
  - bm\_BinaryTransformation, 68
- \* **curve**
  - bm\_PlotResponseCurves, 95
- \* **datasets**
  - bioclim\_current, 3
  - bioclim\_future, 4
  - DataSpecies, 125
  - DataSTOC, 126
  - ModelsTable, 135
  - ODMAP, 136
  - OptionsBigboss, 136
- \* **dataset**
  - BIOMOD\_FormatingData, 38
- \* **disk**
  - bm\_PseudoAbsences, 101
- \* **ensemble**
  - BIOMOD\_EnsembleModeling, 31
- \* **evaluation**
  - BIOMOD\_FormatingData, 38
  - bm\_FindOptimStat, 76
  - bm\_PlotEvalBoxplot, 87
  - bm\_PlotEvalMean, 89
  - bm\_PlotVarImpBoxplot, 99
- \* **factor**
  - bm\_SampleFactorLevels, 114
- \* **filter**
  - bm\_BinaryTransformation, 68
- \* **format**
  - BIOMOD\_FormatingData, 38

- \* **formula**
  - bm\_MakeFormula, 79
  - bm\_RunModelsLoop, 110
- \* **gain**
  - BIOMOD\_RangeSize, 58
  - bm\_PlotRangeSize, 92
  - bm\_RangeSize, 106
- \* **ggplot**
  - bm\_PlotEvalBoxplot, 87
  - bm\_PlotEvalMean, 89
  - bm\_PlotRangeSize, 92
  - bm\_PlotResponseCurves, 95
  - bm\_PlotVarImpBoxplot, 99
- \* **html**
  - BIOMOD\_Report, 62
- \* **importance**
  - bm\_VariablesImportance, 123
- \* **loss**
  - BIOMOD\_RangeSize, 58
  - bm\_PlotRangeSize, 92
  - bm\_RangeSize, 106
- \* **markdown**
  - BIOMOD\_Report, 62
- \* **models**
  - BIOMOD\_EnsembleForecasting, 27
  - BIOMOD\_EnsembleModeling, 31
  - BIOMOD\_Modeling, 48
  - BIOMOD\_Projection, 54
  - bm\_FindOptimStat, 76
  - bm\_MakeFormula, 79
  - bm\_ModelAnalysis, 80
  - bm\_ModelingOptions, 83
  - bm\_RunModelsLoop, 110
  - bm\_SRE, 116
- \* **mpa**
  - bm\_FindOptimStat, 76
- \* **multivariate**
  - BIOMOD\_Modeling, 48
- \* **nonlinear**
  - BIOMOD\_Modeling, 48
- \* **nonparametric**
  - BIOMOD\_Modeling, 48
- \* **options**
  - bm\_FindOptimStat, 76
  - bm\_MakeFormula, 79
  - bm\_ModelingOptions, 83
  - bm\_RunModelsLoop, 110
- \* **projections**

- BIOMOD\_RangeSize, 58
- bm\_PlotRangeSize, 92
- bm\_RangeSize, 106
- \* **projection**
  - BIOMOD\_EnsembleForecasting, 27
  - BIOMOD\_Projection, 54
- \* **pseudo-absence**
  - BIOMOD\_FormatingData, 38
  - bm\_PseudoAbsences, 101
- \* **quantile**
  - bm\_SRE, 116
- \* **random**
  - bm\_PseudoAbsences, 101
  - bm\_VariablesImportance, 123
- \* **range**
  - BIOMOD\_RangeSize, 58
  - bm\_PlotRangeSize, 92
  - bm\_RangeSize, 106
  - bm\_SRE, 116
- \* **regression**
  - BIOMOD\_Modeling, 48
- \* **report**
  - BIOMOD\_Report, 62
- \* **residuals**
  - bm\_ModelAnalysis, 80
- \* **response**
  - bm\_PlotResponseCurves, 95
- \* **sample**
  - bm\_SampleBinaryVector, 113
  - bm\_SampleFactorLevels, 114
- \* **shuffle**
  - bm\_VariablesImportance, 123
- \* **species**
  - BIOMOD\_RangeSize, 58
  - bm\_PlotRangeSize, 92
  - bm\_RangeSize, 106
- \* **sre**
  - bm\_SRE, 116
- \* **surface**
  - bm\_SRE, 116
- \* **threshold**
  - bm\_BinaryTransformation, 68
- \* **tree**
  - BIOMOD\_Modeling, 48
- \* **tss**
  - bm\_FindOptimStat, 76
- \* **weights**
  - BIOMOD\_EnsembleModeling, 31
- ANN\_biomod2\_model-class
  - (biomod2\_model), 67
- bam, 50, 53, 135
- bioclim\_current, 3
- bioclim\_future, 4
- BIOMOD.ensemble.models.out, 4, 5, 10, 15, 16, 18, 20, 22, 23, 25–27, 36, 45, 62, 66, 68, 87, 88, 90, 91, 95–97, 99, 100, 128, 131, 133, 134, 140
- BIOMOD.ensemble.models.out-class
  - (BIOMOD.ensemble.models.out), 4
- BIOMOD.formated.data, 7, 9, 20, 26, 43, 49, 62, 63, 71, 83, 111, 120, 131, 132, 138, 140, 141
- BIOMOD.formated.data(), 5, 15, 16, 18, 20, 22, 23, 25, 26, 66, 68
- BIOMOD.formated.data,data.frame,ANY-method
  - (BIOMOD.formated.data), 7
- BIOMOD.formated.data,numeric,data.frame-method
  - (BIOMOD.formated.data), 7
- BIOMOD.formated.data,numeric,matrix-method
  - (BIOMOD.formated.data), 7
- BIOMOD.formated.data,numeric,SpatRaster-method
  - (BIOMOD.formated.data), 7
- BIOMOD.formated.data-class
  - (BIOMOD.formated.data), 7
- BIOMOD.formated.data.PA, 11, 20, 43, 49, 62, 71, 83, 104, 111, 120, 131, 132, 138, 140, 141
- BIOMOD.formated.data.PA(), 5, 10, 16, 18, 20, 22, 23, 25, 26, 66, 68
- BIOMOD.formated.data.PA,numeric,data.frame-method
  - (BIOMOD.formated.data.PA), 11
- BIOMOD.formated.data.PA,numeric,SpatRaster-method
  - (BIOMOD.formated.data.PA), 11
- BIOMOD.formated.data.PA-class
  - (BIOMOD.formated.data.PA), 11
- BIOMOD.models.options, 5, 10, 15, 16, 16, 18, 20, 22, 23, 25, 26, 50, 51, 66, 68, 84, 85, 111, 121, 136
- BIOMOD.models.options-class
  - (BIOMOD.models.options), 16
- BIOMOD.models.out, 5, 10, 15, 16, 17, 17, 20, 22, 23, 25, 26, 32, 45, 52, 55, 62, 66, 68, 81, 87, 88, 90, 91, 95–97, 99, 100, 128, 131, 133, 134, 140
- BIOMOD.models.out-class
  - (BIOMOD.models.out), 17

- BIOMOD.options.dataset, [16](#), [19](#), [20](#), [22](#), [51](#), [119](#)
- BIOMOD.options.dataset(), [5](#), [10](#), [15](#), [16](#), [18](#), [22](#), [23](#), [25](#), [26](#), [66](#), [68](#)
- BIOMOD.options.dataset, character-method (BIOMOD.options.dataset), [19](#)
- BIOMOD.options.dataset-class (BIOMOD.options.dataset), [19](#)
- BIOMOD.options.default, [16](#), [20](#), [21](#), [119](#)
- BIOMOD.options.default(), [5](#), [10](#), [15](#), [16](#), [18](#), [20](#), [23](#), [25](#), [26](#), [66](#), [68](#)
- BIOMOD.options.default, character-method (BIOMOD.options.default), [21](#)
- BIOMOD.options.default-class (BIOMOD.options.default), [21](#)
- BIOMOD.projection.out, [5](#), [10](#), [15](#), [16](#), [18](#), [20](#), [22](#), [23](#), [25](#)–[27](#), [29](#), [57](#), [66](#), [68](#), [128](#), [131](#), [133](#), [134](#), [140](#)
- BIOMOD.projection.out-class (BIOMOD.projection.out), [22](#)
- BIOMOD.rangesize.out, [5](#), [10](#), [15](#), [16](#), [18](#), [20](#), [22](#), [23](#), [25](#), [26](#), [66](#), [68](#)
- BIOMOD.rangesize.out-class (BIOMOD.rangesize.out), [25](#)
- BIOMOD.stored.data, [5](#), [10](#), [15](#), [16](#), [18](#), [20](#), [22](#), [23](#), [25](#), [26](#), [66](#), [68](#), [133](#), [134](#)
- BIOMOD.stored.data-class (BIOMOD.stored.data), [26](#)
- BIOMOD.stored.data.frame-class (BIOMOD.stored.data), [26](#)
- BIOMOD.stored.files-class (BIOMOD.stored.data), [26](#)
- BIOMOD.stored.formated.data-class (BIOMOD.stored.data), [26](#)
- BIOMOD.stored.models.out-class (BIOMOD.stored.data), [26](#)
- BIOMOD.stored.options-class (BIOMOD.stored.data), [26](#)
- BIOMOD.stored.SpatRaster-class (BIOMOD.stored.data), [26](#)
- biomod2\_ensemble\_model, [5](#), [10](#), [15](#), [16](#), [18](#), [20](#), [22](#), [23](#), [25](#), [26](#), [65](#), [65](#), [68](#)
- biomod2\_ensemble\_model-class (biomod2\_ensemble\_model), [65](#)
- biomod2\_model, [5](#), [10](#), [15](#), [16](#), [18](#), [20](#), [22](#), [23](#), [25](#), [26](#), [66](#), [67](#), [67](#), [127](#), [128](#)
- biomod2\_model-class (biomod2\_model), [67](#)
- BIOMOD\_EnsembleForecasting, [4](#), [22](#), [23](#), [26](#), [27](#), [36](#), [56](#), [60](#), [70](#), [108](#)
- BIOMOD\_EnsembleForecasting(), [36](#), [43](#), [47](#), [53](#), [57](#), [60](#)
- BIOMOD\_EnsembleModeling, [4](#), [5](#), [17](#), [18](#), [26](#)–[29](#), [31](#), [45](#)–[47](#), [53](#), [57](#), [62](#), [65](#), [66](#), [78](#), [87](#), [88](#), [90](#), [91](#), [95](#)–[97](#), [99](#), [100](#), [124](#)
- BIOMOD\_EnsembleModeling(), [29](#), [43](#), [47](#), [53](#), [57](#), [60](#)
- BIOMOD\_FormatingData, [7](#), [10](#), [11](#), [15](#), [17](#), [20](#), [28](#), [29](#), [34](#), [36](#), [38](#), [49](#)–[53](#), [55](#), [62](#), [71](#), [74](#), [83](#), [84](#), [96](#), [104](#), [111](#), [117](#), [120](#), [133](#), [138](#), [141](#)
- BIOMOD\_FormatingData(), [29](#), [36](#), [47](#), [53](#), [57](#), [60](#)
- BIOMOD\_LoadModels, [4](#), [5](#), [17](#), [18](#), [45](#)
- BIOMOD\_LoadModels(), [29](#), [36](#), [43](#), [53](#), [57](#), [60](#)
- BIOMOD\_Modeling, [5](#), [7](#), [10](#), [11](#), [15](#)–[22](#), [26](#), [29](#), [31](#)–[34](#), [36](#), [42](#), [43](#), [45](#)–[47](#), [48](#), [52](#), [54](#), [55](#), [57](#), [62](#), [67](#), [68](#), [74](#), [78](#), [81](#), [84](#), [85](#), [87](#), [88](#), [90](#), [91](#), [95](#)–[97](#), [99](#), [100](#), [110](#), [113](#), [117](#), [121](#), [124](#), [133](#)
- BIOMOD\_Modeling(), [29](#), [36](#), [43](#), [47](#), [57](#), [60](#)
- BIOMOD\_PresenceOnly, [4](#), [5](#), [17](#), [18](#)
- BIOMOD\_Projection, [17](#), [18](#), [22](#), [23](#), [26](#), [27](#), [53](#), [54](#), [60](#), [70](#), [84](#), [108](#)
- BIOMOD\_Projection(), [29](#), [36](#), [43](#), [47](#), [53](#), [60](#)
- BIOMOD\_RangeSize, [25](#), [29](#), [57](#), [58](#), [92](#), [93](#)
- BIOMOD\_RangeSize(), [29](#), [36](#), [43](#), [47](#), [53](#), [57](#)
- BIOMOD\_Report, [61](#), [136](#)
- bm\_BinaryTransformation, [68](#)
- bm\_BinaryTransformation(), [74](#), [78](#), [80](#), [81](#), [85](#), [88](#), [91](#), [93](#), [97](#), [100](#), [104](#), [108](#), [113](#)–[115](#), [117](#), [121](#), [124](#)
- bm\_BinaryTransformation, data.frame-method (bm\_BinaryTransformation), [68](#)
- bm\_BinaryTransformation, matrix-method (bm\_BinaryTransformation), [68](#)
- bm\_BinaryTransformation, numeric-method (bm\_BinaryTransformation), [68](#)
- bm\_BinaryTransformation, SpatRaster-method (bm\_BinaryTransformation), [68](#)
- bm\_CalculateStatAbun (bm\_FindOptimStat), [76](#)
- bm\_CalculateStatAbund (bm\_FindOptimStat), [76](#)
- bm\_CalculateStatBin (bm\_FindOptimStat), [76](#)

- bm\_CrossValidation, [7](#), [10](#), [11](#), [15](#), [20](#), [36](#),  
[42](#), [51](#), [53](#), [70](#), [83](#), [111](#), [115](#), [120](#),  
[138](#), [141](#)
- bm\_CrossValidation(), [70](#), [78](#), [80](#), [81](#), [85](#),  
[88](#), [91](#), [93](#), [97](#), [100](#), [104](#), [108](#),  
[113–115](#), [117](#), [121](#), [124](#)
- bm\_CrossValidation\_block  
(bm\_CrossValidation), [70](#)
- bm\_CrossValidation\_block, BIOMOD.formated.data-method  
(bm\_CrossValidation), [70](#)
- bm\_CrossValidation\_block, BIOMOD.formated.data.PA-method  
(bm\_CrossValidation), [70](#)
- bm\_CrossValidation\_env  
(bm\_CrossValidation), [70](#)
- bm\_CrossValidation\_env, BIOMOD.formated.data-method  
(bm\_CrossValidation), [70](#)
- bm\_CrossValidation\_env, BIOMOD.formated.data.PA-method  
(bm\_CrossValidation), [70](#)
- bm\_CrossValidation\_kfold  
(bm\_CrossValidation), [70](#)
- bm\_CrossValidation\_kfold, BIOMOD.formated.data-method  
(bm\_CrossValidation), [70](#)
- bm\_CrossValidation\_kfold, BIOMOD.formated.data.PA-method  
(bm\_CrossValidation), [70](#)
- bm\_CrossValidation\_random  
(bm\_CrossValidation), [70](#)
- bm\_CrossValidation\_random, BIOMOD.formated.data-method  
(bm\_CrossValidation), [70](#)
- bm\_CrossValidation\_random, BIOMOD.formated.data.PA-method  
(bm\_CrossValidation), [70](#)
- bm\_CrossValidation\_strat  
(bm\_CrossValidation), [70](#)
- bm\_CrossValidation\_strat, BIOMOD.formated.data-method  
(bm\_CrossValidation), [70](#)
- bm\_CrossValidation\_strat, BIOMOD.formated.data.PA-method  
(bm\_CrossValidation), [70](#)
- bm\_CrossValidation\_user.defined  
(bm\_CrossValidation), [70](#)
- bm\_CrossValidation\_user.defined, BIOMOD.formated.data-method  
(bm\_CrossValidation), [70](#)
- bm\_CrossValidation\_user.defined, BIOMOD.formated.data.PA-method  
(bm\_CrossValidation), [70](#)
- bm\_FindOptimStat, [76](#), [112](#), [113](#)
- bm\_FindOptimStat(), [70](#), [74](#), [80](#), [81](#), [85](#), [88](#),  
[91](#), [93](#), [97](#), [100](#), [104](#), [108](#), [113–115](#),  
[117](#), [121](#), [124](#)
- bm\_MakeFormula, [79](#), [113](#)
- bm\_MakeFormula(), [70](#), [74](#), [78](#), [81](#), [85](#), [88](#), [91](#),  
[93](#), [97](#), [100](#), [104](#), [108](#), [113–115](#), [117](#),  
[121](#), [124](#)
- bm\_ModelAnalysis, [80](#)
- bm\_ModelAnalysis(), [70](#), [74](#), [78](#), [80](#), [85](#), [88](#),  
[91](#), [93](#), [97](#), [100](#), [104](#), [108](#), [113–115](#),  
[117](#), [121](#), [124](#)
- bm\_ModelingOptions, [16](#), [17](#), [19–22](#), [29](#), [36](#),  
[50](#), [51](#), [53](#), [80](#), [83](#), [111](#), [113](#), [117](#),  
[119](#), [121](#)
- bm\_ModelingOptions(), [70](#), [74](#), [78](#), [80](#), [81](#),  
[88](#), [91](#), [93](#), [97](#), [100](#), [104](#), [108](#),  
[113–115](#), [117](#), [121](#), [124](#)
- bm\_PlotEvalBoxplot, [5](#), [18](#), [36](#), [53](#), [87](#)
- bm\_PlotEvalBoxplot(), [70](#), [74](#), [78](#), [80](#), [81](#),  
[85](#), [91](#), [93](#), [97](#), [100](#), [104](#), [108](#),  
[113–115](#), [117](#), [121](#), [124](#)
- bm\_PlotEvalMean, [5](#), [18](#), [36](#), [53](#), [89](#)
- bm\_PlotEvalMean(), [70](#), [74](#), [78](#), [80](#), [81](#), [85](#),  
[88](#), [93](#), [97](#), [100](#), [104](#), [108](#), [113–115](#),  
[117](#), [121](#), [124](#)
- bm\_PlotRangeSize, [25](#), [60](#), [92](#), [108](#)
- bm\_PlotRangeSize(), [70](#), [74](#), [78](#), [80](#), [81](#), [85](#),  
[88](#), [91](#), [97](#), [100](#), [104](#), [108](#), [113–115](#),  
[117](#), [121](#), [124](#)
- bm\_PlotResponseCurves, [5](#), [18](#), [36](#), [53](#), [95](#)
- bm\_PlotResponseCurves(), [70](#), [74](#), [78](#), [80](#),  
[81](#), [85](#), [88](#), [91](#), [93](#), [100](#), [104](#), [108](#),  
[113–115](#), [117](#), [121](#), [124](#)
- bm\_PlotVarImpBoxplot, [5](#), [18](#), [36](#), [53](#), [99](#), [124](#)
- bm\_PlotVarImpBoxplot(), [70](#), [74](#), [78](#), [80](#), [81](#),  
[85](#), [88](#), [91](#), [93](#), [97](#), [104](#), [108](#),  
[113–115](#), [117](#), [121](#), [124](#)
- bm\_PseudoAbsences, [14](#), [15](#), [41–43](#), [101](#), [115](#),  
[117](#)
- bm\_PseudoAbsences(), [70](#), [74](#), [78](#), [80](#), [81](#), [85](#),  
[88](#), [91](#), [93](#), [97](#), [100](#), [108](#), [113–115](#),  
[117](#), [121](#), [124](#)
- bm\_PseudoAbsences\_disk  
(bm\_PseudoAbsences), [101](#)
- bm\_PseudoAbsences\_disk, ANY, SpatRaster-method  
(bm\_PseudoAbsences), [101](#)
- bm\_PseudoAbsences\_disk, ANY, SpatVector-method  
(bm\_PseudoAbsences), [101](#)
- bm\_PseudoAbsences\_random  
(bm\_PseudoAbsences), [101](#)
- bm\_PseudoAbsences\_random, ANY, SpatRaster-method  
(bm\_PseudoAbsences), [101](#)
- bm\_PseudoAbsences\_random, ANY, SpatVector-method

- (bm\_PseudoAbsences), 101
- bm\_PseudoAbsences\_sre
  - (bm\_PseudoAbsences), 101
- bm\_PseudoAbsences\_sre, ANY, SpatRaster-method
  - (bm\_PseudoAbsences), 101
- bm\_PseudoAbsences\_sre, ANY, SpatVector-method
  - (bm\_PseudoAbsences), 101
- bm\_PseudoAbsences\_user.defined
  - (bm\_PseudoAbsences), 101
- bm\_PseudoAbsences\_user.defined, ANY, SpatRaster-method
  - (bm\_PseudoAbsences), 101
- bm\_PseudoAbsences\_user.defined, ANY, SpatVector-method
  - (bm\_PseudoAbsences), 101
- bm\_RangeSize, 93, 106
- bm\_RangeSize(), 70, 74, 78, 80, 81, 85, 88, 91, 93, 97, 100, 104, 113–115, 118, 121, 124
- bm\_RangeSize, data.frame, data.frame-method
  - (bm\_RangeSize), 106
- bm\_RangeSize, SpatRaster, SpatRaster-method
  - (bm\_RangeSize), 106
- bm\_RunModel, 67, 68
- bm\_RunModel (bm\_RunModelsLoop), 110
- bm\_RunModelsLoop, 10, 15, 20, 22, 78, 80, 110, 117, 124
- bm\_RunModelsLoop(), 70, 74, 78, 80, 81, 85, 88, 91, 93, 97, 100, 104, 108, 114, 115, 118, 121, 124
- bm\_SampleBinaryVector, 113
- bm\_SampleBinaryVector(), 70, 74, 78, 80, 81, 85, 88, 91, 93, 97, 100, 104, 108, 113, 115, 118, 121, 124
- bm\_SampleFactorLevels, 113, 114
- bm\_SampleFactorLevels(), 70, 74, 78, 80, 81, 85, 88, 91, 93, 97, 100, 104, 108, 113, 114, 118, 121, 124
- bm\_SRE, 42, 51, 103, 104, 116, 121, 135
- bm\_SRE(), 70, 74, 78, 80, 81, 85, 88, 91, 93, 97, 100, 104, 108, 113–115, 121, 124
- bm\_Tuning, 7, 10, 11, 15, 16, 20, 22, 51, 53, 80, 84, 85, 117, 118
- bm\_Tuning(), 70, 74, 78, 80, 81, 85, 88, 91, 93, 97, 100, 104, 108, 113–115, 118, 124
- bm\_VariablesImportance, 5, 18, 36, 52, 53, 112, 113, 123
- bm\_VariablesImportance(), 70, 74, 78, 80, 81, 85, 88, 91, 93, 97, 100, 104, 108, 113–115, 118, 121
- cito, 50, 53, 135
- CTA\_biomod2\_model-class
  - (biomod2\_model), 67
- DataSpecies, 125
- DataSTOC, 126
- DNN\_biomod2\_model-class
  - (biomod2\_model), 67
- earth, 51, 53, 113, 135
- EMca\_biomod2\_model-class
  - (biomod2\_ensemble\_model), 65
- EMci\_biomod2\_model-class
  - (biomod2\_ensemble\_model), 65
- EMcv\_biomod2\_model-class
  - (biomod2\_ensemble\_model), 65
- EMfreq\_biomod2\_model-class
  - (biomod2\_ensemble\_model), 65
- EMmean\_biomod2\_model-class
  - (biomod2\_ensemble\_model), 65
- EMmedian\_biomod2\_model-class
  - (biomod2\_ensemble\_model), 65
- EMmode\_biomod2\_model-class
  - (biomod2\_ensemble\_model), 65
- EMwmean\_biomod2\_model-class
  - (biomod2\_ensemble\_model), 65
- ENMevaluate, 121
- expand.grid, 121
- facet\_wrap, 23, 88
- fda, 50, 53, 113, 135
- FDA\_biomod2\_model-class
  - (biomod2\_model), 67
- formalArgs, 84
- formals, 84
- formula, 80
- free (getters.out), 128
- free, BIOMOD.projection.out-method
  - (getters.out), 128
- gam, 50, 53, 135
- GAM\_biomod2\_model-class
  - (biomod2\_model), 67
- gbm, 51, 53, 113, 135
- GBM\_biomod2\_model-class
  - (biomod2\_model), 67
- geom\_point, 23

- `get.block`, 74
- `get_built_models`, 28, 32, 33, 46, 55, 81, 96, 131
- `get_built_models (getters.out)`, 128
- `get_built_models, BIOMOD.ensemble.models.out-method` (getters.out), 128
- `get_built_models, BIOMOD.models.out-method` (getters.out), 128
- `get_calib_lines`, 20, 83, 120, 138, 141
- `get_calib_lines (getters.out)`, 128
- `get_calib_lines, BIOMOD.models.out-method` (getters.out), 128
- `get_eval_data (getters.out)`, 128
- `get_eval_data, BIOMOD.formated.data-method` (getters.out), 128
- `get_evaluations`, 52, 88, 90, 91
- `get_evaluations (getters.out)`, 128
- `get_evaluations, BIOMOD.ensemble.models.out-method` (getters.out), 128
- `get_evaluations, BIOMOD.models.out-method` (getters.out), 128
- `get_formal_data`, 132
- `get_formal_data (getters.out)`, 128
- `get_formal_data, BIOMOD.ensemble.models.out-method` (getters.out), 128
- `get_formal_data, BIOMOD.models.out-method` (getters.out), 128
- `get_formal_model`, 123
- `get_formal_model (getters.bm)`, 127
- `get_formal_model, biomod2_model-method` (getters.bm), 127
- `get_kept_models (getters.out)`, 128
- `get_kept_models, BIOMOD.ensemble.models.out-method` (getters.out), 128
- `get_optim_value`, 51, 77
- `get_optim_value (bm_FindOptimStat)`, 76
- `get_options (getters.out)`, 128
- `get_options, BIOMOD.models.out-method` (getters.out), 128
- `get_predictions`, 23, 132
- `get_predictions (getters.out)`, 128
- `get_predictions, BIOMOD.ensemble.models.out-method` (getters.out), 128
- `get_predictions, BIOMOD.models.out-method` (getters.out), 128
- `get_predictions, BIOMOD.projection.out-method` (getters.out), 128
- `get_projected_models`, 59
- `get_projected_models (getters.out)`, 128
- `get_projected_models, BIOMOD.projection.out-method` (getters.out), 128
- `get_scaling_model (getters.bm)`, 127
- `get_scaling_model, biomod2_model-method` (getters.bm), 127
- `get_species_data (getters.out)`, 128
- `get_species_data, BIOMOD.formated.data-method` (getters.out), 128
- `get_species_data, BIOMOD.formated.data.PA-method` (getters.out), 128
- `get_variables_importance`, 100, 124
- `get_variables_importance (getters.out)`, 128
- `get_variables_importance, BIOMOD.ensemble.models.out-method` (getters.out), 128
- `get_variables_importance, BIOMOD.models.out-method` (getters.out), 128
- `getModelInfo`, 120
- `getters.bm`, 127, 134, 140
- `getters.out`, 128, 128, 134, 140
- `glm`, 51, 53, 135
- `GLM_biomod2_model-class` (biomod2\_model), 67
- `kfold`, 74
- `load`, 36, 53
- `load_stored_object`, 134
- `load_stored_object()`, 128, 134, 140
- `load_stored_object, BIOMOD.stored.data-method` (load\_stored\_object), 134
- `load_stored_object, BIOMOD.stored.SpatRaster-method` (load\_stored\_object), 134
- `mars`, 113
- `MARS_biomod2_model-class` (biomod2\_model), 67
- `match.call`, 63
- `MAXENT_biomod2_model-class` (biomod2\_model), 67
- `maxnet`, 51, 53, 113, 135
- `MAXNET_biomod2_model-class` (biomod2\_model), 67
- `ModelsTable`, 84, 85, 119, 121, 135
- `nnet`, 50, 53, 113, 135
- `ODMAP`, 63, 136

- OptionsBigboss, [51](#), [84](#), [85](#), [136](#)
- PackedSpatRaster, [26](#)
- plot, [23](#)
- plot, BIOMOD.formated.data, missing-method, [138](#)
- plot, BIOMOD.projection.out, missing-method (BIOMOD.projection.out), [22](#)
- predict2.bm, [128](#), [134](#), [140](#)
- predict2.em, [128](#), [134](#), [140](#)
- print, BIOMOD.models.options-method (BIOMOD.models.options), [16](#)
- print, BIOMOD.options.dataset-method (BIOMOD.options.dataset), [19](#)
- prune, [113](#)
- randomForest, [51](#), [53](#), [113](#), [124](#), [135](#)
- RasterLayer, [107](#)
- RF\_biomod2\_model-class (biomod2\_model), [67](#)
- RFd\_biomod2\_model-class (biomod2\_model), [67](#)
- rpart, [50](#), [53](#), [113](#), [135](#)
- s, [79](#), [80](#)
- set\_new\_dirname (setters), [140](#)
- set\_new\_dirname, BIOMOD.ensemble.models.out-method (setters), [140](#)
- set\_new\_dirname, BIOMOD.models.out-method (setters), [140](#)
- set\_new\_dirname, BIOMOD.projection.out-method (setters), [140](#)
- setters, [128](#), [134](#), [140](#)
- show, BIOMOD.ensemble.models.out-method (BIOMOD.ensemble.models.out), [4](#)
- show, BIOMOD.formated.data-method (BIOMOD.formated.data), [7](#)
- show, BIOMOD.models.options-method (BIOMOD.models.options), [16](#)
- show, BIOMOD.models.out-method (BIOMOD.models.out), [17](#)
- show, BIOMOD.options.dataset-method (BIOMOD.options.dataset), [19](#)
- show, BIOMOD.projection.out-method (BIOMOD.projection.out), [22](#)
- show, biomod2\_ensemble\_model-method (biomod2\_ensemble\_model), [65](#)
- show, biomod2\_model-method (biomod2\_model), [67](#)
- SpatialPoints, [102](#)
- SpatialPointsDataFrame, [102](#), [103](#)
- SpatRaster, [3](#), [4](#), [9](#), [10](#), [12–14](#), [28](#), [29](#), [39–42](#), [55–57](#), [69](#), [76](#), [96](#), [103](#), [107](#), [114–117](#)
- SpatVector, [8](#), [9](#), [12](#), [13](#), [39–42](#), [76](#), [116](#)
- SRE\_biomod2\_model-class (biomod2\_model), [67](#)
- summary, BIOMOD.formated.data-method, [141](#)
- train, [20](#), [119](#), [121](#)
- trainControl, [120](#), [121](#)
- tune, [121](#)
- xgboost, [51](#), [53](#), [113](#), [135](#)
- XGBOOST\_biomod2\_model-class (biomod2\_model), [67](#)